

Index

- 5G, 1
64 QAM, 139
6G, 1
air mass, 23
ambient backscattering, 173
ambient electromagnetic energy, 110
antenna far-field, 122
antenna oscillator, 105
ASTM, 23
backscatter communication, 170
battery, 158
 C-rate, 160
 capacity, 160
Bequerel, E., 21
bimorph, 53
Bode and Fano, 124
boost converter, 148
Brown, W. C., 99
cantilever, 53
capacitor, inkjet printed, 17
carbon nanotube, 15
Carnot efficiency, 64
characteristic equation, 94
class-F
 rectifier, 105
CMOS, 163
coefficient
 Peltier, 59
 Seebeck, 59
 Thomson, 60
coffee ring, 15
coil
 misalignment, 87
Colpitts oscillator, 138
complementary cumulative distribution function (CCDF), 135
conduction, 61
continuous conduction mode (CCM), 148
continuous wave, 135
convection, 61
conversion efficiency, 117
coupled resonator theory, 84
coupling coefficient, 52, 80, 87
cross-linking, 15
 heat, 15
 UV, 15
current responsivity, 114
damping factor, 50
detailed balance limit, 26, 31
Dickinson, 99
diode
 breakdown voltage, 116
diode rectifier, 101
discontinuous conduction mode (DCM), 148, 152
efficiency
 amplifier, 75
 aperture, 76
 rectifier, 76
efficiency, TEG, 64
electric generator model, 47
electromagnetic interference, 98
energy harvester
 piezoelectric, 53
energy harvesting
 electromagnetic, 110
 kinetic, 44
 RF, 76
 solar, 21
energy storage, 142, 158
figure of merit, thermoelectric material, 67, 68
fill factor, 32
Fourier's law, 62
generation, solar cell, 22
Glaser, 99
Goldstone, 99
graphene, 15
Hamill, 105
harmonic balance, 122, 127
heat diffusion equation, 64
helicopter, 99

- HEMT, 106
HVAC, 44
illuminance, 23
impedance matching, 86
inductive coupling
 measurements, 89
 nonresonant, 79
 resonant, 81
inkjet printing, 6
 continuous, 7
 drop-on-demand, 7
instantaneous power variance, 139
Internet of Things, 1, 5, 163
irradiance, 23
Jet Propulsion Laboratory, 107
Kelvin relationships, 60
kinetic energy transducer, 44
 electromagnetic, 46
 electrostatic, 45
 piezoelectric, 47
Kirchoffs law, 93
Kyoto University, 99
Lambert function, 33, 119
laser beam, 108
linear regulator, 145
 series, 146
 shunt, 146
Marconi, G., 2
maximum power point tracking (MPPT), 166
MEMS, 53
metamaterial arrays, 94
Mica, 1
microcontroller, 164
 active mode, 167
 clock frequency, 167
 hibernate mode, 168
 low power, 166
 power saving mode, 167
milling, 10
modified Bessel function, 119
mutual inductance, 80, 89
nanowire, 16
natural modes, 94
Ohm's law, 62
open-circuit voltage, 29, 122
operational amplifier, 145
oscillator, 156
Paradiso, 54
parasitic resistance, 30
 parallel, 30
 series, 30
particle swarm optimization, 97
peak-to-average-power ratio (PAPR), 136
pellet, 60
Peltier effect, 59
phased array, 95, 99
photoconductor, 22
photodiode, 22
piezoelectric, 16
 nanowire, 16
Planck's distribution, 25
polymer, 14
power converter, 142
 linear, 142, 145
 step down, 144
 switched mode, 142
power density, 110
power management unit, 164
power supply, 142
power transfer
 capacitive, 97
power transfer efficiency, 81, 83
primary battery, 159
PVDF, 54
PZT, 54
Qi standard, 78
quality factor, 90
quantum dot, 22
Queisser, 25
Ragone diagram, 159
rechargeable battery, 159
reciprocity theory, 121
recombination, 26, 28, 29
rectenna, 111
 angle of arrival, 132
 class-F, 107
 nonlinear optimization, 120
rectifier, 100, 112
 bidirectional, 106
 equivalent capacitance, 126
 equivalent resistance, 126
 millimeter wave, 107
 multiband, 124
 optimum input resistance, 120
 optimum load, 120
 Schottky diode, 115
 transistor, 106
 Wilkinson, 133
regulator
 Zener, 157
relay resonators, 94
resistance compression circuit, 130
resistive divider, 146
RFID, 1, 163, 170
 bistatic configuration, 171
 reference range, 171
 transmission coefficient, 170

- s-parameters, 121
- secondary battery, 159
- Seebeck effect, 58
- Seiko, 55
- self-inductance, 89
- sensing
 - antenna-based, 168
 - sheet resistance, 13
 - Shenk, 54
 - Shockley, 25
 - short-circuit current, 29
 - signal optimization, 135
 - silver nanoparticle ink, 13
 - sintering, 11
 - laser, 12
 - thermal, 11
 - UV plasma, 12
 - smart dust, 1
 - software-defined radio, 97
 - solar antenna, 38
 - PET, 39
 - slot, 39
 - textile, 39
 - solar power satellite, 78, 99
 - solar rectenna, 38
 - solar RFID, 39
 - specific energy, 158
 - specific power, 158
 - spectral irradiance
 - direct and circumsolar, 23
 - global, 23
 - spectrum analyzer, 136
 - SPICE model, TEG, 69
 - strong coupling
 - double peak, 84
 - SU-8, 15
 - supercapacitor, 158
 - equivalent circuit, 161
 - surface energy, 10
 - switch, 102
 - SPDT, 147
 - SPST, 147
 - switched mode power converter, 155
 - input resistance, 143
 - boost, 147
 - buck, 147
 - buck-boost, 147
 - efficiency, 143
 - flyback, 147
 - steady-state analysis, 147
 - step-down, 147
 - step-up, 147
 - tandem solar cell, 35
 - series connected, 35
 - unconstraint, 35
 - TEG, 58
 - Telos, 1
 - Tesla, N., 2
 - thermal radiation, 62
 - thermodynamics
 - first law, 63
 - thermoelectric phenomena, 58
 - Thevenin equivalent circuit, 121
 - Thomson effect, 60
 - time reversal duality, 104
 - transducer
 - thermoelectric, 58
 - transmission coefficient, 52
 - ultimate solar cell efficiency, 25
 - vector signal analyzer, 136
 - vibration sources, 51
 - wet etching, 10
 - Wheeler formula, 91
 - Wilkinson power combiner, 133
 - Williams, 47
 - wireless communication transceiver, 169
 - wireless power transmission, 75
 - wireless sensing platform, 163
 - WISP, 171
 - Yates, 47
 - Zener diode, 145