

Index

- 1/f noise, 39, 101
- Active load modulation, 171
- Adjacent channel power ratio (ACPR), 5
- Advanced Extremely High Frequency (AEHF), 9
- AM/AM distortion, 98, 124
- Analog-to-digital Converters (ADC), 439
- Asymmetric Multilevel Outphasing (AMO), 312
- Automotive radar, 9, 412
- Backhaul, 2, 68, 257, 376
- Backoff, 171, 177, 314
- Balun, 280
- Baseband, 307, 310, 316, 331, 334, 338, 341, 345, 353, 378, 385
- Base Current Reversal, 41, 190
- Base Resistance, 19, 25, 34, 37, 43, 59
- Bipolar junction transistors (BJT), 18, 218
- Bit error rate (BER), 5
- Breakdown voltage, 41, 63, 103, 143, 187
- BSIM model, 85, 119, 131
- Built-in self-test (BIST), 3, 8
- Cartesian, 4, 340, 349, 361, 366
- Cascode, 107, 142, 219, 230, 280, 339, 400, 403, 413, 423, 425, 435, 441
- Channel capacity, 5, 316
- Chireix, 202, 314, 338
- Co-channel interference, 6
- Collector-base breakdown voltage for an open emitter (BV_{CB0}), 41, 60, 63, 143, 167, 193, 195, 403
- Collector-emitter breakdown voltage for open base (BV_{CEO}), 41, 63, 143, 167, 188
- Conduction Angle, 156, 162
- Coplanar Waveguide (CPW), 148
- Coupler, 218, 260, 267, 384, 392, 402, 429
- Deep N-well (DNW), 279
- Deep trench (DT), 29, 30, 45
- Defense Advanced Research Projects Agency (DARPA), 10
- Digital to Analog Converter (DAC), 201, 318, 335, 346, 360, 366, 410, 439
- Doherty, 170, 174
- DOTFIVE, 64
- Drain Induced Barrier Lowering (DIBL), 82, 131, 150, 419
- Early effect, 53
- Effective isotropic radiated power (EIRP), 377, 388
- Efficient Linearized All-Silicon Transmitter ICs (ELASTx), 10
- Electromigration, 61, 63
- Envelope Elimination and Restoration (EER), 200, 337
- Envelope Tracking (ET), 8
- Error vector magnitude (EVM), 5, 201, 320, 334, 337, 339, 341, 359, 381, 383, 384
- ESD, 131
- f_{max} , 25, 86, 149, 152, 195, 226
- Fifth-generation commercial wireless standard (5G), 2, 9, 257
- Forward-bias current stress, 60
- Gate resistance, 87, 99, 149, 151, 230, 241
- Ground-shielded Coplanar Waveguide (GSCPW), 392
- Gysel, 400
- Harmonic, 92, 108, 121, 129, 142, 155, 168, 180, 188, 215, 240, 334, 363
- High Current Model (HICUM), 52
- Homodyne, 6
- IEEE 802.11ad, 8, 378, 380, 383, 408
- IIP3 (Third Order Intercept Point), 95
- IM3 (Third Order Intermodulation), 91
- Impact ionization, 40, 124, 188
- Impedance Transformation, 7, 146, 176, 210, 288
- Industrial, scientific, and medical (ISM), 2, 8
- Intermodulation distortion (IMD), 91, 96
- Johnson Figure of Merit (JFoM), 132
- Kahn Transmitter, 200
- Kirk effect, 22, 53
- Knee Voltage, 78, 141, 189, 215

- Linearity, 1, 7, 78, 83, 91, 139, 188, 200, 223, 304, 322, 329, 334, 337, 348, 356, 380, 394, 424, 449
- Loadline resistance, 145, 161, 168, 173
- Load Pull, 108, 119, 182, 338, 356, 360
- Long-range radars (LRR), 9, 412
- Loss factor, 142, 146, 165
- Maximum Available Gain (MAG), 149, 153
- Memory effect, 98, 102, 104
- Metal-Insulator-Metal (MIM) capacitor, 51, 115
- Metal-Oxide-Metal (MOM) capacitor, 115, 323
- Mixed-mode stress, 60
- Mixer, 322, 339, 347, 381, 397
- Most Exquisite Transistor Model (MEXTRAM), 52
- Multi-Input Multi-Output (MIMO), 378
- Noise, 5, 37, 53, 98, 342, 427
- Noise figure, 37
- Nonlinearity, 5, 91, 97
- Orthogonal frequency division multiplexing (OFDM), 8, 200, 308, 335, 379, 380, 383, 405
- Outphasing transmitter, 202, 302, 340
- Patch antenna, 364, 366, 407, 411
- Patterned Ground Shield (PGS), 117
- Peak-to-average power ratio (PAPR), 139, 317, 380
- Phased array, 2, 5, 388, 389, 391, 398
- Phase locked loop (PLL), 6, 307, 383, 397–399, 409, 413, 422
- Phase Noise, 381, 413
- p-i-n diode, 49
- Polar, 4, 200, 337
- Power added efficiency (PAE), 7, 129, 140, 163, 182, 191, 235, 302
- Process, voltage, and temperature (PVT), 6, 421, 422
- PSP model, 131
- Quadrature Amplitude Modulation (QAM), 139, 171, 200, 335, 346, 366, 378
- Quality Factor, 48, 77, 116, 142, 146, 163, 183, 288, 381
- Quantization, 339, 342, 373
- Receiver, 5, 359, 379, 385, 413
- Reliability, 58, 105, 216
- Reverse bias emitter-base stress, 59
- RF DAC, 338, 340, 350, 357
- Safe Operating Area (SOA), 63
- SATCOM, 10
- Schottky Barrier Diodes, 47
- Self-heating, 43, 103, 123, 232
- Shape factor, 141, 159, 163
- Short-range radars (SRR), 9, 412
- Silicon-on-insulator (SOI), 77, 98, 121, 150, 175, 218, 224
- Spectral regrowth, 5, 201, 320, 325, 329, 334, 337, 340, 426
- Spice Gummel–Poon Model, 52
- Stability, 151, 221, 230, 264, 267, 302
- System-on-a-chip (SOC), 2, 3, 5, 10, 11, 290, 378, 379
- Thermal effect, 44, 102, 119
- Thermal resistance, 43, 63, 103, 232
 - Mutual thermal resistance, 46
- Thin-film microstrip (TFMS), 263, 266, 279
- Through-silicon-via (TSV), 51
- Transformer, 117, 146, 171, 218, 238, 260, 268, 270, 273, 315
- Vertical Bipolar Inter Company Model (VBIC), 52
- Voltage Standing Wave Ratio (VSWR), 420, 453
- Wilkinson Power Combiner/Divider, 238, 250, 260, 265, 312, 314, 338, 356, 358, 362, 393, 400
- Wireless Gigabit Alliance (WiGig), 8, 361, 362, 364, 408
- Zero-derivative of voltage switching (ZdVS), 181, 182, 235, 237
- Zero-voltage Switching (ZVS), 142, 180–182, 235, 237