

Index

- accelerometers, 206, 208, 223
- acrylamide, 68
- adaptive noise cancellation (ANC)
 - experiments for, 165–7
 - objects for, 167–8
 - principles of, 164–5
 - simulation of, 165
 - single moving objects for, 167–8
 - two moving objects in, 168
 - for wearable radar tag systems, 164–7
- AICP implants. *See* analog intracranial pressure implants
- air tests
 - for ICP implants, 62–5
 - in vitro tests and, 71
 - schematics for, 63
- alcohol, 129–31
- algorithms, for Doppler radar systems, 164–5
- amplitude-shift keying (ASK) data, 14
- amplitude-shift keying (ASK) modulation, 4–6, 11
- analog intracranial pressure (AICP) implants
 - animal models and, 92
 - animal studies with, 95
 - DICP implants compared to, 92, 116–20
 - hydrostatic tests for, 95
 - pigs with, 92–4
 - in wireless ICP systems, 94–7
- anatomy
 - ICP implants and, 77–8
 - monitoring and, 42–3
 - skull burr holes in, 61, 80–1
- ANC. *See* adaptive noise cancellation
- animal models
 - AICP implants and, 92
 - for in vivo experiments for, 73
 - for TBI assessment, 92
- animal studies
 - with AICP implants, 95
 - schematics for, 94
 - for TBI assessment, 113–18
- antenna motion
 - accelerometers for, 206, 208, 223
 - EMD for, 219–25
 - in experiments, 206–8, 222–5
 - measurements and, 206
 - in microwave Doppler radar systems, 203–8
 - 219–25
 - motion sensors and, 203
 - signals in, 204–6
- antennas
 - annular slot antennas, 107–8
 - antenna matching for, 108–10
 - block diagrams for, 222
 - chip antennas, 48, 51–2
 - for DICP implants, 106–8
 - for embedded wireless devices, 48–58
 - ERP for, 71–2
 - geometry for, 219–20, 252
 - imaging antennas, 251–4
 - monopole antennas, 193, 232, 235–7
 - 251–2
 - PCBs and, 193
 - phantoms for, 48–9
 - simulation of, 253
 - slot antennas, 107–10, 250–4
- ASK data. *See* amplitude-shift keying data
- ASK modulation. *See* amplitude-shift keying modulation
- averaging errors, 83
- Barrett’s esophagus, 7–8
- batteries
 - battery life, 12
 - battery-based wireless and pH sensor capsules, 13–15
 - circuit loading and, 13
 - for DICP implants, 118–19
 - epoxy for, 112
 - technological advances for, 3
- batteryless endoluminal sensing telemeter (BEST) system
 - block diagrams for, 17
 - data from, 25–6
 - in experiments, 23–6
 - for GERD, 16–18

- batteryless wireless impedance and pH sensor
 - capsules
 - integration in, 20–1
 - performance of, 21–6
 - power transfers for, 26–30
 - sensors for, 18–20
 - system architecture for, 16–18
 - wireless signal transduction for, 26–30
- BEST system. *See* batteryless endoluminal sensing
 - telemeter system
- biocompatible coating, 60
- biological processes, 147–8
- biological samples, 128–9
- biomatter, 124–5
- biomedical applications
 - of Doppler radar systems, 239–43
 - of Gaussian signals, 232–5, 243, 251
 - of localization systems, 229–30
 - of monopole antennas, 193, 232, 235–7, 251–2
 - of Optotrak 3020, 235–9
 - of pulse radar, 250–4, 257–60
 - of slot antennas, 107–10, 250–4
 - of TDOA concepts, 229–31
 - UWB technology, 228, 260
 - of x-ray mammography, 250
- biomedical imaging, 175–6
- biomolecules, 131–7
- biosensors. *See* microwave biosensors
- blast injury studies, 84–5
- block diagrams
 - for antennas, 222
 - for BEST system, 17
 - for breast cancer detection, 251
 - for chip integration, 190
 - for Doppler radar systems, 163
 - for ICP monitoring, 46
 - for instruments-based physiologic radar system, 178
 - for PCBs, 180
 - of pulse radar, 194, 196
 - for quadrature Doppler radar, 176–7
 - for radar systems, 197
 - for SFCW radar, 192
 - for two-frequency radar, 163
 - UWB technology, 251
- Bluetooth, 180
- board level radar, 178–9, 182–4
- Boltzmann constant, 130
- BRAVO devices
 - battery life for, 12
 - for implantable systems, 10–12
 - MII probes compared to, 11–12, 19–20, 22–3
 - for reflux monitoring, with endoluminal
 - applications, 10–12
- breast cancer detection
 - block diagrams for, 251
 - clutter in, 255–7
 - experiments for, 257–60
 - imaging antennas for, 251–4
 - numerical simulation in, 257–9
 - UWB technology for, 250–60
- breath-rate sensing, 197
- broadband spectroscopy
 - for chemicals, 128
 - lymphoma cells in, 147–8
- calibration approaches, for radar systems, 255–7
- camino catheters, 61–3, 73–6, 78–83
- camino probes, 96, 116
- cancer
 - breast cancer detection, 250–60
 - esophageal cancer, 7
 - tumor tissues, 253
- canines. *See* dogs
- capacitive pressure-sensing elements, 47
- catheters, 43–4, 61–3, 73–6, 78–83
- cell detection
 - in cellular investigations, 140–3
 - electromagnetic wave penetration for, 141
 - microwave frequencies for, 129–31
 - radiofrequencies in, 129
 - traditional culture mediums for, 140–3
- cell proliferation, 139–40
- cell quantification, 143–5
- cells measurement, 143–5
- cellular analysis
 - lymphoma cells in, 143–6
 - microwave dielectric spectroscopy for, 142–3, 148–9
 - noninvasive investigations and, 125–8
 - single-cell analysis, 143–5
 - technological advances in, 127–8
 - yeast viability in, 146
- cellular investigations, 139
 - cell detection in, 140–3
 - cell quantification in, 143–5
 - microwave sensors in, 137–8
 - real time monitoring in, 147–8
 - RF signatures in, 145–7
- cerebral perfusion pressure (CPP), 119–20
- cerebrospinal fluid (CSF)
 - catheters for, 43
 - ICP and, 40–1, 43–4
- chemicals, 128
- chip antennas, 48, 51–2
- chip development. *See* physiologic radar sensor chip
 - development
- chip integration
 - block diagrams for, 190
 - for CW radar, 187–93
 - for pulse radar, 193–7
- chirp signals, 173–4
- chronic diseases, 41–2
- circuit loading, 13

- clutter
 - in breast cancer detection, 255–7
 - radar clutter, 164–8, 180–2
- CMOSs. *See* complementary metal-oxide semiconductors
- cochlear implants, 2–3
- coils
 - frequencies and, 30
 - in in vivo experiments, 27
 - power transfers and, 29–30
- complementary metal-oxide semiconductors (CMOSs), 4–6
- conductivity, 18–19
- continuous-wave (CW) radar, 154. *See also* stepped-frequency continuous-wave radar
- chip integration for, 187–93
- in Doppler radar systems, 202
- for physiologic radar sensor chip development, 172–3
- correlation, in in vivo experiments, 81–2
- CPP. *See* cerebral perfusion pressure
- CSF. *See* cerebrospinal fluid
- CW. *See* continuous-wave (CW) radar
- data. *See also* amplitude-shift keying data
 - ASK data, 14
 - ASK modulation for, 4–6, 11
 - from BEST system, 25–6
 - IR-UWB communication for, 6, 195
 - for patients, 30–1
 - for reflux diseases, 21–6
- deionized (DI) water, 25–6
- demodulated signals, 206–9, 222
- design
 - design frequencies, 156–8
 - for DICP implants, 97
 - harmonic tag design, 156–9
- design frequencies, 156–8
- DI water. *See* deionized water
- diagnostic methods
 - for GERD, 8, 30
 - for NERD, 8, 30
 - for reflux monitoring, with endoluminal applications, 8
- DICP implants. *See* digital intracranial pressure implants
- DICP prototypes. *See* digital intracranial pressure prototypes
- dielectric contrast, 146
- digital intracranial pressure (DICP) implants
 - AICP implants compared to, 92, 116–20
 - alternative processing method for, 106
 - animal studies for, 113–18
 - annular slot antennas for, 107–8
 - antenna matching for, 108–10
 - antennas for, 106–8
 - batteries for, 118–19
 - configuration for, 106
 - design for, 97
 - epoxy for, 106–7
 - eZ430-RF2500 for, 97, 108–10
 - gross pathology exams for, 115
 - in vitro tests for, 98–104, 111–13
 - in vivo experiments for, 98–9
 - in vivo study for, 113–15
 - long-term studies for, 104
 - MEMS for, 98, 118
 - pigs with, 113–18
 - power management in, 118–19
 - for rotational head injury assessment, 104–5
 - schematics for, 106
 - signal-strength test for, 110–11
 - technological advances for, 118
 - in wireless ICP systems, 97–104
- digital intracranial pressure (DICP) prototypes, 99–100
- diode impedance, 156–8
- distances, in experiments, 246–50
- dogs, in experiments, 76–81
- Doppler radar systems, 212, 219. *See also* microwave Doppler radar systems
 - algorithms for, 164–5
 - biomedical applications of, 239–43
 - biomedical imaging from, 175–6
 - block diagrams for, 163
 - CW radar in, 202
 - experiments for, 244–50
 - frequencies for, 190–2, 243–6
 - measurements from, 154–5, 161–3
 - micro-Doppler phenomenon in, 239–40
 - micro-Doppler signature extraction, 240–3
 - noninvasive investigations with, 176
 - objects for, 160–1
 - PCBs for, 184–5
 - for physiologic monitoring, 155–9, 163–4
 - quadrature Doppler radar, 159–60, 176–7
 - RFID systems compared to, 154–5
 - technological advances in, 197–8, 225
- drift, 56–7
- dry tests, 100–1
- effective radiated power (ERP), 71–2
- electrical detection. *See* microwave dielectric spectroscopy
- electrical implants, 2–3
- electrodes, 20
- electromagnetic wave penetration, 141
- embedded wireless devices
 - antennas for, 48–58
 - catheters compared to, 44
 - for ICP, 84–5
 - in vitro tests for, 68–73
 - in vivo experiments for, 73–82
 - medical uses for, 40–1

- embedded wireless devices (cont.)
 microwave frequencies for, 41
 operating principles for, 45–7
 packaging concepts for, 58–61
- empirical mode decomposition (EMD)
 for antenna motion, 219–25
 for human subjects, 212–19
 IMFs and, 212–16
 measurements and, 212–18
 in microwave Doppler radar systems, 208–12
 signal analysis and, 212
 signal performance of, 210–12, 217–18
 for wireless vital signs monitoring devices, 218–19
- endoluminal capsule applications, 4–6
- endoscopic procedures
 NOTES for, 3–4
 for wireless implants, 3–4
- epidural implants, 78
- epoxy
 for batteries, 112
 for DICP implants, 106–7
 permittivity of, 107
- ERP. *See* effective radiated power
- esophageal cancer, 7
- evaluation methods, for in vitro implants
 air tests for, 62–5
 hydrostatic tests for, 65–6
 microwave transmission in, 66
 polyacrylamide phantoms in, 66–7
 types of, 61–2
- experiments. *See also* in vivo experiments
 for ANC, 165–7
 antenna motion in, 206–8, 222–5
 BEST system in, 23–6
 for breast cancer detection, 257–60
 distances in, 246–50
 for Doppler radar systems, 244–50
 experimental verification in, 160–3
 geometry in, 257–8
 human subjects in, 167–9
 1D noncoherent experiments, 233–4
 for PIFA, 51–8
 single-person experiments, 244–5
 3D noncoherent experiments, 234–5
 time-domain in, 165–7
 two-person experiments, 246–8
 for wearable radar tag systems, 160–3
- eZ430-RF2500, 97, 108–10
- fidgiting, in human subjects. *See* microwave Doppler radar systems
- field-programmable gate arrays (FPGAs), 178
- finger pulse reference signals, 213–18
- flow cytometers, 125–7
- fluorophores, 125–7
- FMCW radar. *See* frequency modulated continuous-wave radar
- FPGAs. *See* field-programmable gate arrays
- frequencies
 coils and, 30
 design frequencies, 156–8
 for Doppler radar systems, 190–2, 243–6
 of heart rates, 222
 for imaging, 17–18, 57
 for incident radiation, 156–9
 microwave frequencies, 41, 129–31
 MPE for, 17–18
 pressure and, 68
 radiofrequencies, 129
 relaxation oscillators for, 20–1
 for RF devices, 155–6
 for rotational head injuries, 109
 signal accuracy maps for, 28–9
 STFT in, 243
 time-domain and, 172–4
- frequency modulated continuous-wave (FMCW) radar, 172–4, 229–30
- frequency-doubling tags
 harmonic radar motion sensitivity for, 156
 harmonic tag design for, 156–9
 schematics for, 155
- gastroesophageal applications. *See* implantable wireless medical devices
- gastroesophageal reflux disease (GERD)
 BEST system for, 16–18
 diagnostic methods for, 8, 30
 medical definition of, 6–7
 wireless capsules for, 13–15
- Gaussian signals
 biomedical applications of, 232–5, 243, 251
 in radar systems, 195–6, 214–18
- gel phantoms. *See also* polyacrylamide phantoms
 for PIFA, 65
 temperatures and, 57–8
 water and, 68
- geometry
 for antennas, 219–20, 252
 in experiments, 257–8
 PIFA geometry, 48–9
 of signal returns, 256
- GERD. *See* gastroesophageal reflux disease
- glucose, 132–4
- gross pathology exams, 115
- harmonic radar motion sensitivity, 156
- harmonic tag design, 156–9
- heart rates
 frequencies of, 222
 radar heart signals for, 214–18, 223–5
 simulation for, 214

- heartburn. *See* gastroesophageal reflux disease;
nonerosive esophagus reflux disease
- HHT. *See* the Hilbert-Huang transform
- the Hilbert transform, 209–10
- the Hilbert-Huang transform (HHT), 210
- human gait analysis
- distances in, 246–50
 - single-person experiments for, 244–5
 - two person experiments for, 246–8
- human subjects
- for breath-rate sensing, 197
 - EMD for, 212–19
 - in experiments, 167–9
 - pseudo-Wigner-Ville distribution for, 247–8
 - respiration rates in, 161
- hydrostatic tests
- for AICP implants, 95
 - for evaluation methods, for in vitro implants, 65–6
 - in vitro tests and, 71, 111–13
 - schematics for, 65, 112–13
- HYGE devices, 94
- hyperventilation, 74–5
- IACUC. *See* Institutional Animal Care and Use Committee
- ICP. *See* intracranial pressure
- ICP implants. *See* intracranial pressure implants
- ICP monitoring. *See* intracranial pressure monitoring
- ICs. *See* integrated circuits
- imaging. *See also* magnetic resonance imaging
- biomedical imaging, 175–6
 - CMOSs for, 4–6
 - frequencies for, 17–18, 57
 - imaging antennas, 251–4
 - instrument shake in, 202–3
 - neuroimaging, 43–4
- IMFs. *See* intrinsic mode functions
- impedance changes, 8–10, 14–15, 19–20
- impedance measurements
- conductivity for, 18–19
 - with wireless capsules, 15
- implantable systems. *See also* analog intracranial pressure implants; digital intracranial pressure implants
- BRAVO devices for, 10–12
 - cochlear implants as, 2–3
 - epidural implants, 78
 - for ICP, 42–3, 47, 61
 - implantable visual prosthetics, 2–3
 - temperature changes and, 63
 - wireless implants, 3–5
- implantable wireless medical devices, 31. *See also* batteryless wireless impedance and pH sensor capsules; reflux monitoring, with endoluminal applications
- endoluminal capsule applications for, 4–6
 - implementation methods for, 3–4
 - wireless communication in, 1–3
- impulse-radio ultra-wideband (IR-UWB) communication, 6, 195
- incident radiation, 156–9
- indoor positioning software
- 1D noncoherent experiments for, 233–4
 - 3D dynamic free motion for, 235–6
 - 3D noncoherent experiments for, 234–5
 - 3D robot tracking for, 237–8
 - uses of, 228–9, 239
 - UT tracking software for, 230–3
- indoor positioning systems, 229–30
- inductive-coupling, 26–7
- in vitro antenna characterization, 48–9
- in vitro implants, 61–8
- in vitro tests
- air tests and, 71
 - for DICP implants, 98–104, 111–13
 - on DICP prototypes, 99–100
 - dry tests in, 100
 - for embedded wireless devices, 68–73
 - hydrostatic tests and, 71, 111–13
 - measurements for, 68–70
 - microwave transmission in, 71–2
 - parylene coating in, 70, 72–3
 - performance of, 103–4
 - signal-strength tests in, 102–3
 - temperature sensitivity in, 70
 - temperature tests in, 103
 - water tests in, 100–2
- in vivo experiments, 23–6
- animal models for, 73
 - coils in, 27
 - correlation in, 81–2
 - for DICP implants, 98–9
 - on dogs, 76–81
 - for embedded wireless devices, 73–82
 - IACUC for, 74, 92, 113
 - for ICP, 61
 - measurements in, 79–80
 - on pigs, 73–7
 - skull burr holes in, 80–1
 - surgical procedures for, 74–6
- in vivo studies, 113–15
- Institutional Animal Care and Use Committee (IACUC), 74, 92, 113
- instrument shake, 202–3
- instruments-based physiologic radar system, 177–8, 185–7
- integrated circuits (ICs), 20, 177, 179–80, 183
- interference-reduction. *See* microwave Doppler radar systems
- intracranial hypertension, 41, 73, 76, 79–80
- intracranial pressure (ICP). *See also* analog intracranial pressure implants; digital intracranial pressure implants

- intracranial pressure (ICP). (cont.)
 - camino catheters for, 61–3, 73–6, 78–83
 - chronic diseases and, 41–2
 - CPP and, 119–20
 - CSF and, 40–1, 43–4
 - dynamics model for, 120
 - embedded wireless devices for, 84–5
 - hyperventilation and, 74–5
 - implantable systems for, 42–3, 47, 61
 - in vivo experiments for, 61
 - measurements for, 89–90
 - MRI for, 43–4
 - for patients, 40
 - piezoresistive pressure-sensing elements for, 62–3
 - PZR implants for, 68–70
 - risks of, 41–2
- intracranial pressure (ICP) implants
 - air tests for, 62–5
 - anatomy and, 77–8
 - measurements for, 76
 - probes compared to, 84–5
 - schematics for, 47
- intracranial pressure (ICP) monitoring
 - block diagrams for, 46
 - technological advances for, 44–5
 - technology for, 43–4
- intrinsic mode functions (IMFs)
 - EMD and, 212–16
 - for signals, 208–12
- ions, 140–1
- ion-selective field-effect transistor sensors, 22
- IR-UWB communication. *See* impulse-radio ultra-wideband communication
- liquid analysis. *See* microwave analysis
- localization systems, 229–30
- long-term studies
 - for DICP implants, 104
 - for TBI, 119
- lymphoma cells
 - in broadband spectroscopy, 147–8
 - in cellular analysis, 143–6
 - dielectric contrast of, 146
 - microwave biosensors for, 143–5
- magnetic resonance imaging (MRI), 43–4
- mannequins, 21–2
- MATLAB programs, 98–9, 165, 214, 220, 222
- maximum permissible exposure (MPE), 17–18
- measurements
 - antenna motion and, 206
 - camino probes for, 96, 116
 - of cells, 143–5
 - from Doppler radar systems, 154–5, 161–3
 - for dry tests, 100–1
 - EMD and, 212–18
 - errors in, 83, 111
 - for ICP, 89–90
 - for ICP implants, 76
 - for in vitro tests, 68–70
 - in in vivo experiments, 79–80
 - MATLAB programs for, 98–9, 165, 214, 220, 222
 - for performance, 54–8
 - pH measurements, 15
 - RF measurement, 140–3
 - rotational head injuries and, 95–7, 113–15
 - of signal returns, 256–7
 - VNA for, 51–2, 198
- MEMS. *See* microelectromechanical systems
- metals, 58–9
- micro-Doppler phenomenon, 239–40
- micro-Doppler signature extraction, 240–3
- microelectromechanical systems (MEMS)
 - for DICP implants, 98, 118
 - in microwave biosensors, 136–7
- microscopy
 - fluorophores in, 125–7
 - microwave dielectric spectroscopy compared to, 127–8
- microwave analysis
 - of biomolecules in aqueous solution, 131–7
 - ions in, 140–1
 - permittivity in, 143
 - water in, 132–4
- microwave biosensors
 - for lymphoma cells, 143–5
 - MEMS in, 136–7
 - for noninvasive investigations, 124–5, 148–9
 - schematics of, 145
 - for selectivity, 135–7
 - for single-cell analysis, 148–9
 - for spectroscopy, 131–7
- microwave dielectric spectroscopy
 - biosensors for, 131–7
 - for cellular analysis, 142–3, 148–9
 - microscopy compared to, 127–8
 - for molecular analysis, 148–9
 - for molecular investigations, 125–8
- microwave Doppler radar systems
 - antenna motion in, 203–8, 219–25
 - EMD in, 208–12
 - for vital signs detection, 202–3
- microwave frequencies
 - for cell detection, 129–31
 - for embedded wireless devices, 41
- microwave sensors, 137–8
- microwave spectroscopy. *See also* microwave dielectric spectroscopy
 - for molecular investigations, 137
 - for noninvasive investigations, 128–31
 - specificity in, 145–7
- microwave transmission
 - in evaluation methods, for in vitro implants, 66

- in in vitro tests, 71–2
- MII Probes. *See* multichannel intraluminal impedance probes
- millimeter waves. *See* microwave analysis
- module-based integration, 176–8
- molecular analysis, 148–9
- molecular investigations. *See also* cellular investigations; noninvasive investigations
 - microwave dielectric spectroscopy for, 125–8
 - microwave spectroscopy for, 137
- monitoring. *See also* intracranial pressure monitoring; vital signs monitors
 - anatomy and, 42–3
 - diagnostic methods in, 8, 30
 - finger pulse reference signals for, 213–18
 - monitoring duration, 11–12
 - real time monitoring, 147–8
 - of respiration, 195–7
- monopole antennas, 193, 232, 235–7, 251–2
- motion. *See* Doppler radar systems
- motion sensors, 203
- moving target indicators, 212, 219
- MPE. *See* maximum permissible exposure
- MRI. *See* magnetic resonance imaging
- multichannel intraluminal impedance (MII) probes
 - BRAVO devices compared to, 11–12, 19–20, 22–3
 - for patients, 9
 - for reflux monitoring, with endoluminal applications, 8–10
- natural orifice transluminal endoscopic surgery (NOTES), 3–4
- NERD. *See* nonerosive esophagus reflux disease
- neuroimaging, 43–4
- neuropathologic studies, 119–20
- noise-reduction. *See* microwave Doppler radar systems
- noncontact motion sensors, 187–93
- nonerosive esophagus reflux disease (NERD)
 - diagnostic methods for, 8, 30
 - medical definition of, 7
- noninvasive investigations. *See also* cellular investigations
 - cellular analysis and, 125–8
 - with Doppler radar systems, 176
 - microwave biosensors for, 124–5, 148–9
 - microwave spectroscopy for, 128–31
 - optical techniques in, 127
 - with radar, 176
 - sensitivity in, 138–40
- nonpolar liquids, 68
- NOTES. *See* natural orifice transluminal endoscopic surgery
- numerical simulation, 257–9
- objects
 - for ANC, 167–8
 - for Doppler radar systems, 160–1
 - single moving objects, 167–8
- 1D noncoherent experiments, 233–4
- optical techniques, 127
- Optotrak 3020, 235–9
- packaging concepts, for embedded wireless devices
 - biocompatible coating for, 60
 - materials for, 58–9
 - metals for, 58–9
 - pressure-sensing methods for, 60
 - pressure-sensing sites for, 60–1
 - sealants for, 59
 - superstrates for, 59–60
- parylene coating, 70, 72–3
- patients
 - data for, 30–1
 - ICP for, 40
 - mannequins as, 21–2
 - MII probes for, 9
 - receivers for, 11
 - wireless communication for, 1–3
- PCBs. *See* printed circuit boards
- performance
 - of batteryless wireless impedance and pH sensor capsules, 21–6
 - of EMD signals, 210–12, 217–18
 - of in vitro tests, 103–4
- performance, measurements for
 - drift in, 56–7
 - silicone coating thickness in, 54–5
 - temperature changes and, 57–8
- permittivity
 - acrylamide and, 68
 - of epoxy, 107
 - of glucose, 132–4
 - in microwave analysis, 143
 - nonpolar liquids and, 68
 - of tumor tissues, 253
 - of water, 134–6
- pH measurements, 15
- phantoms
 - for antennas, 48–9
 - gel phantoms, 57–8, 65, 68
 - ingredients and, 67–8
 - polyacrylamide phantoms, 66–7
 - recipe for, 66–7
 - saline in, 52
- physiologic monitoring
 - Doppler radar systems for, 155–9, 163–4
 - experimental verification for, 160–3
 - radar clutter in, 164–8
 - wearable radar tag systems for, 154–5, 168–9
 - wireless technology for, 180

- physiologic radar sensor chip development
 - case studies for, 197–8
 - chip integration for, 187–97
 - CW radar for, 172–3
 - FMCW radar for, 172–4
 - module-based integration for, 176–8
 - PCBs for, 178–87
 - pulse radar for, 174–5
 - theory for, 172
 - UWB SFCW radar for, 175–6
- physiologic signals, 209
- piezoresistive (PZR) implants, 68–70
- piezoresistive pressure-sensing elements, 45–7
 - 62–3
- PIFA. *See* planar inverted-F antenna
- pigs
 - with AICP implants, 92–4
 - with DICP implants, 113–18
 - in in vivo experiments, 73–7
- planar inverted-F antenna (PIFA)
 - characterization for, 49–51
 - experiments for, 51–8
 - gel phantoms for, 65
 - geometry for, 48–9
 - for rotational head injuries, 107–8
 - superstrates for, 59–60
 - VCO for, 51, 53–4
 - for VNA measurements, 51–2
- polyacrylamide phantoms, 66–7
- polydimethylsiloxane, 20
- portable radar systems, 179–80
- postoperative provisions, 94
- power
 - coils and, 29–30
 - ERP, 71–2
 - power amplifiers, 21
 - power management, 118–19
 - power transfers, 26–30
 - for radar systems, 190–3, 232–3
 - RF power, 138–40
 - VCOs for, 45–7
 - wireless power, 26–7
- pressure, 68
 - pressure-sensing elements, 45–7
 - pressure-sensing methods, 60
 - pressure-sensing sites, 60–1, 83
- printed circuit boards (PCBs)
 - antennas and, 193
 - block diagrams for, 180
 - for board level radar, 178–9
 - for Doppler radar systems, 184–5
 - for portable radar systems, 179–80
 - in RF boards, 182–4
 - VCOs and, 179–83
 - for wearable radar tag systems, 184–5
- probes, 84–5
- pseudo-Wigner-Ville distribution, 247–8
- pulse radar. *See also* ultra-wideband (UWB) technology
 - biomedical applications of, 250–4, 257–60
 - block diagrams of, 194, 196
 - chip integration for, 193–7
 - for physiologic radar sensor chip development, 174–5
 - RTOF for, 172, 174–5
 - theory of, 240–1
 - UWB for, 172, 174–6, 193–7
- PZR implants. *See* piezoresistive (PZR) implants
- quadrature Doppler radar, 159–60, 176–7
- radar systems. *See also* Doppler radar systems; physiologic radar sensor chip development; pulse radar; signals
 - biomedical imaging from, 175–6
 - block diagrams for, 197
 - board level radar, 178–9, 182–4
 - calibration approaches for, 255–7
 - chirp signals for, 173–4
 - FMCW radar, 172–4, 229–30
 - FPGAs for, 178
 - Gaussian signals in, 195–6, 214–18
 - heart signals in, 214–18, 223–5
 - ICs for, 20, 177, 179–80, 183
 - instruments-based physiologic radar system, 177–8, 185–7
 - noninvasive investigations with, 176
 - portable radar systems, 179–80
 - power for, 190–3, 232–3
 - quadrature Doppler radar, 159–60, 176–7
 - radar clutter in, 164–8, 180–2
 - radar signal processing in, 241–3
 - RF devices for, 176–8
 - selectivity for, 154
 - sensitivity in, 188–92, 195–7
 - two-frequency radar, 163–4
- radiation, 156–9
- radiofrequencies, 129
- radiofrequency devices. *See* RF devices
- radiofrequency identification (RFID) principle, 12–13
- radiofrequency identification (RFID) systems, 154–5
- radiofrequency integrated circuits (RFICs), 1–2
- real time monitoring, 147–8
- receivers, 11
- reception, of signals, 204–6
- reflux diseases. *See also* gastroesophageal reflux disease; nonerosive esophagus reflux disease
 - data for, 21–6
 - impedance changes in, 8–10, 14–15
 - 19–20
 - monitoring duration for, 11–12
 - water variations and, 25–6

- reflux monitoring, with endoluminal applications
 - battery-based wireless and pH sensor capsules for, 13–15
 - BRAVO devices for, 10–12
 - diagnostic methods for, 8
 - MII probes for, 8–10
 - significance of, 6–8
 - wireless impedance sensors, with RFID for, 12–13
- relaxation models, 133–4
- relaxation oscillators, 20–1
- relaxation times, 129–31
- resonant devices, 135–6
- respiration
 - breath-rate sensing, 197
 - monitoring of, 195–7
 - respiration rates, 161, 172, 243–8
 - respiration signals, 220
- RF devices
 - frequencies for, 155–6
 - for radar, 176–8
 - RF boards, 182–4
 - RF energy in, 158–9
 - for RF measurement, 140–3
 - RF power in, 138–40
 - RF resonators, 136
 - RF signatures in, 145–7
 - RF transmitters, 14
- RFICs. *See* radiofrequency integrated circuits
- RFID principle. *See* radiofrequency identification principle
- RFID systems. *See* radiofrequency identification systems
- robots. *See* Optotrak 3020; 3D robot tracking
- rodent studies. *See* in vivo experiments
- rotational head injuries. *See also* analog intracranial pressure implants; digital intracranial pressure implants
 - assessment of, 104–5
 - frequencies for, 109
 - HYGE devices for, 94
 - measurements and, 95–7, 113–15
 - PIFA for, 107–8
 - TBI and, 90–1, 94
 - USB-based wireless development tools for, 97–9
- round-trip time of flight (RTOF), 172, 174–5
- saline, 52
- salt water, 25–6
- Sapphire DART system, 229–30
- scattering-parameter measurements, 54
- schematics
 - for air tests, 63
 - for animal studies, 94
 - for DICP implants, 106
 - for dry tests, 100
 - for eZ430-RF2500, 109
 - of flow cytometers, 125–6
 - for frequency-doubling tags, 155
 - for hydrostatic tests, 65, 112–13
 - for ICP implants, 47
 - of microwave biosensors, 145
- sealants, 59
- selectivity
 - microwave biosensors for, 135–7
 - for radar, 154
- sensitivity
 - in noninvasive investigations, 138–40
 - in radar systems, 188–92, 195–7
 - of resonant devices, 135–6
 - temperature sensitivity, 70
- sensors. *See specific* sensors
- SFCW radar. *See* stepped-frequency continuous-wave radar
- short-time Fourier transform (STFT), 243
- signals
 - in antenna motion, 204–6
 - chirp signals, 173–4
 - demodulated signals, 206–9, 222
 - EMD signals, 210–12, 217–18
 - finger pulse reference signals, 213–18
 - Gaussian signals, 195–6, 214–18, 232–5, 243, 251
 - HHT for, 210
 - the Hilbert transform for, 209–10
 - IMFs for, 208–12
 - physiologic signals, 209
 - radar heart signals, 214–18, 223–5
 - radar signal processing, 241–3
 - reception of, 204–6
 - respiration signals, 220
 - signal accuracy maps, 28–9
 - signal analysis, 212
 - signal returns, 256–7
 - simulation of, 220–1
 - wireless signal transduction, 26–30
- signal-strength tests, 102–3, 110–11
- silicone coating thickness
 - in performance, measurements for, 54–5
 - for TBI assessment, 106
- simulation
 - of ANC, 165
 - of antennas, 253
 - for heart rates, 214
 - numerical simulation, 257–9
 - of signals, 220–1
- single moving objects, 167–8
- single-cell analysis, 143–5, 148–9
- single-person experiments, 244–5
- skull burr holes, 61, 80–1
- slot antennas, 107–10, 250–4
- specificity, in RF signatures, 145–7
- spectroscopy. *See* microwave dielectric spectroscopy; microwave spectroscopy

- stepped-frequency continuous-wave (SFCW) radar
 - block diagrams for, 192
 - UWB for, 175–6
- STFT. *See* short-time Fourier transform
- studies
 - animal studies, 94–5, 113–18
 - blast injury studies, 84–5
 - case studies, 197–8
 - in vivo studies, 113–15
 - long-term studies, 104, 119
 - neuropathologic studies, 119–20
- superstrates, 59–60
- surgical procedures
 - for in vivo experiments, 74–6
 - for TBI assessment, 92–4
- swine. *See* pigs
- tags. *See* specific tags
- tap water, 25–6
- TBI. *See* traumatic brain injury
- TBI assessment. *See* traumatic brain injury assessment
- TDOA concepts. *See* time-difference-of-arrival concepts
- technological advances
 - for batteries, 3
 - in cellular analysis, 127–8
 - for DICE implants, 118
 - in Doppler radar systems, 197–8, 225
 - for electrical implants, 2–3
 - for ICP monitoring, 44–5
 - in respiration monitoring, 195–7
 - for RFICs, 1–2
 - in telemetry, 85
 - Time Domain Corporation for, 228
- technology
 - for ICP monitoring, 43–4
 - of indoor positioning software, 228–39
 - for vital signs detection, 239–40
 - wireless technology, 40–1, 180
- telemedicine, 40–1
- telemetry
 - technological advances in, 85
 - for wireless implants, 4–5
- temperature changes
 - implantable systems and, 63
 - performance, measurements for, and, 57–8
 - in TBI assessment, 112–13
- temperatures
 - gel phantoms and, 57–8
 - temperature sensitivity, 70
 - temperature tests, 103
- theory
 - for physiologic radar sensor chip development, 172
 - of pulse radar, 240–1
- 3D dynamic free motion, 235–6
- 3D noncoherent experiments, 234–5
- 3D robot tracking, 237–8
- Time Domain Corporation, 228
- time-difference-of-arrival (TDOA) concepts, 229–31
- time-domain
 - in experiments, 165–7
 - frequencies and, 172–3, 172–4
- tracking software, 230–3
- traditional culture mediums, 140–3
- traumatic brain injury (TBI). *See also* analog
 - intracranial pressure implants; digital
 - intracranial pressure implants
 - long-term studies for, 119
 - neuropathologic studies for, 119–20
 - rotational head injuries and, 90–1, 94
- traumatic brain injury (TBI) assessment
 - animal models for, 92
 - animal studies for, 113–18
 - postoperative provisions after, 94
 - silicone coating thickness for, 106
 - surgical procedures for, 92–4
 - temperature changes in, 112–13
 - wireless ICP systems for, 89–90, 118–20
- tumor tissues, 253
- two-frequency radar, 163–4
- two-person experiments, 246–8
- ultra-wideband (UWB)
 - for pulse radar, 172, 174–6, 193–7
 - for SFCW radar, 175–6
- ultra-wideband stepped-frequency continuous wave (UWB SFCW) radar, 175–6
- ultra-wideband (UWB) technology. *See also* human gait analysis
 - biomedical applications of, 228, 260
 - block diagrams of, 251
 - for breast cancer detection, 250–60
 - for indoor positioning software, 228–39
 - for vital signs detection, 239–50
- University of Texas (UT) tracking software, 230–3
- USB-based wireless development tools, 97–9
- UT tracking software. *See* University of Texas tracking software
- UWB SFCW radar. *See* ultra-wideband stepped-frequency continuous wave radar
- UWB technology. *See* ultra-wideband (UWB) technology
- VCOs. *See* voltage controlled oscillators
- vector network analyzer (VNA)
 - for measurements, 51–2, 198
 - PIFA measurements for, 51–2
 - scattering-parameter measurements for, 54
- vital signs detection. *See also* human gait analysis
 - micro-Doppler signature extraction in, 240–3

- respiration rate in, 243–8
- technology for, 239–40
- vital signs monitors, 202–3
- VNA. *See* vector network analyzer
- voltage controlled oscillators (VCOs)
 - PCBs and, 179–83
 - for PIFA, 51, 53–4
 - for power, 45–7
- water. *See also specific waters*
 - DI water, 25–6
 - gel phantoms and, 68
 - in microwave analysis, 132–4
 - permittivity of, 134–6
 - salt water, 25–6
 - tap water, 25–6
 - water tests, 100–2
 - water variations, 25–6
- wearable radar tag systems
 - ANC for, 164–7
 - experiments for, 160–3
 - frequency-doubling tags for, 155–9
 - PCBs for, 184–5
 - for physiologic monitoring, 154–5
168–9
 - two-frequency radar for, 163–4
- wireless capsules
 - for GERD, 13–15
 - impedance measurements with, 15
 - pH measurements with, 15
 - power amplifiers for, 21
- wireless communication, 1–3
- wireless ICP systems. *See* wireless intracranial pressure systems
- wireless impedance sensors, with RFID, 12–13
- wireless implants
 - endoscopic procedures for, 3–4
 - telemetry for, 4–5
- wireless intracranial pressure (ICP) systems
 - AICP implants in, 94–7
 - DICP implants in, 97–104
 - for TBI assessment, 89–90, 118–20
- Wireless pH monitoring capsules. *See* BRAVO devices
- wireless power, 26–7
- wireless signal transduction, 26–30
- wireless technology
 - for physiologic monitoring, 180
 - for telemedicine, 40–1
- wireless vital signs monitoring devices, 218–19
- x-ray mammography, 250
- yeast viability, 146