

# Index

Figures and tables are denoted in bold typeface.

- accuracy (performance metric), **82, 83**
- additive white Gaussian noise (AWGN). *See also* interference and lamp arrangement, 56
  - channel capacity, 141
  - dimming strategies, 19–21, **20, 21, 22**
- algorithm complexity (performance metric), **83**
- algorithms (indoor positioning), 75–82
- ALOHA protocol, 84
- analog dimming, 17–21, **20, 21, 22**
- angle-of-arrival measurement systems, 79–81, **79, 89**
- angulation (triangulation), 79–81, **79**
- ANSI E1.11 standard, 111, 112, **112**
- asymmetrically clipped optical OFDM (ACO-OFDM), 145, 151–152, **151, 153, 154, 154, 155, 160, 164, 165**
- automobile (ITS in), 4, **4, 201–202, 201**
- BER. *See* bit error rate
- bidirectional links, 159
- bit error rate (BER)
  - and LED dimming control technique, 61–64, **62**
  - DMT, 164, 165
  - IPPM, 123–124, 125–130, **127, 129, 130**
  - lamp arrangement, 56–59, **57**
  - M-QAM OFDM, 64
  - OOK, 120–121
  - plane tilting technique, 49–51, **50, 51**
  - PPM, 121–123
  - VPPM, 124–125
- blinking pattern light extraction, 199–201, **200**
- blockage (light), 84–85
- bridge structure monitoring, 202, 203, **203**
- camera geometry (computer vision), 196–198, **197**
- capacity
  - channel, 59–60, **60, 140–143, 142**
  - dimming, 17–21, **18, 20, 21, 22**
- channel capacity
  - arranging VLC lamps, 59–60, **60**
  - LOS, **142**
- charged coupled device image sensor (CCD), **182**
- CIM. *See* color intensity modulation
- civil engineering applications, 202–203, **203**
- clipping LED modulation, 153–154
- code-division-multi-access (CDMA), 84
- color intensity modulation (CIM)
  - multi-colored LED, **12, 36, 37**
  - multi-colored VLC, 33–37, **34, 35, 36**
- color shift keying (CSK), **12, 33, 36**
- complementary metal oxide semiconductor image sensor (CMOS), 183, **183**
- computer vision (single view geometry), 196–198, **197**
- constraint. *See* lighting constraint
- coplanar rotation method, 99–102, **101**
- Cramer–Rao lower bound performance metric (CRLB), 93–94, **95**
- CSK. *See* color shift keying
- cyclic prefix, 147–149, **147, 156**
- data rates
  - bandwidth congestion, 71, 73, **73**
  - high VLC scenarios, 135–139, **136, 137, 139**
  - IEEE 802.15.7 standard, 110
  - increasing around world, 6
  - indoor VLC systems, 41
  - real-time mobile, **169**
- DC-biased discrete multitone modulation, 144, 145–149, **146, 147, 149, 150, 154, 155, 160, 161, 165**
- diffuse link, 136, 137
- dimensionality (performance metric)
  - camera geometry (computer vision), 196–198, **197**
  - indoor LPS, **83**
- dimnable visible light communication
  - and reliable communication, 160–161
  - capacity, 17–21, **18, 20, 21, 22**
  - indoor, 60–66, **61, 62, 65**
  - ISC in, 13–16, **14, 15**
  - multi-level transmission, 21–33
- dimming coding. *See* inverse source coding

- directed link, 136
- discrete multitone modulation (DMT). *See also* orthogonal frequency division multiplexing, indoor light positioning system
  - advanced multi-color applications, 161–162, **161**
  - enhancement approaches, 155–158
  - implementation, 163–170, **164, 166, 168**
  - lack of standards, 135
  - system design, 158–170, **162, 164, 166, 167, 168**
  - systems, 143–155
- diversity-combined orthogonal frequency division multiplex, 157
- DMT. *See* discrete multitone modulation
- economics
  - and low-cost multimedia, 71–72
  - image sensors, 204
  - LBS, **71**
- entropy (dimming capacity), 17–21, **18**
- Ethernet power line communication (PLC)
  - combined with VLC, 159–160
  - VLC downlink, 1
- femto-cells, 73
- field-of-view receiver (FOV), 136–137, **136, 190**
- flip-orthogonal frequency division multiplex (flip-OFDM), 156, 164
- fly-eye receiver, 84
- frequency-division-multi-access (FDMA), 84
- geometry
  - computer vision, 196–198, **197**
  - indoor, **42**
  - plane tilting technique, **46**
  - single view, 196–198, **197**
- global positioning systems (GPS)
  - as TOA system, 75
  - channel multi-access, 84
  - difficult to use indoors, 70, 71, **72, 88**
- GPS. *See* global positioning systems
- hardware complexity (performance metric), **83**
- high-bandwidth islands, 73, 74
- Huffman code, 13–15, **15**. *See also* inverse Huffman code
- hybrid dimming, 17–21, **18, 21, 22**
- hybrid multi-layer modulation (MLM), 158
- IEC 62386 DALI VIC standard, 111
- IEC TC 34 standard, 107, 109, 112–113, **113**
- IEEE 802.15.4 standard, 112
- IEEE 802.15.7 standard, 6, 107, 109, 110, 114, 172
- IM/DD. *See* intensity modulation with direct detection
- image sensors. *See also* photodiodes
  - applications, 201–203, **201, 203**
  - as receiver, 185–187, **185, 186, 187**
  - definition, 181, 182
  - fusion technology, 85, 90–94, **91, 95, 133**
- link establishment, **195**
- massively parallel visible light transmission, 192–196, **193, 194, 196**
- pose estimation, 196–201, **197, 199, 200**
- system design using, 187–192, **188, 189, 190, 191**
- types of, 182–184, **182**
- indoor light positioning system. *See also* light emitting diodes, discrete multitone modulation
  - advantages of, 70–75, **71, 72, 73, 74**
  - algorithms, 75–82
  - arranging VLC lamps, 51–60
  - background of, 41, **43, 70**
  - based on VLC and image sensors, 90–94, **91, 95**
  - channel capacity, 140–143
  - dimming control technique, 60–66, **61, 62, 65**
  - link types, 135–139, **136, 137, 138**
  - multipath reflections in, 82–84
  - operation in light blockage, 84, 85
  - performance comparison, 81–82, **83**
  - plane tilting technique, 41–51, **42**
  - technologies, 88–89
- Infrared Data Association, 172
- infrared laser
  - and optical WiFi, 137, **138**
  - operation in light blockage, 85
  - VLC system, 169
- infrared light (as uplink), 1, **3, 4**
- intelligent transport systems (ITS)
  - as application of VLC technology, 1, 4, **4**
  - outdoor light positioning system, 89, 90
  - passenger information, **138**
  - traffic signal communication, 201–202, **201**
- intensity modulation with direct detection (IM/DD)
  - compared to OFDM, 143–144, **144**
  - hybrid MLM scheme, 158
  - MC-CDMA, 158
- interference. *See also* additive white Gaussian noise
  - inter-symbol, 136, 137, 143
  - ISI, 143
  - RF, 5, 74
- internet of things (IOT), 1, 4
- inter-symbol interference (ISI)
  - diffuse link, 136, 137
  - in high transmission, 143
- inverse Huffman code. *See also* Huffman code
  - ISC, **16**
  - M*-ary PAM, 17, **17**
- inverse pulse position modulation (IPPM)
  - and clock jitter, 129, 130, **130**
  - and clock synchronization, 125–129, **127**
  - BER, 123–124
  - statistical parameters, **126**
  - VLC, 116
- inverse source coding (ISC)
  - and change level distribution, 11
  - dimnable VLC, 13–21
  - dimming capacity, **20, 21, 22**

- IOT. *See* internet of things  
IPPM. *See* inverse pulse position modulation  
ISC. *See* inverse source coding  
ISI. *See* inter-symbol interference  
ITS. *See* intelligent transport systems  
ITU-T SG 16 standard, 114, 172
- literation (in triangulation), 75–79, **76, 78**  
LBS. *See* location-based services  
LED. *See* light emitting diodes  
Li-Fi, 137, **138**  
light emitting diodes (LEDs). *See also* on-off keying modulation, indoor light positioning system  
    and DMT, 135–158  
    and VLC, 1  
    for indoor light positioning systems, 73  
    illumination compatibility with VLC, **108**  
    illumination standards, 112–113, **113**  
    in toy and entertainment arena, 5–6, **5**  
    indoor light positioning system, 88–89, **91, 95**  
    ITS applications, 201–202, **201**  
    modulation bandwidth, 139–140  
    multi-colored, **12, 34, 35, 35, 36**  
    vendor compatibility, 109, **109**  
lighting constraint, 10–37  
line-of-sight (LOS)  
    channel capacity, **142**  
    non-blocked, 136, **136, 137**  
    system design for, 158–159  
location-based services (LBS)  
    definition, 70  
    economics of, **71**  
LOS. *See* line-of-sight
- MAC. *See* media access control protocol  
*M*-ary PAM. *See* *M*-ary pulse amplitude modulation  
*M*-ary pulse amplitude modulation (*M*-ary PAM)  
    ISC in, 16, 17, **17**  
    multi-colored VLC, 33–34, **35**  
    scheme, 23–28, **23, 26, 143**  
*M*-ary quadrature amplitude modulation (*M*-QAM)  
    and LED dimming control technique, 64–66, **64**  
    OFDM, 64–66, **64**  
    plane tilting technique, 49, **50, 51**  
massively parallel visible light transmission, 192–196, **193, 194, 196**  
MC-CDMA. *See* multicarrier code division multiple access  
media access control protocol (MAC), 160  
modulated retro reflector, 1, 3, 4  
modulation  
    CIM, **12, 33–37, 34, 35, 36, 37, 38**  
    DMT, 133–170, **161, 164, 166, 169**  
    IM/DD, 143–144, **144, 158**  
    IPPM, **119, 123–124, 125–130, 127, 129, 130**  
    multi-colored VLC, 33–37, **34, 35, 36, 37, 38**  
    OOK, 61–64, **62, 116, 117, 120–121, 133–135, 134, 143, 144, 163, 164**  
    OSM, 162  
    PAM, 16–21  
    PAM-DMT, 145, 152–154, **154, 164**  
    PPM, 11, **11, 116, 118, 118, 121–123**  
    PWM, 11, 60–66, **61, 143, 144, 188**  
    VPPM, 118–119, **119**  
Monte-Carlo simulation, **57**  
*M*-QAM. *See* *M*-ary quadrature amplitude modulation  
MSM. *See* multiple subcarrier modulation  
multicarrier code division multiple access (MC-CDMA), 158  
multi-colored visible light communication  
    DMT/OFDM applications, 161–162, **161**  
    LED colors, 140  
    modulation of, 33–37, **34, 35, 36**  
    SCM, 159  
multi-level transmission (dimnable VLC)  
    approach to, 21–23  
    performance, 28, **28, 29, 30, 30**  
    scheme, 23–28, **23, 26**  
    simulations, 30–33, **32**  
multimedia network service, 71, 73, **73**  
multiple subcarrier modulation (MSM), 141, 143  
multiple-input multiple-output processing (MIMO), 161–162
- noise. *See* signal-to-noise ratio, additive white  
    Gaussian noise  
non-orthogonal multi-colored channel, 37  
NRZ-OOK, 13–16, **14, 15**
- OFDM. *See* orthogonal frequency division multiplexing  
on-off keying modulation (OOK). *See also* light emitting diodes  
    and LED dimming control technique, 61–64, **62**  
    BER, 120–121  
    IEEE 802.15.7 standard, 110  
    IM/DD in, 144  
    LED driver efficiency, 163, **164**  
    time multiplex, 11  
    used in most VLC systems, 133, **134, 135**  
    VLC, 116, **117, 143**  
OOK. *See* on-off keying modulation  
optical spatial modulation (OSM), 162  
optical wireless communication. *See* visible light communication  
orthogonal frequency division multiplexing (OFDM). *See also* discrete multitone modulation  
    and LED dimming control technique, 64–66  
    diversity-combined, 157  
    flip, 156  
    MSM implemented by, 144, **144**  
    plane tilting technique, 49, 51, **52**  
    position modulating, 157  
    spectrally factorized, 156  
    unipolar, 156  
OSM. *See* optical spatial modulation

- outdoor light positioning system
  - basics of, 89, 90
  - LED traffic light and photodiode, 94–104, **96, 97, 99, 101, 102, 103**
- PAM. *See* pulse amplitude modulation
- performance
  - CIM and CSK, **37**
  - computer vision, 196–198, **197**
  - dimmable VLC, 28, **28, 29, 30, 30**
  - DMT, 155–158
  - DMT/OFDM, 153–155, **154**
  - indoor light positioning system, **83, 93, 94, 95**
  - indoor LPS, 81, 82
  - ISC transmission efficiency, **15**
  - outdoor light positioning system, 102–104, **102, 103**
  - plane tilting technique, **52**
- photodiodes (PD). *See also* image sensors
  - outdoor LPS, 94–104
  - used in most VLC systems, 135
- physical layer
  - and low-cost multimedia, 71–72
  - DMT MAC, 160, **166**
  - IEEE 802.15.7 standard, 110
  - VLC downlink, 10–37
- plane tilting technique, 41–51, **46**
- PLASA CPWG standard, 114
- PLASA E1.4.5 DMX-512A VLC standard, 109, 111
- PLASA E1.4.5 standard, 107
- pose estimation, 196–201, **197, 199, 200**
- position modulating OFDM, 157
- positioning system. *See* outdoor light positioning system,
  - indoor light positioning system
- PPM. *See* pulse position modulation
- protocol. *See also* standards
  - ALOHA, 84
  - MAC, 160
  - wired transmission, 111, 112, **112**
- proximity indoor positioning algorithm, 81, 82, **82, 83**
- pulse amplitude modulation (PAM), 16–21
- pulse position modulation (PPM)
  - and lighting constraint, 11
  - BER, 121–123
  - VLC, 116, 118
  - with dimming control, **11**
- pulse width modulation (PWM)
  - and LED dimming control technique, 60–66, **61**
  - and lighting constraint, 11
  - as simple low-cost system, 143
  - IM/DD in, 144
  - image sensors, **188**
- pulse-amplitude-modulated discrete multitone modulation (PAM-DMT), 145, 152–154, **154, 164**
- PWM. *See* pulse width modulation
- radio-frequency technology (RF)
  - and GPS, 70, 71, **72**
  - and machine-to-machine communication, 137
  - bandwidth, 73, 133
  - interference in, 5, 74
  - lighting constraint, 10
  - not energy saving, 1
  - radio-frequency identification technology (RFID), 74
  - received signal strength measurement (RSS), 76, **76, 81**
  - RF. *See* radio-frequency technology
  - Rician *K*-factor, 140–143, **142**
- scene analysis indoor positioning algorithm, **81**
- SCM. *See* subcarrier multiplexing
- signal-to-noise ratio (SNR)
  - and lamp arrangement, 51–60, **53, 55**
  - DMT, 165
  - image sensors helping, 89
  - LED clipping, 153, 154
  - plane tilting technique, 41–51, **45, 47, 48**
- simulations
  - multi-level transmission, 30–33, **32**
  - VLC lamp arrangement, **57**
- spectrally factorized OFDM, 156
- standards. *See also* protocol
  - do not include DMT, 135
  - for portable devices, 172
  - IEC, 107, 109, 111–113, **113**
  - IEEE, 6, 107, 109, 110, 112, 114, 172
  - ITU, 114, 172
  - PLASA, 107, 109, 111, 114
  - Zhaga, 109, 112
- subcarrier multiplexing (SCM), 159
- time compensation (average constant), 10, 11
- time of arrival measurement (TOA), 75, 76
- time-difference-of-arrival measurements (TDOA)
  - channel multi-access, 84
  - outdoor light positioning system, 97–98, **99**
  - triangulation, 77–79
- time-division-multi-access (TDMA), 84
- TOA. *See* time of arrival measurement
- triangulation
  - indoor, 75–81, **76, 78, 79**
  - outdoor, 202–203, **203**
- TTA VLC working group, 114
- ultra-wide band radio frequency (UWB), 74
- unipolar OFDM, 156, 164, 165
- variable pulse position modulation (VPPM)
  - BER, 124–125
  - principles of, 110–111, **111**
  - VLC, 118–119, **119**
- vehicle-to-infrastructure VLC system, 201–202, **201**
- visible light communication (VLC)
  - advantages of positioning, 73–75, **74**
  - building blocks of, 133, **134**
  - definition, 1

- visible light communication (VLC) (cont.)
  - high-speed transmission, 139–143, **142**
  - history of, 133
  - physical layer, 10–37
  - pose estimation, 198–199, **199**
  - real-time mobile, 166, 169, **169**
  - standards, 6, 107–114, **108, 110, 111, 112, 113**
- visible light communication (VLC) applications
  - hospital, 1, 5
  - IOT, 1, 4
  - ITS, 1, 4, **4**
  - machine-to-machine, **139**
  - smart city concept, 1
  - smart phone camera advertising, 1, 6
  - toys and theme park entertainment, 1, 5, **5, 6**
  - WiFi and cellular augmentation, 1–4, **2, 3**
- visible light communication (VLC) modulation
  - IPPM, 116, **119**
  - OOK, 116, **117**
  - PPM, 116, 118, **118**
  - VPPM, 116, 118–119, **119**
- VLC. *See* visible light communication
- Volterra equalization, 164
- VPPM. *See* variable pulse position modulation
- wavelength division multiplexing (WDM), 34–35, **36, 161**
- wired transmission protocol (VLC), 111, 112, **112**
- wireless fidelity (WiFi)
  - in indoor light positioning, 88
  - optical, 137, **138**
  - VLC alternative for, 41
- wireless local area network (WLAN)
  - optical WiFi in, 137, **138**
  - radio-frequency technology, 74
- wireless transmission protocol (VLC), 112
- Zhaga engine standard, 109, 112
- ZigBee, 112