

INDEX

- $1/f$ noise, *see* noise
 $ABCD$ parameters, 229
 $F_S/4$ frequency conversion, 564–568
 $\pi/4$ -QPSK, *see* modulation
 μ -law, *see* companding
- A-law, *see* companding
 absorption
 atmospheric, 93–94, 590
 ionospheric, 96
 acquisition, of phase, 124
 active mixer, *see* mixer
 adaptive differential PCM (ADPCM), 142
 adjacent channel power ratio (ACPR), 541
 admittance (Y) parameters, 229
 advanced wireless services (AWS), 587
 alias (aliasing), *see* analog-to-digital converter
 AM broadcasting, 3, 58, 482, 516, 583–584
 AM-PM conversion, 348–349
 ampliphase, 537
 amplitude modulation (AM), *see* modulation
 analog modulation, *see* modulation
 analog-to-digital converter (ADC), 11, 446–458
 alias (aliasing), 449
 aperture uncertainty, 458
 dynamic range, 453–457
 effective number of bits (ENOB), 457
 flash, 447, 448
 lowpass sampling, 451
 Nyquist zone, 449
 pipeline, 448
 sigma-delta (Σ - Δ), 448
 signal-to-noise ratio, *see* quantization
 subranging, 448
 successive approximation, 448
 timing jitter, *see* timing jitter
 undersampling, *see* undersampling
 angle modulation, *see* modulation
 antenna, 9, 17–58
 array, 54–55
 beam, 53
 beam antenna, 49–51
 cell phone, 382
 current distribution, 35
 dipole, 35–43, 221, 255, 381, 391
 dipole, $5/8$ - λ , 39
 dipole, batwing, 43
 dipole, bowtie, 42
 dipole, electrically-short (ESD), 20
 dipole, folded, 42, 55
 dipole, full-wave (FWD), 39
 dipole, half-wave (HWD), 20, 37, 49
 dipole, off-center-fed, 39, 40
 dipole, planar, 41
 dipole, sleeve, 41
 discone, 382
 electrically-small (ESA), 382–390
 equivalent circuit, 40
 feed, 51, 56, 224
 helix, axial-mode, 57
 helix, normal-mode, 57
 horn, 56, 92, 224, 381
 impedance matching, *see* impedance matching, antennas
 integration, 33–35, 363–396
 isotropic, 30
 log-periodic beam, 382
 loopstick, 58
 monopole, 43–46, 56, 255, 391, 392
 monopole, $5/8$ - λ , 45
 monopole, electrically-short (ESM), 44
 monopole, quarter-wave (QWM), 44, 45, 366, 376
 patch, 46–48, 55, 381
 planar inverted-F antenna (PIFA), 47, 386, 389
 receiving, 25, 31, 363–375
 reflector, 51–53, 56, 224–226
 resonant, 381
 temperature, 108, 208, 364
 transmitting, 21, 29
 tuner, 389–390
 turnstile, 43
 WiFi, 382
 Yagi, 49
 antenna temperature, *see* antenna
 APCO P25, *see* land mobile radio
 aperture efficiency, 52
 aperture uncertainty, *see* analog-to-digital converter
 application-specific integrated circuit (ASIC), 576
 arcing, 109
 array (antenna), *see* antenna
 array factor, 54
 ASK, *see* modulation
 atmospheric absorption, *see* absorption, atmospheric
 atmospheric noise, *see* noise
 ATSC, *see* television
 attenuation constant, 93, 234
 attenuation rate, *see* path loss
 attenuator, digital step, 481
 audio processing, 137–138
 autocorrelation, 85
 automatic gain control (AGC), 87, 122, 138, 154, 163, 179, 182, 188, 195, 462, 478–480
 fast, 136, 478
 slow, 478, 479
 available gain circle, 307
 available gain design method, 306–309
 available power, 240, 365
 axial-mode helix, *see* antenna
- backhaul, 5, 214–216
 backlobe, 48
 balanced circuit, *see* differential circuit
 balun, 35, 256–257, 390–396
 $\lambda/2$ transmission line, 394
 coaxial choke, 392–394
 ferrite choke, 394
 folded, 394
 Guanella, 256
 LC, 257, 392
 Marchand, 395
 Ruthroff, 256
 sleeve, 393
 transformer, 256, 392
 transmission line, 257, 256–257

- band-edge tracking, 188, 574
- bandwidth, 1
 - amplifiers, 332
 - analog filters, 398–399
 - analog-to-digital conversion, 447–451
 - coherence, 77–80, 86, 88, 96, 173, 197, 199
 - decreasing, 271–273
 - first null (FNBW), 148, 151
 - fractional, 380, 398
 - fundamental limit, 271
 - half-power, 266
 - impedance matching, 266–268
 - increasing, 268–271
 - noise, 100, 127
 - noise-equivalent, 153, 158
 - quality factor, 266–268, 401
 - resolution, 359
 - unity-gain, *see* transistor
- Barkhausen criteria, 489, 492
- baseband modulation, *see* modulation
- baseband representation, 115
- batwing (antenna), *see* antenna
- BCH (Bose, Chaudhuri, and Hocquenghem) coding, 177
- beam (antenna), *see* antenna
- beamforming, 54, 183
- beamwidth
 - half-power (HPBW), 36, 37, 48, 52, 216
- beat frequency, 347
- beat product, 347
- Beidou (GNSS), 594
- bias tee, 305, 325, 327
- biasing, *see* transistor
- BiCMOS, 287
- bilateral (two-port), 238
- bilateral design, 302–310
- binomial approximation, 72
- bipolar junction transistor (BJT), *see* transistor
- birdie, 471, 473
- bit error rate (BER), 160
- block code, 177
- blocking dynamic range, *see* dynamic range
- Bluetooth, 503, 592
- Boltzmann’s Constant, 100, 286
- bowtie (antenna), *see* antenna
- BPSK, *see* modulation
- branch, 182
- branch line coupler, 548
- breakpoint, 70, 73, 90
- brightness temperature, 109, 110
- broadband over power line (BPL), 109
- broadcast (link), 6
- broadcasting, 3, 55, 463, 523, 538, 583–585
- buffer, 334, 499, 539
- C-band, 3
- C4FM, *see* modulation
- cable driver, 301
- capacitor, digital step, 506
- capacity, 174
- capture threshold, 137
- carrier, 81
- carrier aggregation, 220, 588
- carrier frequency estimation, 155, 188–189, 574
- carrier phase estimation, 154, 169, 189
- carrier sense multiple access with collision avoidance (CSMA/CA), 8, 589
- Carson’s Rule, 133
- Cartesian feedback linearization, 545
- cascaded integrator comb (CIC), *see* filter, digital
- CB radio, 3, 517, 586
- cell, 8
- cellular, 3, 5, 6, 75, 142, 184, 197–200, 216–220, 345, 472, 479, 483, 484, 502, 517, 540, 586–589
- central processing unit (CPU), 513, 574
- channel coding, 139, 176–179, 219
- channel impulse response (CIR), 74–80, 185–186
- characteristic curve, *see* transistor
- characteristic impedance, *see* transmission line
- charge pump, *see* synthesizer (frequency)
- checksum, 177
- chip, 196
- Chireix, 537
- Citizen’s Band, *see* CB radio
- Clapp, *see* oscillator
- Class A, 132, 145, 524, 526–529
- Class AB, 132, 145, 524, 533–534
- Class B, 524, 526, 530–533
- Class C, 132, 145, 524, 526, 534–535
- Class D, 524, 526, 535–536
- Class E, 524, 536
- Class F, 524, 536
- Class G, 536
- Class H, 536
- Class S, 536
- clipping (ADC), 448, 460
- coaxial choke balun, *see* balun
- code division multiple access (CDMA), 5, 8, 196–199, 220, 345, 478, 479, 484, 503, 534, 540, 541, 543, 587
- code excited linear prediction (CELP), 142
- code rate, 177
- codec, 143
- codeword, 177
- coding gain, 178
- coefficient, reflection, 64
- coherence bandwidth, *see* bandwidth, coherence
- coherence distance, 87
- coherence time, 84, 87, 90, 121, 193, 478
- coherent demodulation
 - of AM, 122–125
 - of digital modulations, 154–155, 187
 - sensitivity, 125
- collector efficiency, *see* power amplifier, efficiency
- collector feedback stabilization, 292
- color dot, *see* land mobile radio
- Colpitts oscillator, *see* oscillator
- common mode interference, 255
- commutator, 561
- companding, 142
 - μ -law, 142
 - A-law, 142
- complementary code keying (CCK), *see* modulation
- complementary error function, 159
- complementary metal–oxide semiconductor (CMOS), 287, 333–334
- complex baseband representation, 115–118, 440
- compression (of data), 139, 141
- compression point, 1 dB, 342–343, 346–347
- conduction angle, 524, 533
- conductivity, 64
- constant modulus (CM), 524, 534
- constellation diagram, 144
- continuous wave (CW), 139
- continuously-variable slope delta modulation (CVSDM), 142
- convolution coding, 178
- CORDIC, 513
- correlation receiver, 156, 172, 196
- cosmic microwave background (CMB), 110, 111
- COST231 model, *see* path loss
- Costas loop, 124, 189
- crest factor, 540
- crystal, 426, 482, 504, 514
- cumulative distribution function (CDF), 82
- current mode, 35, 253
- current moment, 18
- current source array, 519
- cutoff frequency, *see* filter, analog
- cyclic prefix, 200

- dBm/Hz, 357
 DC current gain, 286
 decimation, 561–564
 decision feedback equalization, *see* equalization
 decision metric, 154, 156, 168, 182, 186
 decision rule, 158, 163
 decision threshold, 158, 163
 DECT, 172, 503
 DECT1800, 172
 DECT1900, 172
 deemphasis, 136
 delay filter, *see* filter, digital
 delay spread, 76–77, 86, 88, 96, 185, 198
 delay spread, root mean square (RMS), 77
 delay-locked loop (DLL), 573
 derotation, 123, 125, 169, 179, 182, 188
 despreading, 196
 device-to-device (D2D) communications, 589
 dibit, 144
 differential amplifier, 333
 differential BPSK (DBPSK), 169
 differential circuit, 35, 253–257
 impedance matching, 274
 in ADC, 457
 in DAC, 519
 in phase-switching mixer, 436
 differential coding, 168
 differential detection, 167–170
 differential PCM (DPCM), 142
 differential QPSK (DQPSK), 169, 592
 diffraction, 52, 67, 88
 Digital Enhanced Cordless Telecommunications, *see* DECT
 digital modulation, *see* modulation
 Digital Radio Mondiale (DRM), 584, 585
 digital signal processing (DSP), 550–576
 digital video broadcasting – terrestrial (DVB-T), *see* television
 digital-to-analog converter (DAC), 10, 512, 518–523
 diode detector, 122
 diode, tuning, *see* varactor
 diplexer, 415, 434
 dipole, *see* antenna, dipole
 Dirac delta function, 18, 339
 direct broadcast satellite, 94, 224–226, 484, 585
 direct conversion, 117, 475–477, 517, 550
 direct digital synthesis (DDS), 511–513
 direct method (of FM modulation), 135
 direct sampling, *see* receiver
 direct sequence spread spectrum (DSSS), 8, 195–199, 587, 589, 592
 directivity, 29, 37, 48, 52
 director, 49
 discrete Fourier transform (DFT), 200
 dispersion (dispersive response), 413
 dither (dithering), 456
 diversity, 84, 87, 181–184
 Doherty, 537
 Doppler shift, 81, 84, 173, 188
 Doppler spread, 81, 87, 201
 double-balanced mixer, *see* mixer
 downconversion, 430–431, 446
 drain efficiency, *see* power amplifier, efficiency
 driver (antenna), 49
 dual modulus, 509
 ducting, 97
 duplexer, 6
 dynamic range, 359–361
 blocking, 360, 453
 quantization, 453
 spurious-free (SFDR), 360, 457
 E-plane, 29, 48
 early-late synchronizer, 573
 Ebers–Moll model, 286
 Edwards–Sinsky metric, 247
 effective aperture, 28, 37, 52, 92
 effective height, 28
 effective isotropic radiated power (EIRP), 206, 379–380
 effective length, 26, 37, *see also* vector effective length
 effective number of bits (ENOB), *see* analog-to-digital converter
 effective radiated power (ERP), 14, 206–207, 379
 electric field, 16, 18, 26, 29, 46
 electrically-short dipole, *see* antenna
 electrically-short monopole, *see* antenna
 emitter degeneration, 294–297
 emitter follower, *see* transistor
 emitter induction, *see* inductive degeneration
 encryption, 139, 141
 energy efficiency, 127, 174–178
 energy per bit, 152, 209
 enhanced variable rate codec (EVRC), 142
 envelope, *see* modulation
 envelope detection, 121, 135, 480
 envelope elimination and restoration (EER), 537
 equal-gain combining, 181
 equalization
 adaptive, 187
 decision feedback (DFE), 185
 least mean squares (LMS), 187
 minimum mean square error (MMSE), 186–187, 194, 574
 recursive least squares (RLS), 187
 zero-forcing, 185, 185
 error control coding, 141, 177, 181, 192
 error correcting capability, 177
 error vector magnitude (EVM), 542
 Euler’s formula, 115
 exciter, 10
 external noise dominance, *see* noise, external
 external temperature, 208
 extinction, *see* path loss
 fade margin, 221
 fading, 79–87, 89–90
 fast, 82, 132
 flat, 81, 154, 179–184
 frequency-selective, 79
 ionospheric, 96
 log-normal, 91
 Nakagami, 90
 Rayleigh, 83
 Ricean, 89
 slow, 91
 two-ray, 89
 Family Radio Service (FRS), 586
 Fano–Bode relation, 271, 385, 387–389
 far field, 19
 fast fading, *see* fading
 fast Fourier transform (FFT), 200, *see also* filter, digital
 Federal Communications Commission (FCC), 205
 feed (antenna), *see* antenna
 feedback linearization, 544–546
 feedforward linearization, 543–544
 femtocell, 220
 field effect transistor (FET), *see* transistor
 field programmable gate array (FPGA), 513, 575–576
 fifth-generation (5G) cellular, 588, 591
 filter, analog
 absorptive, 399
 allpass, 397
 bandpass, 397, 400–402, 407–409, 411, 421, 422
 bandstop, 397, 409–411
 bandwidth, *see* bandwidth, analog filters
 Bessel, 415
 Butterworth, 404–410
 Cauer, 415
 ceramic, 427
 Chebyshev, 410–412

- coaxial, 425
- coupled resonator, 424
- crystal, 426
- cutoff frequency, 398
- definition, 397
- dielectric resonator, 427
- distributed, 418–425
- elliptic, 415
- equiripple, *see* Chebyshev
- Gaussian, 415
- group delay, 399, 413
- helical, 425
- highpass, 397, 399, 401, 405–407, 411
- interdigital, 424
- lowpass, 397, 399, 401, 404–405, 411–412, 419–420
- maximally flat, *see* Butterworth
- mechanical, 427
- notch, 397, 401–402, 423
- order, 398, 410
- passband, 398
- reflective, 399, 415
- stepped impedance, 425
- stopband, 398
- surface acoustic wave (SAW), 427
- tracking, 427, 464, 483
- transition band, 398
- tubular, *see* filter, analog, coaxial
- Zolotarev, 415
- filter, digital
 - Butterworth, 559
 - cascaded integrator comb (CIC), 563
 - Chebyshev, 559
 - delay, allpass, 559, 573
 - design using FFT method, 558, 559
 - design using windows, 555–558
 - elliptic, 559
 - finite impulse response (FIR), 186, 550–574
 - halfband, 560, 566
 - infinite impulse response (IIR), 550–551, 559, 574
 - multirate, 560–574
 - order, 552
 - Parks–McClellan algorithm, 559
- finger, 76, 198
- finite alphabet, 140
- finite impulse response (FIR) filter, *see* filter
- finite-difference time-domain (FDTD), 25, 37, 41, 43, 50
- fixed bias, *see* transistor
- flat earth, 68
- flat fading, *see* fading, flat
- flicker FM, 502
- flicker noise, *see* noise
- FM broadcasting, 3, 134, 137, 469, 470, 477, 482, 504, 516, 583–584
- FNBW, *see* bandwidth
- folded dipole, *see* antenna
- forward error control (FEC), *see* error control coding
- forward power gain, 235
- forward-active mode, 286, 290
- Foster–Seeley discriminator, 135
- fourth-generation (4G) cellular, 588, 591
- FR4, *see* printed circuit board (PCB)
- fractional bandwidth, *see* bandwidth
- frequency deviation, 133
- frequency diversity, 200
- frequency divider, 508
- frequency division multiple access (FDMA), 5, 7, 588
- frequency hopping spread spectrum (FHSS), 8, 589, 592
- frequency modulation, *see* modulation
- frequency stability, 504
- frequency-division duplexing (FDD), 5
- frequency-selective fading, *see* fading, frequency selective
- Friis transmission equation, 62–63, 203–205
- front-to-back ratio, 48
- full quieting, 137
- full-duplex, 5
- full-wave dipole, *see* antenna
- fundamental (tone), 342
- gain
 - available, 306
 - conversion, *see* mixer
 - DC current, *see* DC current gain
 - forward, *see* forward power gain
 - maximum available, *see* maximum available gain
 - maximum stable, *see* maximum stable gain
 - maximum unilateral, 310
 - normalized available, 307
 - operating, 309
 - receiver specification, 459–462
 - reverse, *see* reverse power gain
 - transducer, *see* transducer power gain
 - varying, 480–481
- gain (antenna), 30
- gain compression, 242, 342–343, 359
- gain over temperature (G/T), 211
- Galactic noise, *see* noise
- GALI-74, 107, 333
- Galileo (GNSS), 594
- gamma match, 51
- geometrical optics, 51
- Gibbs phenomenon, 554
- Gilbert cell mixer, *see* mixer
- global navigation satellite systems (GNSS), 483, 594–595
- global positioning system (GPS), 46, 196–197, 466–468, 484, 594–595
- Global System for Mobile Communications, *see* GSM
- GLONASS, 196, 595
- GMSK, *see* modulation
- graphics processing unit (GPU), 575
- Gray coding, 144
- ground plane, 43, 45, 46
- groundwave, 66
- group delay, *see* filter, analog
- GSM, 172, 345, 386, 472, 473, 503, 587
- GVA-81, 107
- H-plane, 29, 48
- half-duplex, 5
- half-IF problem, 470
- half-power beamwidth (HPBW), *see* beamwidth
- half-wave dipole, *see* antenna
- halfband filter, *see* filter, digital
- Hamming distance, 177
- harmonic
 - second-order, 342
 - third-order, 342
- harmonic filtering, *see* power amplifier
- Hartley method, 128, 193, 442–443, 474
- Hartley oscillator, *see* oscillator
- Hata model, *see* path loss
- helix (antenna), *see* antenna
- high-side injection, 430
- Hilbert transform, 130, 193
- horizon, radio, *see* radio horizon
- horn antenna, *see* antenna
- hybrid (Y) parameters, 229
- hybrid (microwave device), 441, 546–548
- hybrid- π model, *see* transistor
- I-Q imbalance, 441, 475
- IEEE 802.11, 589
- IEEE 802.11a, 200, 590
- IEEE 802.11ac (VHT), 590–591
- IEEE 802.11ad (WiGig), 590–591
- IEEE 802.11af (TVWS), 591
- IEEE 802.11b (Wi-Fi), 589–590
- IEEE 802.11g, 200, 590
- IEEE 802.11n, 590
- IEEE 802.15.1, *see* Bluetooth
- IEEE 802.15.4, *see* ZigBee
- IEEE 802.16 (WiMAX), 591
- image frequency, 432–433
- image rejection, *see* mixer
- image theory, 43
- impedance (Z) parameters, 229

- impedance buffer, *see* buffer
- impedance inversion, 283, 420–422, 536
- impedance inverter, *see* impedance inversion
- impedance matching, 33–35, 259–283
 - antennas, 380–390
 - conjugate matching, 259
 - double stub, 282
 - power amplifier loads, 538–539
 - quarter wave, 282
 - reflectionless, 259, 279
 - resistive, 260
 - single stub, 278–282
 - two reactance (“L”), 261–265
 - two-reactance cascades, 268–273
 - using transformers, 260–261
- improved multiband excitation (IMBE), 142
- impulse modulation, *see* modulation
- impulse response, channel, *see* channel impulse response (CIR)
- In Band On Channel (IBOC), 583
- incoherent demodulation
 - of AM, 121–122
 - of FSK, 173
 - of OOK, 162–163
 - sensitivity, 126
- indirect method (of FM modulation), 135
- induction, *see* inductive degeneration
- inductive degeneration, 321–322
- infinite impulse response (IIR) filter, *see* filter
- Inmarsat, 142, 587
- input matching network (IMN), 301
- insertion loss (IL), 236
- instability, 242
- instantaneous frequency, 132
- integrated circuit (IC), 12, 333–334, 482–484, 519, 575–576
- intercept point
 - second-order, 347–348
 - third-order, 344–347
- interference, 109
- interleaving, 180–181
 - convolutional byte, 192
- intermediate frequency (IF), 429
- intermediate frequency (IF) sampling, *see* receiver
- intermodulation, 343–348
 - second-order, 344, 347–348, 476
 - third-order, 344–347
- International Telecommunications Union (ITU), 2, 111
- internet of things (IoT), 589
- interpolation, 562–563
 - zero-fill, 562
 - zero-order hold (ZOH), 562
- interstage matching network (ISMN), 333
- intersymbol interference (ISI), 86, 147, 185, 187, 198
- inverse discrete Fourier transform (IDFT), 200, 559
- inverse fast Fourier transform (IFFT), 200, 559
- inverse hybrid parameters, 229
- ionosphere, 95
 - layers, 96, 221
- Iridium, 142, 188, 473, 587
- irregular terrain model (ITM), *see* path loss
- IS-54, 503
- ISDB-T, *see* television
- isotropic, *see* antenna
- Johnson noise, *see* noise
- Johnson–Nyquist noise, *see* noise, Johnson
- Jupiter, 110, 111
- K-band, 3
- Ka-band, 3
- Kahn EER, *see* envelope elimination and restoration
- Kahn modulation, *see* envelope elimination and restoration
- Kirchoff’s Voltage Law (KVL), 291
- klystron, 285
- Ku-band, 3
- L-band, 3
- land mobile radio (LMR), 3, 5, 6, 55, 69, 134, 137, 142, 210, 345, 353, 366, 379, 462, 474, 552, 585–586
 - APCO P25, 585, 586
 - color dot frequency, 462, 465
 - TETRA, 585, 586
- Lange coupler, 548
- latency, 181
- lead zirconate titanate (PZT), 506
- Lee model, *see* path loss
- lightning, 110, 111
- limiting, 136
- linear amplification using non-linear components (LINC), 537
- linear modulation, *see* modulation
- linear prediction (source coding), 142
- linearity, 13, 338–340
 - mixer, *see* mixer
- link budget, 211–226
- link margin, 215–216
- load pull, 539
- local oscillator (LO), 10, 429
- log-normal fading, *see* fading
- logarithmic amplifier, 480
- long term evolution (LTE), 200, 201, 586, 588
- Longley–Rice model, *see* path loss
- loopstick (antenna), *see* antenna
- low noise block (LNB), 224–226
- low-density parity-check (LDPC) coding, 178
- low-noise amplifier (LNA), 11, 301, 314–318, 320–332
 - bypassing, 479, 481
- low-side injection, 430, 470
- lower sideband (LSB), *see* modulation
- machine-to-machine (M2M) communications, 589
- magnetic field, 16, 29
- main lobe, 48
- Marchand balun, *see* balun
- matched filtering, 151, 154–156
- maximal ratio combining (MRC), 86, 181–184, 198
- maximum a posteriori (MAP), 156
- maximum available gain (MAG), 247
- maximum effect time (MET), 147, 149, 190, 572
- maximum likelihood (ML), 156
- maximum likelihood sequence estimation (MLSE), 185–186, 574
- maximum stable gain (MSG), 248–250
- maximum useable frequency (MUF), 96
- Maxwell’s equations, 17, 25
- mechanical filter, *see* filter, analog
- memoryless system, 340
- meteor scatter, 96
- method of moments, 25, 37, 41, 43, 50
- microelectromechanical systems (MEMS), 390
- microstrip line, *see* transmission line
- Miller modulation, *see* modulation
- minimum discernible signal (MDS), 355–359
- mixed excitation linear prediction (MELP), 142
- mixer, 433–439
 - active, 435, 438–439
 - conversion gain, 437
 - double-balanced diode ring, 436–438
 - Gilbert cell, 438
 - image rejection, 442–444
 - linearity, 437
 - LO isolation, 437
 - noise figure, 437
 - phase-switching, 435–436
 - square-law, 433–435
 - VSWR, 437
- MMSE, *see* equalization

- modulation, 87
 $\frac{\pi}{4}$ -DQPSK, 592
 $\frac{\pi}{4}$ -QPSK, 145, 535, 585, 586
 amplitude (AM), 535
 amplitude (defined), 118
 amplitude-shift keying (ASK), 143, 164–165, 189, 193, 535, 592
 analog (defined), 114
 angle, 115
 baseband, 114
 binary frequency shift keying (BFSK), 171–173
 binary phase shift keying (BPSK), 143, 157–160, 162, 168–169, 179, 182–183, 189, 221, 535
 complementary code keying (CCK), 589
 continuous 4-level frequency (C4FM), 585, 586
 digital (defined), 114, 139
 double sideband large carrier (DSB-LC) AM, 115, 118–120, 584–586
 double sideband suppressed carrier (DSB-SC) AM, 115, 120
 envelope, 121
 frequency (FM), 115, 132–137, 349, 524, 534, 540
 frequency-shift keying (FSK), 170–173, 534, 585, 586, 592
 frequency, narrowband (NBFM), 134, 210, 586, 587
 frequency, wideband (WBFM), 134, 584
 Gaussian frequency shift keying (GFSK), 592
 Gaussian minimum shift keying (GMSK), 172, 534, 587
 impulse, 114
 linear, 115, 118
 lower sideband (LSB), 127
 memoryless, 154
 Miller, 594
 minimum-shift keying (MSK), 171–173, 524, 534, 540
 multicarrier, *see* multicarrier modulation
 offset QPSK (OQPSK), 144, 535, 592
 on-off keying (OOK), 143, 157, 160–163, 189
 phase (PM), 115
 phase shift keying (PSK), 143, 166–167, 349, 535, 540, 592
 phase-amplitude, 143, 146, 151, 152, 154, 540
 pilot-assisted, 131
 pulse, 114
 quadrature, 115, 130
 quadrature amplitude (QAM), 143, 165–166, 201, 349, 502, 535, 588
 quadrature phase shift keying (QPSK), 143–145, 163–164, 219, 535, 587, 588
 single sideband (SSB), 115, 127–131, 193, 524, 535, 585
 sinusoidal carrier, 115, 143
 trellis-coded, *see* trellis-coded modulation (TCM)
 upper sideband (USB), 127
 vestigial sideband (VSB), 115, 131
 modulation index, 133
 moment method, *see* method of moments
 monolithic microwave integrated circuit (MMIC), 107, 333, 346, 348
 monopole, *see* antenna, monopole
 Moon, 110
 MPEG-2, 143, 191
 MPEG-4, 143
 MSK, *see* modulation
 multicarrier modulation, 199
 multipath, 68, 73–87, 185, 200
 multiple access, 7
 multiple-input multiple-output (MIMO), 184–185, 588, 590
 multiplexer, 417, 464
 multiplier, four-quadrant, *see* mixer, Gilbert cell
 multirate filter, *see* filter, digital
 Nakagami fading, *see* fading
 nanocell, 220
 navigation, 3
 near-vertical incidence skywave (NVIS), 220–224
 near-zero IF, *see* receiver
 negative resistance oscillator, *see* oscillator
 neutralization, 313
 noise
 $1/f$, 101
 amplifier (example), 105
 anthropogenic, 108, 111–112
 atmospheric, 110, 111
 external, 108–112, 138, 222, 364
 flicker, 101
 floor, 213, 358–359
 Galactic, 110, 222
 Johnson, 99
 natural, 108–111
 non-thermal, 101–102
 shot, 101
 terrain, 110
 thermal, 99–101, 213
 voltage spectral density, 100
 noise blanking, 138
 noise factor, 103
 noise figure, 103–108, 314–318, 373
 mixer, *see* mixer
 noise figure circle, 316–318
 noise resistance, 314
 noise temperature, 101–108
 noise temperature, input-referred, 104
 noise temperature, reference (T_0), 104
 non-thermal noise, *see* noise
 normal-mode helix, *see* antenna
 normalized capacity, *see* capacity
 NTSC, *see* television
 numerically-controlled oscillator (NCO), 125, 135
 Nyquist criterion for zero ISI, 148, 155
 Nyquist sampling criterion, 448–451, 522, 552
 Nyquist zone, *see* analog-to-digital converter
 OFDM, *see* orthogonal frequency division multiplexing (OFDM)
 off-center-fed (dipole), *see* antenna
 offset binary, 447, 519
 OOK, *see* modulation
 operating gain design method, 306, 309–310
 operating point, 286, 322, 339, 341
 operational amplifier (op-amp), 334, 347, 514
 OQPSK, *see* modulation
 orthogonal frequency division multiplexing (OFDM), 199–201, 540, 584, 588, 590
 oscillation, 242, 486
 oscillator, 9, 241, 242
 Butler, 505
 Clapp, 500, 505, 507
 Colpitts, 489, 491–499, 507
 crystal, 504–506
 grounded base, 491–499
 Hartley, 490, 500
 IC implementation, 513–514
 LC feedback, 486–499
 negative resistance, 507
 oven-controlled crystal (OCXO), 506
 phase-shift, 514
 relaxation, 488, 514
 ring, 514
 starting problem, 489, 492, 495, 497
 temperature-compensated crystal (TXCO), 506
 voltage-controlled, *see* voltage-controlled oscillator
 Wein bridge, 514
 outphasing, 537

- output matching network (OMN), 301
 oxygen absorption, *see* atmospheric absorption
- P-band, 3
 P25, *see* land mobile radio
 PAL, *see* television
 parity, 177
 Parks–McClellan algorithm, *see* filter
 passband, *see* filter, analog
 patch (antenna), *see* antenna
 path gain, 63
 path loss, 61
 associated with effective aperture, 92, 92
 attenuation rate, 93
 average, 63, 90–91
 COST231 model, 91, 217, 582
 empirical, 91
 extinction, 93
 free space, 60–62, 578, 580
 Hata model, 91, 580–582
 irregular terrain model (ITM), 91
 Lee model, 91
 location-specific, 91
 Longley–Rice model, 91
 media loss, 93–94
 median, 63
 rain fade, 94
 two-ray, 72–73, 578, 580
 pattern, 29, 31
 pattern multiplication, 55
 peak-to-average power ratio (PAPR), 201, 540, 588
 permeability, 64
 permittivity, 64
 permittivity, relative, 276
 personal area network (PAN), 592
 personal communications services (PCS) band, 587
 phase comparator, 135, 508, *see also* synthesizer (frequency)
 phase modulation, *see* modulation
 phase noise, 500–502
 single sideband (SSB), 501
 phase velocity, 276
 phase-locked loop (PLL), 124, 135, 190, 544, *see also* synthesizer (frequency)
 phasor, 21
 physical aperture, 52
 picocell, 220
 pilot-assisted modulation, *see* modulation
 planar dipole, *see* antenna
 planar inverted-F antenna (PIFA), *see* antenna
 Planck’s Law, 100
- plane of incidence, 64
 plane wave, 22, 60
 point-to-point, 6
 polar feedback linearization, 544
 polarization, 32–33, 204
 circular, 32
 elliptical, 33
 linear, 32
 polarization diversity, 184
 power amplifier (PA), 10, 92, 145, 172, 201, 523–549
 back off, 540
 classes of operation, 525–536
 conduction angle, *see* conduction angle
 drive level, 539
 driver, 539
 efficiency, 523–525
 harmonic filtering, 529, 531
 linear, 524
 linearization, 541–546
 load impedance matching, *see* impedance matching
 non-linear, 524
 power handling, 539
 push-pull, 531–533
 quasi-linear, 524, 527
 subranging, 541
 switched, 524
 thermal management, 529
 power available, *see* available power
 power control, 87, 540–541
 power delay profile (PDP), 75
 power density, spatial, 22, 205
 power measurement, 480
 power-added efficiency (PAE), 525
 predistortion, 541–543
 preemphasis, 136–137
 prescaler, *see* synthesizer (frequency)
 preselection, 301, 462–465
 fixed, 463
 tuning (or tracking), 463, 466
 printed circuit board (PCB), 41, 47, 276
 FR4, 277, 309
 processing gain, 196, 197
 product detection, 123
 propagation constant, 234
 PSK, *see* modulation
 pulse
 cosine, 148
 Gaussian, 172
 raised cosine, 149–151
 rectangular, 146, 148, 172, 521
 sinc, 147–148, 521, 551
 sinusoidal, 172
 square root raised cosine, 156, 193
 triangular, 148, 554
 pulse code modulation (PCM), 141
- pulse interval encoding (PIE), 593
 pulse modulation, *see* modulation
 pulse shaping, 147–151, 572
 push-to-talk (PTT), 5, 586
- QAM, *see* modulation
 QPSK, *see* modulation
 quadrature downconversion, 154, 440–442, 475, 484, 545, 564–572, *see also* direct conversion
 quadrature hybrid, *see* hybrid
 quadrature imbalance, *see* I-Q imbalance
 quadrature modulation, *see* modulation
 quadrature splitter/combiner, 441
 quality factor, 264, 267–268, 270, 401
 quantization noise (error), 451–457, 459, 523
 quantization signal-to-noise ratio (QSNR), 452, 523
 quantization, uniform, 452
 quantizer, 447
 quarter-wave monopole, *see* antenna
 quiescent (Q) point, 286
 quieting, 137
- radar, 3, 595
 radiation efficiency, 24, 30, 47, 204–205
 radiation resistance, 22, 364
 radio astronomy, 595
 radio frequency identification (RFID), 3, 468, 593–594
 radio frequency integrated circuit (RFIC), 12, 476, 514
 radio horizon, 87
 rain fade, *see* path loss
 raised cosine pulse, *see* pulse
 rake receiver, 198
 random walk FM, 501
 ray optics, *see* geometrical optics
 Rayleigh distribution, 83, 87
 Rayleigh fading, *see* fading
 Rayleigh–Jeans approximation, 100
 reactance modulation, 135
 receiver, 9
 “divide and conquer”, 474
 architectures, 465–477
 direct conversion, *see* direct conversion
 direct sampling, 465–466
 general coverage, 483
 IF sampling, 468–484
 near-zero IF, 476
 superheterodyne, 468–475, 482
 tuned RF, 468
 up-down superheterodyne, 473–474, 482
 reciprocal mixing, 502
 reciprocity, 26, 49, 55, 238

Reed-Solomon coding, 177, 192	signal-to-noise ratio (SNR), available, 366	superheterodyne, <i>see</i> receiver
reference impedance, 232	signaling, 141	symbol energy, 152
reference temperature, <i>see</i> noise temperature, reference	simplex, 4, 6	symbol timing, 189–191, 572–574
reflection coefficient, <i>see</i> coefficient, reflection	simultaneous conjugate matching, 247–248	synthesizer (frequency) charge pump, 510 fractional-N, 509 IC implementation, 513–514 integer-N, 508–509 lock range, 510, 511 phase comparator, 510 phase noise, 501, 503, 511 phase-frequency detector (PFD), 510 phase-locked loop (PLL), 482, 507–511 prescaler, 511
reflector (antenna), <i>see</i> antenna	SINAD, 210	system temperature, 208–209, 355, 459
reflector (beam antenna component), 49	sinc distortion, 522–559	
refraction, ionospheric, 95	single sideband (SSB), <i>see</i> modulation	tank (circuit), 490, 531
remote keyless entry (RKE), 592	single-carrier FDMA (SC-FDMA), <i>see</i> <i>also</i> long term evolution	Taylor series, 340
remote sensing, 595	single-ended circuit, 35, 253	television ATSC, 188, 191–195, 584 broadcast frequencies, 463, 465 DVB-T, 201, 584 ISDB-T, 584 NTSC, 585 PAL, 585 SECAM, 585 tuner, 482–483
repeater, 6	sinusoidal carrier modulation, <i>see</i> modulation	television white space (TVWS), <i>see</i> IEEE 802.11af
resolution bandwidth, <i>see</i> bandwidth	skywave propagation, 95, 97, 137	TETRA, <i>see</i> land mobile radio
resonance, 267, 400, 488	sleeve dipole, <i>see</i> antenna	thermal noise, <i>see</i> noise
resonance, piezoelectric, 426	slope detection, 135	thermal runaway, 292
resonator ceramic, <i>see</i> resonator, dielectric crystal, <i>see</i> crystal dielectric, 427, 506, 514 LC, 486–488 piezoelectric ceramic, 506 surface acoustic wave (SAW), 506, 514 yttrium iron garnet (YIG), 506	slow fading, <i>see</i> fading	thermal stability, 291
resource block, <i>see</i> long term evolution (LTE)	Smith chart, 244	thermal voltage, 286
return loss (RL), 237	Snell’s law, 64	third-generation (3G) cellular, 587
reverse isolation, 236	SNR per bit, 154, 209	threshold effect, 137
reverse power gain, 236	software radio, 11	TIA-603, 210
Ricean fading, <i>see</i> fading	software-defined radio (SDR), <i>see</i> software radio	time division multiple access (TDMA), 5, 7, 585–587
Rollett stability factor, 246	source coding, 10, 139, 141–181	time-division duplex (TDD), 6
	source induction, <i>see</i> inductive degeneration	timing jitter analog-to-digital converter (ADC), 458 frequency synthesizer, 501
S-band, 3	space-time coding, 181	tire pressure monitoring system (TPMS), 592
SA602A (IC), 439	spatial diversity, <i>see</i> diversity	toll quality, 142
sample and hold (S/H), 447	spectral efficiency, 2, 151, 174–177 of ATSC, 194	tracking filter, <i>see</i> filter, analog
satellite, 62, 205, 206, 211, 224, 473, 484, 587	spectral purity, 14	training sequence, 169, 186, 187, 191, 192, 197
scattering (s) parameters, 229–235, 289, 290	spectral regrowth, 541	transceiver, 518
SECAM, <i>see</i> television	spectrum, 2	transconductance, 493
second-generation (2G) cellular, 587	spherical wave, 60, 65	transducer power gain (TPG), 34, 204, 239–242
sector diversity, 184	SPICE, 290	transformer, 260–261
selection combining, 86, 181	spillover, 52	transistor 2N3904, 290, 495
selectivity, 11, 14, 266, 397, 404, 414, 465	sporadic E, 96	
self bias, <i>see</i> transistor	spread spectrum, <i>see</i> direct sequence spread spectrum (DSSS)	
sensitivity, 13, 210–211, 459–460	spreading, 196	
sensitivity, formal, 210, 355	spurious-free dynamic range, <i>see</i> dynamic range	
Shannon Bound, 174	square law (device), 433	
Shannon–Hartley theorem, 174	square root raised cosine, <i>see</i> pulse squelch, 137	
shape factor, 399	stability, 241–247 circle, 245–246 circle, input, 245 circle, output, 245 conditional, 243 conditions for, 243 unconditional, 243, 246–247	
shift register, 552	stabilization, 252, 313–314, 324	
shortwave, 584, 585	stopband, <i>see</i> filter, analog	
shot noise, <i>see</i> noise	Sun, 110	
sidelobe, 48	Super Wi-Fi, <i>see</i> IEEE 802.11af	
sigma-delta (Σ - Δ), <i>see</i> analog-to-digital converter		
signal space representation, 170		

- transistor (cont.)
 - alternatives to Si for bipolar, 287
 - AT-41511, 244–246, 248, 249, 252, 258, 290
 - ATF-34143, 300
 - ATF-54143, 298
 - BFG540W, 320–332
 - BFU725F/N1, 314, 316
 - bias, active, 298
 - bias, fixed, 291–292
 - bias, self, 292–294, 297–298, 327
 - bias, voltage divider, 295–298
 - biasing, 287, 289–300
 - bipolar junction (BJT), 285–287, 320, 340, 343
 - characteristic curve, 289
 - common base, 301
 - common collector, 301
 - common drain, 301
 - common emitter, 289
 - common gate, 301
 - common source, 298
 - depletion mode FET, 288
 - emitter follower, 301
 - enhancement mode FET, 288
 - field effect (FET), 288–289, 343
 - heterojunction bipolar (HBT), 287, 333
 - high electron mobility (HEMT), 288
 - hybrid- π model, 493
 - indium gallium phosphide (InGaP), 333
 - junction FET (JFET), 289
 - laterally-diffused MOS (LDMOS), 289
 - material compositions for FET, 289
 - metal–epitaxy–semiconductor FET (MESFET), 288
 - metal–oxide semiconductor FET (MOSFET), 288
 - modulation doped FET (MODFET), 289
 - pseudomorphic HEMT (PHEMT), 289, 298–300
 - unity-gain bandwidth, 287
- transition band, *see* filter, analog
- transmission (t) parameters, 229, 250–251
- transmission line
 - characteristic impedance, 275, 277
 - coaxial, 255, 391–396
 - filters, 418–425
 - input impedance, 275
 - microstrip line, 276–278
 - parallel wire, 255
 - properties, 275–276
 - stub, 278, 418–424
- transmit efficiency, 377–380
- transmitter, 9
- traveling wave tube, 285
- trellis-coded modulation (TCM), 178, 192
- tribit, 144
- tropospheric scatter, 97
- trunking, 585
- tuned RF, *see* receiver
- tuner, 446, 482, *see also* receiver
- turbo code, 179
- turnstile (antenna), *see* antenna
- TV broadcasting, 3, 5, 584
- two’s complement, 447, 519
- two-port
 - definition, 229
 - noise characterization, 103–106
 - parameters, 229
- two-ray fading, *see* fading
- ultrawideband (UWB), 114
- unbalanced circuit, *see* single-ended circuit
- undersampling, 451, 457, 564
- unilateral (two-port), 238, 310
- unilateral design, 310–313
- unilateral figure of merit, 311
- unilateralization, 313
- unity-gain bandwidth, *see* transistor
- upconversion, 431–432
- upper sideband (USB), *see* modulation
- V-band, 3
- vacuum tube, 285
- varactor, 135, 390, 427, 506, 514
- variable gain amplifier, 481
- varicap, *see* varactor
- vector effective length, 26, 364
- Very High Throughput (VHT), *see* IEEE 802.11ac
- very small aperture terminal (VSAT), 55
- Viterbi algorithm, 186, 574
- vocoder, 142
- voltage reflection coefficient, 34
- voltage standing wave ratio (VSWR), 34, 319–320, 375–377, 389
- voltage standing wave ratio (VSWR) circle, 320
- voltage-controlled oscillator (VCO), 125, 135, 506–507
- W-band, 3
- wave equation, 17
- waveform table, 512
- wavelength, 1
- wavenumber, 18, 235
- Weaver method, 127, 444, 474
- White-Fi, *see* IEEE 802.11af
- Wi-Fi, *see* IEEE 802.11b
- WiGig, *see* IEEE 802.11ad
- WiMAX, *see* IEEE 802.16
- window, *see also* pulse
- windowing, 554–558
 - Bartlett, 555
 - Blackman, 555
 - Hamming, 555
 - Hann, 555
 - Kaiser, 555–558
 - rectangular, 555
 - triangular, 554
- wireless local area network (WLAN), 3, 55, 196, 200, 483, 503, 540, 589–591
- wireless metropolitan area network (WMAN), 589–591
- X-band, 3
- Yagi (antenna), *see* antenna
- zero-crossing detection, 136
- zero-fill interpolation, *see* interpolation
- zero-forcing equalization, *see* equalization
- zero-order hold (ZOH) interpolation, *see* interpolation
- ZigBee, 592