

Index

- approximation algorithm, 74–7
- artificial transmission lines. *See* composite right/left handed (CRLH) transmission lines
- asynchronously tuned resonators, 71
- attenuation constant, 112, 245
- attenuation poles. *See* transmission zero
- Cauer I and II forms, 71
- central frequency, 71
- characteristic functions, 6, 69
- characteristic impedance, 29, 111, 230, 274
- characteristic polynomials, 7, 69
- collision frequency. *See* damping factor
- complex propagation constant, 112, 245
- composite right/left handed (CRLH) transmission lines, 49, 232, 273–8, *See also* metamaterials
- convergence
  - condition, 79
  - limit, 82
  - time, 8
- coupling
  - anti-parallel, 118
  - aperture, 266
  - coefficient, 7
  - cross, 7
  - electric, 166
  - iris, 302
  - magnetic, 166
  - matrix, 7
  - mixed, 166
  - parallel, 118
  - self-, 7
  - source-load, 31
- critical points, 76–7
- critical temperature, 48
- cut-off frequency, 236, 275
- damping factor, 232
- defected ground structures, 47, 266
- design of metamaterials, 232
- destructive interference, 44, 203
- dielectric permittivity, 230
- dispersion, 232
- double-negative metamaterials (DNG), 230
- double-positive metamaterials (DPS), 230
- Drude model, 233
- dual-composite right/left handed (DCRLH) transmission lines, 295
- effective permeability, 230
- effective permittivity, 230
- electric field, 236–7, 242
- electric wall, 199
- epsilon-near-zero metamaterials, 235–7
- epsilon-near-zero propagation, 238–43
- even/odd mode analysis, 26
- external quality factor, 163
- Fabry–Perot resonance, 236
- feeding scheme
  - asymmetrical, 32
  - symmetrical, 50
- Feldtkeller equation, 70
- ferroelectric varactors, 295
- filter
  - all-pole, 70
  - classical design theory, 6–7, 68–71
  - coupled-reactance, 97
  - dual-path, 44
  - low-pass
    - CLC, 244
    - LCL, 244
  - multi-band bandpass, 6–49
  - multi-band bandstop, 50–2
  - multi-band design methods, 5–4
  - prototype, 68
  - stripline, 80, 86
  - tunable dual-band, 295–8
  - ultra-wideband, 271, 286–90
- fractal curves, 191–8
  - dimension, 195
  - generation, 192–4
  - Hilbert, 196–8
  - Julia sets, 194
  - Koch, 192

- fractal curves, (cont.)
  - Mandelbrot sets, 194
  - Minkowski, 196
  - Peano, 196
  - Sierpinski gasket, 194
  - square Sierpinski, 196
- fractional bandwidth, 71
- fringing fields, 124, 166
- grounding via, 37, 113
- group delay, 235
- group velocity, 231, 274
- guided wavelength, 10
- high-temperature cofired ceramics, 266
- high-temperature superconductor, 49
- host medium, 239
- Hurwitz polynomial, 7
- immittance inverter, 83, 98, 162
  - dual-band, 294–5
- indifferentiability, 195
- initial filtering function, 74
- initial guess, 8
- input impedance, 26, 111–12
- insertion loss method, 68
- intermediate filtering function, 92
- intermediate frequency axis, 92
- liquid crystal polymer technology, 269–72
- Lorentz dispersion model, 232
- low-temperature cofired ceramics, 48, 266–9
- magnetic field, 231, 243, 253
- magnetic permeability, 230
- magnetic wall, 20, 199
- mapping functions, 67
- MEMS-devices, 295
- metamaterials, 49, 230–4, 273
- miniaturization, 48, 110, *See also* metamaterials, fractal curves
- mode
  - degenerative, 20
  - fundamental, 21, 23
  - harmonic. *See* mode: higher-order
  - harmonically related, 19, 25
  - higher-order, 23
  - resonant, 19
- mue-near-zero metamaterials, 237–8
- mue-near-zero propagation, 243–50
- multilayer
  - structure, 47–8, 266, 269
  - technology, 265, *See also* liquid crystal polymer technology
- mutual inductance, 197
- near-zero metamaterials, 234–8
- near-zero propagation, 238–50
- network functions, 69
- normalisation function, 68
- orthogonal field distribution, 20
- out-of-phase signals, 32
- parallel resonant circuit, 112
- phase constant, 111, 229
- phase velocity, 234, 274
- phase-reversing transformers, 89
- piezoelectric actuators, 295
- p-i-n diodes, 295
- plasma frequency, 232
- poles and zeros, 7
- printed circuit board technology, 47
- reactance function, 94
- reactance transform method, 94
- refractive index, 230
- resonant condition, 26
- resonator
  - appended, 72
  - broadside coupled, 207
  - cavity, 20, 298
    - capacitively loaded, 299
    - evanescent wave, 299
    - nested, 301
  - complementary split-ring, 161, 238
  - dual-mode Hilbert fractal, 199–203
  - edge-coupled, 204
  - embedded, 44
  - grounded Hilbert patch, 147
  - grounded patch, 141
  - half-wavelength, 10, 111
  - Hilbert-fork, 212–17
  - inter-digital hairpin, 52
  - meander, 197
  - multi-mode, 19, 290
  - patch configuration, 21
  - patch embedded in microstrip line, 144
  - perturbed grounded patch, 152–3
  - quarter-wavelength, 111–14
  - rectangular grounded patch, 151
  - ring configuration, 21
  - split-ring, 232
  - square patch, 20
  - stepped impedance, 26
    - dual-mode, 26–9
    - grounded, 40, 46
    - non-grounded, 43, 48
  - RH/LH, 280
  - stub-loaded, 39
  - tri-mode, 29–31

- stub-loaded, 35
  - dual-mode, 35–6
  - tri-mode, 36
- tunable, 296
- with perturbation, 20
- scale-invariability, 195
- self-inductance, 197
- self-similarity, 194
- semiconductor varactor diodes, 295
- signal interference technique, 311
- single-negative metamaterials (SNG), 230
- synthesis based on reactance mapping functions, 83
- synthesis through optimization, 83
- synthesis through transformation, 83
- space-mapping electromagnetic optimisation, 83
- standing waves, 279
- stripline, 1
- superconductor, 48
- surrogate model, 84
- susceptance slope parameter, 72, 163
- synchronously tuned resonators, 163
- transfer functions
  - Butterworth, 7, 69
  - Chebyshev, 7, 69
  - elliptic, 7, 69
  - linear phase, 7, 69
  - low-pass, 68
  - quasi-elliptic, 69
- transmission zero, 7
- tunneling. *See* near-zero propagation
- unit cell, 230
- unloaded quality factor, 163
- wave number, 274
- wave vector, 231
- waveguide
  - architecture, 7
  - coplanar, 1
  - junctions, 235
  - rectangular, 236
  - resonator, 113
  - substrate-integrated, 238
- zeroth-order resonance, 236