

Index

- Abbe number, 6
- Abbe’s invariant, 74, 76
- ABCD matrices, 81
- aberration function, 134
- aberrations, 29, 82, 123, 205
- accommodation, 125, 256
- Acrylite, 11
- addition, 260
- addition lens, 338, 351
- additive, 14
- afocal configuration, 344
- afocal telescope, 346, 350, 351
- aided visual acuity, 334
- Airy function, 508
- allyl diglycol carbonate (CR-39), 11
- ametropia, 129, 131
- amplitude of accommodation, 259
- anamorphic distortion, 198
- angular aberration, 495
- angular magnification, 336
- aniseikonia, 192, 201
- anisometropia, 178
- anterior chamber, 125
- anterior chamber depth, 251
- anti-reflective coatings, 428, 430
- anti-reflective coatings (manufacturing), 429
- aqueous body, 125
- aspheric lens, 88
- asphericity parameter, 30
- astigmatic lens, 87
- astigmatism, 131
- atoric lenses, 88
- atoric surface, 37
- aversion reflex, 407, 409
- axial symmetry, 36
- back focal length, 371
- back surface, 83
- back vertex power, 81, 96
- back-side progressive lens, 306
- backwards operators, 161
- barium oxide, 4, 5, 7
- barium oxide glass, 5
- barrel distortion, 503
- barrel toric surface, 45
- base, 428
- base curve, 14
- biconic surface, 52
- bifocal, 255
- binocularity, 176
- binormal vector, 472
- birefringence, 15
- blind, 332
- blindness, 331
- borate glasses, 4
- bridge height, 451
- bridge width, 451
- capsule, 257
- Cartesian CMM, 391
- casting, 364
- cataract, 332
- cataracts, 409
- caustic, 498
- center thickness, 88, 414
- characteristic equation, 484
- chief ray, 166
- chromatic aberration, 3, 6
- ciliary body, 257
- ciliary muscle, 126
- circle of least confusion, 69
- coating, 428
- coatings, 436
- coma, 138, 499
- combined spectacle frame, 447
- commercial magnification, 337
- compensation principle, 151
- compound hyperopic astigmatism, 131
- compound microscope, 336

- compound myopic astigmatism, 131
- concave surface, 83
- concavity, 24
- conicoid, 28
- contact lens, 237
- contrast sensitivity, 409
- contrast transfer function, 509
- convex surface, 83
- convexity, 24
- Coordinate Measuring Machines (CMM), 391
- cornea, 124
- corneal astigmatism, 242
- corneal damage (radiation), 409
- corridor length, 310
- corridor width, 311
- CR-39, 13, 14
- crossed-cylinder prescription, 103
- crown glass, 1, 3, 4, 7, 8, 14
- crown glass (composition), 4
- Cryolite, 431
- crystal (flint glass), 3
- crystalline damage (radiation), 409
- crystalline lens, 125
- curvature, 22, 470
- curve implicit form, 469
- curve parametric form, 468
- cut to polish, 359
- cylinder, 37
- cylinder axis, 37
- Data Communications Standard (DCS), 367
- decentered lens, 181
- deflectometric mappers, 383
- defocus, 138
- depth of focus, 335, 349, 350
- diabetic retinopathy, 332
- diffraction limited systems, 509
- dispersion, 6
- distance between lenses, 451
- distance between rims, 451
- distance reference point, 400
- distortion, 502
- double-side progressive lens, 305
- Drapper-Gotthus law, 406
- dynamic (or rotary) distortion, 223
- dynamic distortion, 503
- dynamic field of view, 189
- dynamic magnification, 193
- eclipse sunburn, 406
- edge thickness, 354, 414
- effective focal length, 371
- effective magnification, 337
- ellipsoid, 30
- emmetropia, 131
- equivalent power, 108, 338
- exposure, 424
- eye aberrations, 128
- eye care professional (ECP), 15, 22, 86
- eye deviation, 168
- eye surface, 83
- eye-point power, 325
- eyebrows, 407
- eyeglasses, 442
- eyelashes, 407
- eyepiece, 348
- far reference point (FRP), 303
- far-point sphere, 212
- field aberrations, 497
- field curvature, 502
- field of view, 189, 335, 348, 349, 351
- fitting point, (FP), 303
- flat field, 343
- flint glass, 3, 4, 7, 8
- flint glass (composition), 5
- focal point on axis focimeter (FOA), 398
- focimeter, 371
- focimeter power, 393, 397
- frame bridge, 448
- frame joint, 448
- frame lug, 448
- frame rim, 448
- Franklin-style bifocal, 269
- Fraunhofer's spectral lines, 6
- free-form lens design, 362
- free-form manufacturing, 366
- free-form personalization, 363
- free-form surfacing, 360
- free-form generators, 361
- Fresnel equations, 413
- front surface, 83
- front-side progressive lens, 304
- fulgurite, 2
- fused bifocal, 266
- Galilean telescope, 344, 346, 348, 351
- Gaussian curvature, 477
- Gaussian power, 97
- Gaussian sphere, 493
- generalized conicoids, 36
- ghost image, 425
- glare, 407
- glass, 1, 2, 4
- glass discovery, 2
- glass-making, 3
- glaucoma, 332
- gradient refractive index media, (GRIN), 21
- gradient tinted lenses, 416
- handheld magnifier, 342
- haptics, 252
- hardening coating, 436
- hardness, 9

544

Hessian matrix, 23, 476
high-reflective coatings, 419
higher order aberrations (HOA), 208
horizontal distance between centers, 451
horizontal lens size, 451
hydrophobic coatings, 439
hyperboloid, 30
hyperopia, 131

image jump, 269, 282
impact resistance, 9
infinite on axis focimeter (IOA), 398
injection molding, 364
inner astigmatism, 243
intraocular lens, 247
iris, 125
ISO standards, 400

Jalie's hyperbolic lenses, 29

Katrál lens, 29
Keplerian telescope, 343, 344, 348
keyhole view, 348
Knapp's law, 193

laboratory management software (LMS), 366
Laguerre polynomials, 58
Lambert-Beer law, 413
lapping, 357
Large field compensation, 148
laser protection glasses, 423
Lau effect, 389
Lau moiré deflectometry, 390
Le Grand full theoretical eye, 129
legal definition of low vision, 331
Legendre polynomials, 59
length of drop, 451
length to bend, 451
lens design software (LDS), 366
lens effectiveness, 152
lens gauge, 370
lens maker equation, 119
lens mapper, 380
lens thickness, 88
lens vertex magnification (LVM), 336
lensmeter, 376
line of sight, 126
linearization, 80
local dioptric power matrix, 488, 491
local ground prism, 490
local Prentice's law, 490
logistic function, 310
LogMAR chart, 155
longitudinal chromatic aberration, 7
longitudinal ray aberration, 495
longitudinal spherical aberration (LSA), 498
low vision, 330
low vision aid, 351

Index

Lucite, 11
luminous transmittance, 410, 412

machine learning, 403
macula, 126
macular degeneration, 332
magnification, 192, 347, 349, 351
magnifier, 336
main curvature profile, 290
main curvatures, 475
main directions, 476
maximum permissible exposure (MPE), 407
mean curvature, 477
mean power, 97
mean power error, 219
mechanical tube length, 341
meniscus, 84
meridional ray, 214
Merte's lenses, 29
mesh-defined surface, 55
metallic spectacle frame, 447
microscope, 336, 341, 343
minimum angle of resolution (MAR), 154, 333
minimum fitting height, (MFH), 310
minimum fitting variance, 60, 505
Minkwitz's theorem, 292
mixed astigmatism, 131
modulation transfer function (MTF), 509
Monge's chart, 473
mounted magnifier, 343
multifocal contact lens, 247
multifocal contact lens design, 247
multifocal lens, 255
myodisc, 354
myopia, 131

natural visual acuity, 334
near reference point, (NRP), 303, 401
negative spherical aberration principle, 247
neutral filter, 412
nodal points, 94
nonafocal telescope, 346
nonparaxial optics, 205
normal curvature, 475
normal vector, 24, 470

object surface, 83
objective, 350
oblate ellipsoid, 30
oblique astigmatism, 219, 500
obliquity angle, 213
obsidian, 2
ocular astigmatism, 243
ocular protection goggles, 423
optical axis, 93
optical center, 94
optical density, 411

- optical glass, 3
- optical plastics, 11
- optical polymers, 11
- optical system, 21, 62, 81, 205
- optical transfer function, 509
- orthogonal polynomials, 59
- orthonormal polynomials, 59
- osculating circle, 470
- osculating paraboloid, 482
- pantoscopic angle, 428, 457
- paraboloid, 30, 482
- paraxial approximation, 74, 93, 205
- paraxial optics, 205
- Percival lens, 222
- perimeters, 331
- peripheral distortion, 223
- Perspex, 11
- photochromic lenses, 416, 422
- photochromic materials, 416
- photopolymerization, 13
- photoqueratitis, 409
- pincushion distortion, 503
- pinguecula, 409
- piston, 137
- planar curve, 469
- plane prism, 161
- plastic spectacle frame, 447
- Plexiglas, 11
- point spread function (PSF), 508
- polarized filters, 420
- polishing, 357
- polycarbonate, 12, 13, 15
- polymer, 13
- polymethyl methacrylate (PMMA), 11
- polysiloxane, 438
- positive distortion, 503
- power “as worn”, 325
- Power Map Datasets file (PMF), 369
- power matrix, 98
- power vector, 141
- Prentice’s rule, 111, 170
- presbyopia, 255, 338
- principal curvature, 23
- principal curve, 307
- principal dispersion, 6
- principal points, 94
- principal power profile, 307
- principal ray, 166, 492
- prism diopter, 163
- prism reference point, (PRP), 303, 401
- prism refraction angle, 161
- prismatic effect, 157
- prismatic imbalance, 177
- progression length, 310
- progressive power lens (PPL), 255, 301
- prolate ellipsoid, 30
- propagation operator, 159
- pseudoinverse matrix, 182
- pseudophakic, 247
- pterygium, 409
- punctual lens, 222
- pupil, 125
- pupil diameter, 407, 411
- quadrafoil, 138
- radiant flux, 7
- radiative photochemical damage, 406
- radiative thermal damage, 406
- range of clear vision, 263
- rare earth glass, 5
- ratio distance magnification (RDM), 336
- readers, 265
- reading cap, 350
- reduced vergence, 74
- reflectance, 406, 518
- reflection coefficient, 518
- reflection fringe deflectometry, 386
- refraction operator, 160
- refractive error, 135
- refractive index, 4, 5
- refractive power, 76
- relative magnification, 193
- relative visual attenuation coefficient, 412
- remote point, 135
- remote-point sphere, 212
- resistance to abrasion, 9
- retina, 126
- retinal damage (radiation), 409
- retinal disparity, 177
- rimless spectacle frame, 447
- ring toric surface, 45
- Risley rotary prism, 165
- RMS error, 139
- rotation center, 127
- roughing, 357
- RX-lab, 22
- RX-lens, 22, 86
- sagittal coma (SCA), 500
- sagittal curvature, 32
- sagittal focal line, 500
- sagittal plane, 214, 492
- sclera, 124
- seamless bifocal, 269
- second fundamental form, 477
- second order aberrations, 123
- secondary astigmatism, 138
- segment, 266
- Seidel aberrations, 496
- selective absorption filters, 421
- semifinished blank, 86
- Shack-Hartmann, 380

546

shape factor, 97
simple hyperopic astigmatism, 132
simple myopic astigmatism, 132
simplecticity, 161
skew ray, 492
smoothing, 357
Snell's law, 74
solid tinted lenses, 414
spectacle frame front, 448
spectacle frame side, 448
spectacle magnification, 192
spectacles, 442
spectral radiant flux, 7
spectral transmittance, 8
sphere, 24
spherical aberration, 138, 498
spherical lens, 87
sphero-torical generators, 358
spherocylindrical lens, 88
spherocylindrical prescription, 103
spherometer, 370
spherotoric lens, 116
spherotoric lenses, 88
stand magnifier, 343
static field of view, 189
stereopsis, 177
stock-keeping unit, (SKU), 304
Sturm's conoid, 70
sunglasses, 421, 422
sunlight, 407
supervised learning, 403
surface, 22
surface elevation, 473
surface parametrization, 473
surface vertex, 481

Talbot effect, 388
Talbot moiré deflectometry, 389
tangent plane, 473
tangent vector, 470
tangential coma (TCA), 500
tangential curvature, 32
tangential focal line, 500
tangential plane, 214, 492
tear layer, 238
tear lens, 236, 241
telemicroscope, 336, 350, 351
telescope, 343, 344, 346, 348
tempering, 10
tensile strength, 9
thermoplastic polymer, 13
thermoset polymer, 13
thickness function, 490

Index

thin lens approximation, 100
thiourethane (high index polymer), 12
tinted lenses, 415
toric surface, 42
torsion, 23
torus, 42
transfer matrix, 157, 516
transmission fringe deflectometry, 385
transmittance, 7, 406
transposition, 105
transverse chromatic aberration (TCA), 7
transverse ray aberration, 495
transverse spherical aberration (TSA), 498
trefoil, 138
Tribrid, 12
Trilogy, 12
Trivex, 12, 15
truing, 357
Tscherning ellipses, 211
tube length, 341
TVC/OMA compliant systems, 368

umbilical curve, 290
umbilical point, 290
unaided visual acuity, 334
user power, 325, 393, 397
UV filters, 422

vergence, 62
vergence amplification, 345
vertex sphere, 213
vertical lens size, 451
visible transmittance, 411
Vision Council (TVC), 367
visual acuity, 154, 331, 351, 409
visual impairment, 331
visual magnification, 333
visually impaired, 332

wave aberration, 493
wave error, 493
wavefront, 62
welding lenses, 423
working distance, 343
World Health Organization (WHO), 331
wrap-around frame, 91

x-tilt, 138

y-tilt, 138

Zernike aberrations, 506
Zernike polynomials, 58, 138, 503
zonule, 257