

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

449

Author Index

- Adler, D., 251
 Al-Jassar, A., 225
 Aljishi, S., 153
 Allison, J., 367
 Ang, S.T., 21
 Arya, R.R., 317
 Aspen, F.E., 41
- Baron, B.N., 15
 Beyer, W., 189
 Book, L., 21
 Booker, J.F., 145
 Boscherini, F., 95
 Botros, K.Z., 225
- Cannella, V., 353, 373
 Capozzi, M., 95
 Carasco, F., 111
 Catalano, A., 317
 Christou, A., 53
 Chu, S.S., 21
 Chu, T.L., 21
 Cohen, J.D., 311
 Cook, Jr., J.W., 135
 Corderman, R.R., 27
 Cousins, D.C., 367
- Dalal, V., 145
 De Keersmaecker, R., 437
 Delahoy, A.E., 33
 Den Boer, W., 385
 Doele, B., 33
 Duong, A., 21
- Efthimiopoulos, T., 53
 Ehara, S., 203, 209
 Ellis, Jr., F.B., 33
 Evangelisti, F., 95, 195
- Faris, F.A., 225
 Fiorini, P., 95, 195
 Fotakis, C., 53
 Fritzsche, H., 127
 Frova, A., 195
 Fujita, N., 161
- Ghannam, M., 437
 Grammatica, S., 111
 Guenzel, E., 325
- Hack, M., 69, 373
 Hamakawa, Y., 239
 Hansell, G., 353
 Harbison, J.P., 311
- Hawkins, W.G., 443
 Hayakawa, T., 203, 209
 Hegedus, S.S., 15
 Herzig, H., 181
 Hishikawa, Y., 275
 Hitotsuyanagi, H., 161
 Hoheisel, M., 434
 Hudgens, S.J., 403
 Hwaung, C.G., 21
 Hyun, C., 373
- Ihara, H., 175
 Imada, E., 203, 209
 Itozaki, H., 161
- Jackson, W.B., 301
 Jacobson, R.L., 41
 Jansen, F., 111
 Jeffrey, F.R., 41
 Johncock, A.G., 403
 Juergens, W., 325
- Kajiwara, Y., 423
 Kakalios, J., 127
 Kakinuma, H., 409
 Kampas, F.J., 27
 Kaneko, S., 423
 Kanicki, J., 101
 Kausche, H., 327
 Kempter, K., 434
 Kerns, R.C., 317
 Kishi, Y., 275
 Kojima, Y., 203, 209
 Konagai, M., 47
 Konenkamp, R., 89
 Kusian, W., 361
 Kuwano, Y., 275
- LeComber, P.G., 341
 Leonard, M., 145
 Lin, S.Y., 135
 Lo, D.H., 21
 Lucovsky, G., 135
 Luft, W., 281
- Madan, A., 89, 167, 287
 Mahan, A.H., 167
 Matsumura, H., 175
 Matsumura, M., 379
 Matsuyama, T., 203, 209
 McMahon, T.J., 167, 287
 Mell, H., 189
 Mertens, R., 437
 Modesti, S., 95
 Moeller, M., 325

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

450

- Morel, D.L., 265
Mort, J., 111
- Nakamura, N., 275
Nakano, S., 275
Nara, Y., 379
Narikawa, S., 203, 209
Nihei, K., 409
Nijs, J., 437
Nishida, S., 47
Nishikawa, S., 409
Nojima, H., 203, 209
- Partlow, W.D., 181
Patel, R.I., 3
Payson, J.S., 385
Perfetti, P., 95
Pfleiderer, H., 361
Piper, W.W., 9
Possin, G.E., 9
Powell, M.J., 215
- Ohkubo, T., 423
Ohnishi, M., 275
Okada, H., 379
Okumura, F., 423
Ovshinsky, S.R., 251
Ozawa, T., 417
- Quaresima, C., 95
- Ramaprasad, K.R., 33
Rajeswaran, G., 27
Robertson, J., 215
Rocheleau, R.E., 15
Rudder, R.A., 135
- Sabisky, E., 281
Sadlon, K., 281
Sa-Neto, A., 389
Sawan, Y., 231
Schwarz, R., 153
Shibuya, H., 275
Shimizu, I., 395
Shur, M., 69, 373
Skebe, G., 385
Slobodin, D., 153
Smith, Z.E., 331
Stafford, B., 281
Stetter, W., 325
Street, R.A., 79
Stutzmann, M., 301
Swartz, L., 385
- Takahama, T., 275
Takahashi, K., 47
Takenouchi, M., 417
Tarui, H., 275
Tasaki, H., 47
Taylor, P.C., 61
- Tiedje, T., 121
Tonon, T., 33
Tsai, C.C., 301
Tsuda, S., 275
Tomiya, S., 417
Turner, D.P., 367
- Uchida, Y., 379
Uesugi, T., 175
- Van Dine, J., 33
Vanier, P.E., 27
Varmazis, C., 53
Vernstrom, G.D., 41
Vijan, M., 353
Von Roedern, B., 167
- Wagner, H., 189
Wagner, S., 153, 331
Wakim, F.G., 225
Wallace, W., 281
Watanabe, T., 409
Watanabe, Y., 379
Wieczorek, H., 434
Wronski, C.R., 295
- Yang, M., 373
Yaniv, Z., 353, 373, 385
- Zellama, K., 311

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

451

Subject Index

- accumulation, 220, 221
- accumulation layer, 83, 220, 308, 344
- activation energy, 22, 49, 70, 71, 130, 138, 143, 169, 204, 205, 207, 225–228, 302–304, 311, 312, 376, 391, 406, 407, 425, 438
- alloys, 95, 135–144, 145, 149, 153, 156, 159, 167–171, 195, 198, 220, 244, 251, 252, 254, 255, 257, 258, 260, 270, 271, 279, 281, 282, 284–286, 304, 353, 359, 403
- ambipolar FET, 365, 366
- ambipolar diffusion, 106, 361
- annealing, 301, 303
 - excimer laser, 53–55
- antibonding states, 306
- Arrhenius plots, 16, 22
- Auger electron spectroscopy, 156, 176, 190, 210
- band bending, 71, 83, 95, 220
- band discontinuities, 95, 96
- band edge, 56, 150
- band gap, 37, 62, 103, 112, 114, 122, 145, 146, 162, 169, 171, 185, 186, 271, 407
- band mobility, 274
- band structure, 116, 186, 255
- band tails, 17, 89, 90, 92, 145, 149, 165, 167, 170, 171, 195, 196, 198, 254–257, 263, 286, 291, 306, 311, 316, 373, 374
- Bethe Lattices, 135, 140
- binding energy, 99
- bipolar transistors, 437–439, 441
- blocking characteristics, 423
- blocking contacts, 429
- blocking electrodes, 397
- blocking layers, 409
- bond-angle disorder, 256
- bond-angle distortions, 254
- bond lengths, 218
- bond energy, 179
- boron profiles, 328
- breakdown, 372, 388
- built-in potential, 82, 85, 86, 292, 295, 425
- capacitance, 18, 21, 24, 25, 69, 79, 87, 102–104, 208, 113, 155, 284, 311–313, 353–356, 358, 362, 374, 381, 382
- capture cross-section, 122, 130, 171, 198, 295, 297
- channel length, 353, 357
- channel mobility, 56
- channel width, 382
- characteristic temperature, 385
- charge collection, 81, 82, 84, 85
- charge density, 313–315
- charge transfer doping, 220
- chemical vapor desposition, 3, 9, 15, 16, 19, 21, 22, 24, 26, 33, 183, 184, 187, 209, 215, 217, 219, 269, 279, 285, 367
- collection efficiencies, 17, 43, 165, 166, 276, 295, 296
- collection lengths, 333, 335, 337
- collection measurements, 295
- collection width, 18, 31
- collector current, 439, 440
- compact scanner, 423, 428
- compensation, 291, 301, 305, 307
- conductivity, 16, 23, 24, 26, 47–50, 52, 71, 72, 84, 103, 106, 108, 128–130, 135, 137, 138, 142, 143, 153, 159, 162, 169, 178, 179, 190, 196, 203–205, 207, 209, 210, 225–227, 234, 271, 277, 311–313, 341, 342, 262, 275, 406, 407, 412, 423, 424, 425, 438
- conductivity modulation, 103, 106, 108
- contacts, 79, 80, 82, 84, 90, 102, 109, 156, 282
- contamination, 30, 284, 291, 307
- continuous web, 41, 257
- coordination number, 254
- core levels, 96, 97, 215
- correlation energy, 61, 62, 217
- current gain, 437, 439–441
- current voltage characteristics, 26, 79
- Cu₃AsSe₄, 231
- damping factor, 186
- dangling bond density, 21, 303, 305, 315
- dangling bonds, 61–63, 66, 67, 91, 122, 127, 128, 130, 135, 136, 140–143, 153, 189, 198, 209, 212, 213, 215–218, 220, 225, 301–304, 307, 311, 315, 316, 319, 331, 332
- Debye length, 26
- decay constant, 302
- decay time, 130, 407, 409, 410, 413, 420–433
- deep level transient spectroscopy, 69, 86, 285, 316, 331
- defect band, 312

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

452

- defect centers, 215
- defect creation, 301, 330
- defect density, 65, 196, 218, 219, 226, 302, 306, 308, 341, 405
- defect states, 195, 199, 225, 227, 228, 286, 289
- defects, 61, 62, 66, 122, 130, 138, 140, 142, 144, 171, 189, 215, 220, 253-255, 260, 303, 304, 337
 - two-fold coordinated, 62, 64, 66 (see also Sedgwick pairs)
- degradation, 167, 175, 178, 252, 260, 263, 284, 295, 305, 308, 317, 325, 327, 328, 330, 331, 334, 335, 337, 387, 412
- delay time, 86, 383
- density of states, 13, 24, 26, 70-72, 79-81, 86, 112, 153, 167-169, 199, 216, 217, 226, 257, 258, 291, 296, 297, 305, 311-313, 315, 318, 365, 375, 376, 405
 - drive level, 315
 - gap, 17, 20, 21, 24, 26, 69, 70, 91, 128, 129, 199, 295, 298, 304, 341, 342, 344, 362-364, 374, 381, 388
 - interface, 13
- depletion, 364-366, 379, 429, 437
 - layers, 81, 83, 85-87, 381
 - region, 104, 313
 - width, 411
- deposition, 139, 176, 209, 220, 267, 284, 287, 288, 290, 307, 312, 317-319, 323, 325-326, 344, 354, 370, 396, 403, 404, 407, 444, 446
 - parameters, 28, 156
 - rates, 31-33, 36, 182, 183, 203-205, 208, 242, 281, 370, 404, 405
 - temperature, 33
- depth profiles, 279
- desorption, 192, 194
- dielectric breakdown strength, 368
- dielectric relaxation time, 129, 412
- diffusion, 81, 102, 105, 107, 129, 192, 268, 285, 445
 - lengths, 17, 18, 38, 39, 91, 146, 149, 295
 - potential, 95
- diode quality factors, 169, 170, 287, 291
- diodes,
 - heterjunction, 424, 425
 - n-i-n, 385, 386
 - p-i-n, 89
 - Schottky, 101, 103, 105, 107, 108, 278, 385, 417
- disorder, 149, 196, 255
 - structural, 149
- doping, 3, 209, 301
 - concentration, 55
 - efficiency, 179, 207
 - ratio, 207, 210
- doping-modulated amorphous semiconductors, 127, 128
- doping-modulated multilayers, 130
- double injection, 89
- drain contacts, 361, 376
- drift, 79
 - length, 432, 433
 - time, 432
- drive level capacitance profiling, 313, 314
- efficiencies, 30, 39, 92, 130, 165-166, 167, 244, 246, 251, 252, 254-257, 260, 261, 272, 274, 275-276, 278, 280, 282-284, 295, 317, 320, 323, 326-330, 332, 336, 337, 403
- 18-electron rule, 232
- electrochemical photocapacitance, 285
- electron accumulation, 364, 365
- electron-beam-induced current, 42, 43
- electron channeling, 57
- electron-phonon coupling, 306
- electron spin resonance, 21, 62, 63, 65-67, 143, 189, 212, 213, 215, 217, 218, 220, 284, 285, 301-303, 311, 331, 332
- electronegativity, 206, 254
- electroneutrality principle, 233
- electron structure, 251
- electrophotographic gain, 211, 212
- electrophotography, 42, 111, 189, 395, 409, 417, 429
- emission rate, 104
- emitter, 437
- encapsulant, 272, 273
- energy barrier, 303
- energy gap, 162, 239, 246
- enthalpy, 4
- entropy, 4
- equilibration time, 129, 130
- equilibrium, 3-5, 7, 8, 72, 102, 103, 107, 129, 219, 231, 365, 381
- etching, 3, 64, 146, 267
 - dry, 242
- evolution, 194
- extended state, 432
- extraction, 92
- F, 153, 157, 160, 179, 251, 253, 260, 262, 263, 325, 327, 328, 330
- Fermi level, 25, 26, 70-72, 83, 116, 142, 143, 167, 168, 198, 207, 213, 217, 255, 308, 313, 315, 316, 374, 377, 388, 405, 438, 443
- field distortions, 82, 84, 432

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

453

- field effect, 10, 12, 13, 79, 260, 287, 290, 342
 - transistor, 9, 10, 12, 195, 342-346, 349, 367, 379, 380, 383
 - silicon, 379
- field profile, 81
- field separation, 128, 131
- filament, 349
- fill factor, 30, 171, 254, 266, 289, 319, 326, 328, 331, 333, 334, 336
- flat band voltage, 362, 364, 373-375
- free energy, 4
- free radical precursors, 403
- gain, 395, 397
- gain bandwidth product, 347
- gap states, 105, 129, 215, 295, 314
- gate,
 - dielectric, 385
 - lengths, 376
 - voltage, 364
 - width, 374
- Ge,
 - amorphous, 95
- Ge:H,
 - amorphous, 254
- generation rate, 297
- glow discharge, 15, 22, 282, 319, 325, 367
 - decomposition, 135, 145, 153, 155, 341
- gradual channel approximation, 361, 374
- graphitic C-coordination, 198
- growth
 - kinetics, 146, 270
 - mechanism, 139, 403
 - rate, 15, 16, 19
- Gummel number, 437, 438, 441
- heat capacity, 4
- Hecht
 - analysis, 212
 - rule, 211
- heterojunctions, 95-99, 220, 429
 - bipolar transistor, 437, 440
 - photodiode, 423, 428
 - solar cells, 240, 242, 244, 245
- heterostructures, 95, 111, 116
- high carrier mobility, 429
- hole
 - injection, 381
 - mobility, 379
- homo CVD, 101-103, 105-107, 109
- homogeneity, 257
- hopping, 116
- hydrogen,
 - concentration, 190, 192-194, 207, 270
 - effusion, 189, 191, 192, 287, 290
 - molecular, 64
- image,
 - sensor, 347, 348, 396, 398, 417, 420-421, 423, 425, 428
 - tubes, 189
- impurities, 179, 266, 267, 284, 317, 319
- impurity,
 - complexes, 319
 - concentrations, 276
- index of refraction, 9, 10, 12
- infrared spectroscopy, 139, 163, 181, 183, 184, 189-191, 193, 370, 371
- injection, 87, 103, 108, 115, 290-292, 432, 438, 440, 441
 - efficiency, 112, 113, 116
- interfaces, 44, 79, 83, 86, 95, 96, 101, 121, 123, 218, 220, 275, 280, 291, 367, 373
- interfacial oxide, 437
- inversion, 364, 366, 437
 - layer, 108
 - voltage, 108
- inverter, 355, 382, 383, 384
- ITO, 282, 418
- junction recovery, 89, 287-289
- kinetics, 281, 302, 331
- laser,
 - printer, 396, 399
 - scribing, 342
- latent image, 399
- lateral devices, 389
- lattice mismatch, 253
- leakage current, 386
- lifetimes, 90, 91, 168, 170, 210, 214, 252, 295-297, 331, 332, 334, 336, 337, 406, 433
- light-induced effects, 37, 62, 66, 161, 218-220, 255, 256, 281, 284, 285, 295, 296, 302-304, 306, 308, 316, 317, 319, 325 (see also Staebler-Wronski effect)
- light-soaked state, 309, 311
- liquid crystal displays, 9, 343, 344, 346, 349, 353, 359, 367, 385, 387
- local bonding, 135
- localized states, 62, 72, 92, 170, 171, 291
- logic circuits, 347, 349, 373
- long-range order, 255
- Lorentz model, 181, 186

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

454

- low-frequency plasma, 9
- LPCVD, 15
- luminescence, 142
 - efficiency, 198
- magnetron sputtering, 135, 136, 285, 286, 367, 371, 372
- matrix addressing, 9
- MBE, 53
- memory devices, 341, 349
 - nonvolatile, 348
- mercury photosensitization, 47
- metal-insulator-metal diodes, 385
- metastable defects, 301, 311
- microcrystallization, 48, 49, 164
- microwave glow discharge, 253, 403
- minority carrier collection, 17
- minority carrier injection, 101, 106
- MINOS, 215, 217, 218
- mobility, 10, 12, 13, 53, 55, 91, 111, 168, 170, 171, 210, 212, 226, 353, 354, 363, 380, 395, 406, 444-448
 - edges, 213, 313
 - field effect, 11, 344, 354, 373, 374, 376
 - gap, 69, 153, 225, 314, 341
 - lifetime product, 89
- modulation-doped film, 130, 131
- modulation-doped superlattices, 127
- morphology, 158
- MOSFETs, 53, 56, 355, 379, 381, 419, 443
- multilayer structures, 122-124, 130
- multiple bonds, 11
- multiplexing, 386
- n channel, 361
- nematic LC material, 386
- neutral dangling bonds, 135
- nonradiative centers, 122, 124
- nuclear magnetic resonance, 62, 285
- on/off current ratio, 373
- open circuit voltages, 29, 168, 244, 287, 289, 319, 323, 326, 331, 430
- optical absorption, 11, 16, 23, 24, 64, 111-113, 116, 156, 206, 218, 257, 270, 295, 335, 369, 395, 405
 - coefficient, 16, 24, 34, 114, 149, 158, 177, 196, 206, 227, 239, 261, 297
 - sub-gap, 24, 149, 167
- optical band gap, 9-12, 23, 47, 52, 135, 138, 175, 177, 178, 189, 189, 209, 228, 276, 280, 418
- optical confinement, 246, 276
- optical gap, 16, 19, 29, 48-50, 121, 142, 143, 153, 158, 159, 193, 197, 198, 205, 225, 227, 412, 423, 424, 425
- optically detected magnetic resonance, 63
- optimization, 7, 165
- oxidation, 268
- p channel behavior, 57, 361
- passivation, 396, 398, 445
- Periodic Table, 256
- phase separation, 391
- photo CVD, 32, 33, 35, 36, 37, 47-52, 161-163, 165, 166, 242, 275, 279, 280, 284
- photo-induced excess conductivity, 127
- photoconductivity, 16-18, 21, 33, 36, 38, 63, 69, 80, 85, 86, 89, 111-113, 128, 130, 135, 137, 138, 142, 143, 145, 146, 156, 159, 162, 169-171, 175, 178, 189, 192, 195-199, 203-205, 207-210, 213, 239, 257, 262, 272, 295, 296, 301, 333, 347, 395, 397, 399
 - persistent, 121
- photocurrent,
 - decay, 412, 430, 432
 - secondary, 209
- photodarkening, 301
- photoemission, 95-96, 111-113, 116, 215, 216
 - x-ray, 181, 183-186
- photolithographic patterning, 431
- photoluminescence, 121, 123, 271, 272, 291
 - efficiency, 122, 124
- photolysis, 47
- photoreceptors, 15, 112, 395-399, 403, 406, 409, 410, 413, 429
 - multilayered a-Si:H, 409
- photosensitivity, 403, 407
- photosensors, 189
- photothermal deflection spectroscopy, 21, 24, 169, 196, 197, 257
- pinch off, 55
- pinholes, 158, 368
- plasma decomposition, 29, 112, 145, 182, 241, 385, 403
- plasma emission spectroscopy, 241
- plasma-enhanced chemical vapor deposition, 341, 343
- plasma etching, 325-328, 330
- plasma excitation, 181, 183-185
- plasma frequency, 185, 186
- plasmons, 184, 185
- polarization, 108
- polycrystalline thin-film devices, 443
- polygermane, 136
- polyimide, 42-45, 282, 398

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

455

- polysilane, 136
- potential barrier, 105, 290
- power,
 - densities, 252, 253
 - modules, 265
 - sensors, 48
- precursors, 16, 33
- preferential,
 - attachment ratio, 138
 - hydrogen attachment, 286
 - incorporation, 157
- pressure sensor, 51
- proximity dc plasma 241
- pseudo gap, 136, 142, 227

- quantum efficiencies, 32, 38, 122, 149, 196, 409, 410, 412, 413
- quantum yield, 407
- quasi equilibrium, 102
- quasi Fermi levels, 13, 128, 198, 385, 433
- quasi neutral region, 105, 106

- radicals, 267
- Raman spectra, 156, 157, 277, 278
- recombination, 87, 89-91, 105, 123, 130, 199, 301-304, 325, 329-330, 331-332, 432, 433, 441
 - centers, 108, 254, 255, 295, 307, 329, 330
 - lifetimes, 128, 131, 199, 289, 433
 - rates, 171
 - times, 90, 91
- recovery, 91, 93, 292
- recrystallization, 53, 55-57, 391
- rectification ratios, 168, 278
- reflection, 156, 183-187, 270
- refractive index, 182
- relaxation, 64, 130, 144
 - time, 102
- release times, 86
- reliability, 273, 281, 284, 304
- residual voltage, 412
- resistivity, 395
- response time, 84, 429
- reverse breakdown voltage, 380
- ring oscillators, 353, 355, 356, 357
- roll-to-roll system, 282

- saturation, 128, 430
 - current, 55, 105, 376
 - voltage, 375
- scattering cross section, 231, 232
- Schottky barriers, 24-26, 29, 79, 92, 93, 101-103, 105, 106, 168, 169, 287, 290, 295, 379, 423, 424, 425, 429
- screening, 85-87, 92
- Sedgwick pairs, 256 (see also two-fold coordinated)
- self-energy shift, 216, 220
- sensitivity, 417
- sensor, 418, 419
- shallow states, 62
- sheet resistance, 269
- shift register, 354
- short-circuit current, 27, 29, 168, 171, 244, 254, 289, 326, 331, 335
- Si,
 - amorphous, 9, 10, 33, 41, 240, 281, 287, 341, 417
 - microcrystalline, 240
- SiC, 183, 186, 187
 - amorphous, 244
- SiC:F:H,
 - amorphous, 175
- SiC:H,
 - amorphous, 181, 186, 195
- Si:F,
 - amorphous, 178
- Si:F:H,
 - amorphous, 257, 261, 262
 - microcrystalline, 47, 51, 52
- SiF₄, 253
- Si-Ge alloys, 135, 244, 254-256, 260, 262
- Si:Ge:F:H,
 - amorphous, 266, 261
- Si,Ge:H,
 - amorphous, 153, 284
- SiGe:H:F,
 - amorphous, 275
- Si:H,
 - amorphous, 15, 21, 95, 103, 111, 127, 257, 261, 165, 301, 305, 306, 290, 409, 423
 - microcrystalline, 47, 52
- SIMS depth profile, 37, 38
- SiN:H,
 - amorphous, 195, 203, 209
- SiSn,
 - amorphous, 244
- Si-Te, 225
- Si₃N₄, 10, 215
- Si₂H₆, 15, 16, 21-24, 26, 27, 29-32, 33-34, 37, 47-49, 189, 207, 208, 284, 285
- signal detection, 419
- silicon active matrix, 379
- solar cells, 15-17, 27, 29, 30, 33, 37, 38, 42, 47, 52, 61, 89, 92, 99, 145, 153, 161, 162, 165-167, 169, 171, 175, 189, 195, 225, 239-249, 251-263, 275, 276, 278-280, 282, 283, 295, 298, 317-323, 325, 331-337, 395, 417
 - stacked, 61, 145, 161, 167, 195, 240, 253, 254, 269, 275, 280, 281-282, 286, 319, 323, 336

Cambridge University Press

978-1-107-40558-5 - Materials Research Society Symposia Proceedings: Volume 49:

Materials Issues in Applications of Amorphous Silicon Technology

Editors: D. Adler, A. Madan and M. J. Thompson

Index

[More information](#)

456

- source contacts, 361
- source-drain current, 55, 344, 345, 363, 373, 375, 376, 383
- source-drain voltage, 55, 344, 345
- source electrodes, 376
- space charge, 17, 18, 84, 102, 103, 432
 - capacitance, 107
 - conductance, 127, 130
 - layer, 13, 80, 82, 105, 108, 307
 - limited current, 21, 26, 69, 72, 84, 287, 297, 298
- spectral response, 29–31, 37, 165
- spectral sensitivity, 406
- spin densities, 63, 213, 218, 219, 306, 312
- sputtering,
 - reactive, 368, 372, 396
- stability, 251, 255, 256, 274, 284–286, 306–308, 318, 323, 325–328, 330, 336, 337, 343, 344, 348, 369, 399, 417, 423
- Staebler-Wronski effect, 33, 36, 127, 128, 130, 146, 255, 273, 195, 301, 325, 331, 332 (see also light-induced effects)
- strained bonds, 61, 62, 64, 66
- stress, 146, 267, 286, 301, 307, 308
- stretching mode, 206, 207
- submodules, 282, 286
- substrates,
 - plastic, 41, 42, 44, 45, 267
 - polymer, 282
 - temperature, 268
- subthreshold regime, 373
- superlattices, 121, 124, 123, 215, 220
- surface charge density, 374
- surface field, 371
- surface photovoltage, 38, 39
- surface potential, 362, 364, 366, 407
- surface potential decay, 210, 211
- surface roughness, 43
- surface voltage, 410, 411, 413
- switching, 349, 353, 381, 385, 389, 391
- switching speeds, 355
- Tauc plot, 158, 193, 195
- tetrahedrally bonded diamond like compounds, 231
- thermal emission rate, 314
- thermal quenching, 33
- thermal stability, 209
- thermpower, 190
- thin-film transistors, 15, 69, 215, 353, 354, 356–359, 361, 364, 366, 372, 373, 376
- threshold, 391
 - characteristics, 373
 - switching, 389, 391
 - voltage, 11, 57, 345, 387, 443, 445, 446
- tight binding model, 135, 140, 143
- time of flight, 79, 209, 212–213
- toxicity, 252
- transconductance, 345
- transfer characteristic, 12, 344, 367, 369, 383
- transfer doping, 121
- transistors,
 - silicon, 437
- transit time, 84, 91, 156, 168, 381
- transmission, 195, 268
- transparent conductors, 269, 275, 275, 417, 418, 429
- transport, 333
 - dispersive, 429
 - properties, 179
- trap density, 362
- trap emission, 91
- trapping times, 171
- traps, 92, 217, 254, 255, 432
- tunnelling, 287, 291, 292
 - current, 411
- two-thermal sandwich, 385
- ultralight module, 260, 263
- uniformity, 256, 259
- Urbach edge, 61, 62, 64, 149, 169, 171, 196–198, 405
- valence alternation pairs, 219
- valence band discontinuity, 98
- valence control, 208
- van Hove singularities, 255
- vidicon, 395, 396–399
- voids, 192–194
- wagging mode, 11, 206, 207
- weak bonds, 319
- work functions, 291
- xerographic discharge, 111–114, 116, 209–211, 213
- zero voltage resistance, 389