

## Index

- acentric factor, 97
- angles
  - absolute flow angle, 52
  - axial lean angle, 491
  - departure angles, 506
  - deviation, 51, 152, 219
  - diffuser inlet flow angle, 367
  - impeller inlet blade angle, 343
  - impeller outlet blade angle, 358
  - incidence, 51
  - lean angle, 383
  - lean angle along a quasi-orthogonal, 492
  - meridional blade angle, 491
  - meridional slope angle, 491
  - metal angle, 52
  - radial lean angle, 490
  - rake angle, 383
  - relative flow angle, 52
  - tangential wrap angle, 382
- applications
  - air-conditioning, 27
  - air separation, 37
  - automotive gas turbines, 31
  - auxiliary power unit, 33
  - carbon capture and storage, 38
  - compressed air, 26
  - compressed air energy storage, 38
  - fluid catalytic cracking, 37
  - fuel cell systems, 39
  - history, 14
  - jet propulsion gas turbines, 31
  - mechanical vapour recompression, 38
  - medical, 40
  - microcompressors, 39
  - micro-gas-turbines, 30
  - oil, gas and chemical industries, 34
  - power generation gas turbines, 29
  - refrigeration and heat pumps, 28
  - synthetic fuels, 38
  - turbochargers, 24
  - vacuum, 27
  - wastewater treatment, 26
- Aungier diffusion factor, 245
- averaging, 142
- Bernoulli equation, 139
- blockage, 138
  - blockage factor, 138
  - due to boundary layers, 155
- boundary layer, 155
  - displacement thickness, 157
  - effect of adverse pressure gradient, 161
  - end-wall, 167
  - fully developed, 156
  - kinetic energy thickness, 159
  - laminar, 159
  - mass-flow thickness, 158
  - momentum thickness, 158
  - profiles, 164
  - separation, 155
  - shape factor, 159, 164
  - thickness, 156
  - transition, 160
    - bypass transition, 160
    - effect of leading edge shape, 163
    - laminar separation bubble, 163
    - Tollmien–Schlichting waves, 160
    - wake induced, 161
  - viscous sub-layer, 165
- Boyle's law, 88
- cascades of blades, 210
  - aerodynamic loading, 236–246
  - alpha-Mach diagram, 222
  - blade-to-blade loading criterion, 245
  - controlled diffusion, 222
  - diffusion, 219, 224
  - effect of incidence, 225
  - effect of solidity, 223
  - flow turning, 219
  - hub-to-shroud loading criterion, 246
  - loss coefficient, 220
  - profile types, 221
  - space-chord ratio, 219
- casing component design
  - axial thrust, 22, 461
  - balance piston, 462
  - casing and rotor configuration, 444

- deswirl vanes
  - axial, 459
  - integral coolers, 460
  - return channel vanes, 458
- inlet
  - inlet guide vanes, 448
  - intermediate inlet volute, 447
  - side-stream inlet, 447
  - suction nozzle, 446
- outlet volute, 449
  - cross sections, 450
  - performance, 451
  - static pressure distortion, 454
- return channel
  - crossover bend, 455
  - outlet width, 456
  - schedule of width ratio, 458
- rotor–stator side space, 462
- swirl brakes, 465
- centrifugal effect, 12, 53, 73, 144
  - degree of, 55
- centrifugal force, 11, 148
- CFD, 117, 137, 154, 528
  - academic codes, 531
  - boundary conditions, 545
  - codes from large organisations, 533
  - commercial codes, 535
  - computational grid, 540
  - difference equations, 537
  - emergence as a design tool, 530
  - finite volume method, 537
  - governing equations, 536
  - interface planes, 547
  - Moore’s law, 529
  - numerical schemes, 543
  - pressure based and density based, 539
  - quality and trust, 554
    - categories of errors, 554
  - turbulence models, 550
  - unsteady calculations, 549
  - use in design, 560–561
    - checklist for aerodynamic aspects, 561
    - postprocessing, 563
- Charles’s law, 89
- choking mass flow, 256
- components, 297
- compressibility factor, 92, 94
- compressible channel flow
  - choking at a throat, 196
  - effect of area, 194–195
  - effect of back pressure, 197
  - effect of Mach number, 192
  - effect of real gas, 206
- compressor
  - API style, 35
  - axial-centrifugal, 1, 7, 32
  - back-to-back in-line, 22
  - barrel, 24
- double suction, 20, 32
- horizontally split, 24
- integral gear, 22
- intercooled, 23
- multistage, 18, 21
- side-stream, 23
- single stage, 15, 20
- straight-through in-line, 22
- vertically split, 24
- compressor performance map
  - choke, 270
  - efficiency contours, 270
  - speed lines, 269
  - surge line, 269
- compressors
  - books, 40
  - conferences, 42
  - technical journals, 42
  - types, 4
- continuity equation, 137
- controlled diffusion blade profiles, 162
- Cordier diagram, 290
- Cordier line, 291, 293
  - approximate equations, 293
- Coriolis force, 148
  - effect on pressure gradient, 149
- corrected flow per unit area, 194, 256
  - effect of real gas, 209
- covolume, 97
- de Haller number, 54, 142, 162, 225, 239, 242, 366, 460
- degree of reaction, 13
  - kinematic, 54, 115, 127–128
  - pressure, 54
- design process, 688–696
  - optimisation and inverse methods, 696
- diagrams showing changes of state, 75
  - aerodynamic work, 75–76
  - displacement work, 75
  - dissipation losses, 75
  - enthalpy change, 75
  - heat transfer, 75
  - preheat effect, 77
- diffuser design
  - effect of diffuser inlet flow angle, 409
  - effect of impeller outlet Mach number, 411
  - effect of impeller velocity triangle, 406
  - effect of nonuniformities in the flow, 407
  - effect of pinch, 410
  - vaned diffuser
    - comparison with planar diffuser, 418
    - comparison with vaneless, 417
    - low solidity, 406
    - matching with the impeller, 430
    - types, 418
      - unconventional, 441
    - with straight vanes, 421

- diffuser design (cont.)
  - vaned diffuser guidelines, 437
  - vaned diffuser pressure recovery
    - cascade diffuser channel, 435
    - effect of blockage at the throat, 428
    - exit semi-vaneless and vaneless space, 441
    - ideal, 423
    - low-solidity channels, 438
    - pipe diffuser, 440
    - vaneless and semi-vaneless space, 426
    - wedge diffuser channel, 433
  - vaned diffuser zones, 424
    - diffuser channel, 425
    - downstream vaneless space, 425
    - upstream semi-vaneless space, 425
    - upstream vaneless space, 425
  - vaneless diffuser, 412
    - choke, 417
    - effect of the Mach number, 416
    - effect of radius ratio, 413
    - flow path length, 414
    - governing equations, 416
    - ideal pressure recovery, 412
    - instability, 414
  - diffusers, 210
    - planar diffusers, 226–235
    - diffusers in series, 235
    - effect of inlet blockage, 234
    - effect of Mach number, 229, 234
    - flow regimes, 230
    - optimum area ratio, 233
    - performance coefficients, 227
    - Reneau chart, 232
    - step diffuser, 235
  - drag coefficient, 260
  - drag force, 159
  - dynamic stresses
    - achieving safe designs, 659
    - bladed-disc structures, 658
    - circular discs, 658
    - linear mass-spring-damper model, 653
    - logarithmic decrement, 655
    - mistuning, 658
    - mode shapes, 657
    - natural frequency, 654
    - phase angle, 655
    - source of vibrations, 653
    - tapered beam, 657
    - uniform cantilevered beam, 656
  - efficiency
    - adiabatic, 108
    - effect of heat transfer, 132
    - general definition, 70
  - isentropic, 107–108
  - entropy based, 112
  - evolution in a stage, 116
  - static–static, 111
  - total–static, 114–115
  - total–total, 113, 115
  - isothermal, 107–108, 133
  - mechanical, 130
  - minimum reversible work, 107, 118
  - polytropic, 107–108
    - components, 126, 706
    - diabatic, 130, 132
    - entropy based, 121
    - real gas, 134
    - side-loads, 130
    - small-scale, 118
    - wheel, 74, 129
  - equation of state
    - calorific, 57
    - calorically perfect gas, 88
    - ideal gas, 88–89
    - incompressible fluid, 91
    - real gas, 88
      - Aungier–Redlich–Kwong, 97, 99
      - Benedict–Webb–Rubin, 98
      - generalised cubic equation, 96
      - Lee–Kesler, 98
      - mixtures, 98
      - Peng–Robinson, 97
      - Redlich–Kwong, 97
      - Span–Wagner, 98
      - virial equation, 97
    - real gas with constant compressibility factor, 93
    - simple model of real gas, 88
    - Soave, 97
    - thermal, 57
    - thermally perfect gas, 88
    - van der Waals equation, 95, 97
  - equivalent diffuser opening angle, 242
  - Euler equations, 141
    - normal to a streamline, 142
    - in streamwise direction, 142
  - Euler number, 250
  - Euler turbine equation, 7, 46, 141
  - expansion waves, 202
  - Fischer–Tropsch process, 38
  - flow coefficient
    - global, 18, 254
      - effect on efficiency, 255
      - optimum values, 285
    - local, 50, 254, 367
      - optimum values, 23, 327
  - friction factor, 167, 260
    - Colebrook–White formula, 170
    - fully developed pipe flow, 169
    - Haaland equation, 170

- Galilean transformation, 8
- generalised compressibility chart, 94
- geometry definition
  - axisymmetric stream surface, 467
  - Bernstein polynomial, 472
  - Bezier curve, 471–472
  - Bezier patch, 475
  - Bezier polygon, 473
  - Bezier surface, 474
  - camber surface, 478
  - circular arc blades, 479
  - coordinate systems, 466
  - $m'$  meridional coordinate, 468
  - meridional coordinate, 467
  - normalised meridional coordinate, 467
  - parameters for the meridional channel, 477
  - Pascal triangle, 472
  - ruled surface, 478
  - surface of revolution, 467
  - thickness, 478
- Gibbs equation, 68, 250
- head coefficient, 258
  - isentropic, 258
  - optimum values, 285
  - polytropic, 258
- ideal pressure recovery coefficient, 240
- impeller
  - open, 18, 340–341, 644
  - shroud, 19, 342, 644
  - tip-speed, 343
- impeller design, 338–390
  - blade angle distribution, 384
  - blade number, 372
  - blade outlet
    - advantages of backsweep, 362
    - backsweep, 358
      - effect on work, 359
    - effect of backsweep on characteristic, 360
    - effect of work coefficient on stability, 362
  - outlet velocity triangle, 367
  - outlet width ratio, 366
- comparison with axial compressor, 397
- comparison with centrifugal pump, 399
- comparison with mixed flow impeller, 398
- comparison with radial turbine, 401
- control of clearance flows, 384
- inducer inlet
  - blade angle variation with radius, 352
  - casing relative Mach number, 353
  - choke, 357
  - optimum inlet angle, 343, 348, 358, 367
  - optimum radius ratio, 346, 348
- splitter blades, 354
- splitter vanes
  - leading-edge camber, 355
  - throat area, 355
- outlet blade angle
  - effect on the degree of reaction, 368
- rake angle, 384
- rake multipoint design, 387
- transonic inducer, 385
  - free-form surface, 388
  - leading-edge sweep, 389
  - ruled surface, 387
  - unique incidence, 385
- impeller families
  - cut back leading edges, 396
  - cut back outlet diameter, 396
  - determination of meridional contours, 395
  - effect of Mach number, 396
  - master stages, 390
  - number of different families, 393
  - overfile and underfile, 396
  - Renard series, 392
  - trimming hub or shroud, 393
- instrumentation and measurements, 708–714
- isolated aerofoil, 211
  - angle of attack, 212
  - drag force, 212
  - effect of curvature, 211
  - effect of Mach number, 218
  - lift force, 5, 211–212
  - stall, 212
  - supercritical profile, 218
  - types of stall, 217
- jet-wake flow, 156, 158, 180–191
- Joule cycle, 29, 31, 632
- Kutta–Joukovsky condition, 155
- Lieblein diffusion factor, 162, 221, 225, 243, 460
  - modified for radial impellers, 244
- loss coefficients
  - defined by component efficiency, 301
  - dissipation, 300
  - enthalpy, 301
  - total pressure, 300
- loss correlations, 318
  - aerodynamic loss mechanisms, 318
  - efficiency based on duty, 325
    - effect of diffuser type, 329
    - effect of flow coefficient, 326
    - effect of tip-speed Mach number, 328
  - optimum geometry, 319
- loss mechanisms, 303, 317
  - boundary layer, 304
  - dissipation, 309
  - dissipation coefficient

- loss mechanisms (cont.)
  - Denton loss model, 304
  - Traupel loss model, 305
  - dissipation coefficient for compressors, 307
  - effect of Mach number, 315
  - end-wall loss, 303
  - importance of hydraulic diameter, 305
  - incidence loss, 314
  - leakage over a shroud, 317
  - profile loss, 303
  - Reynolds dependent, 313
  - Reynolds-dependent losses, 308
  - Reynolds independent, 312
  - Reynolds-independent losses, 309
  - tip leakage loss, 315
  - trailing edge, 313
  - viscous dissipation, 303
- Mach number
  - tip-speed, 256, 262
- manufacturing
  - flank-milling, 646
  - heat treatment, 648
  - materials, 647
  - open impellers, 645
  - shrouded impellers, 647
- matching
  - matching in multistage compressors, 629
  - matching of compressor and turbine in a gas turbine, 631
  - matching of compressor and turbine in a turbocharger, 634
    - conventional system, 639
    - engine operation in compressor map, 638
    - matching conditions, 637
    - use of a bypass valve, 641
    - use of a variable turbine geometry, 642
  - matching of impeller and diffuser, 628
- maximum pressure rise coefficient, 241
- meridional direction, 12
- momentum equation, 139
- Navier–Stokes equations, 137, 141
- Newton's laws of motion, 7, 45, 139, 141
- operation off-design, 565
  - effect of Mach number, 588
  - effect of work coefficient, 588
  - field experience, 587
- instability, 566
  - acoustic resonance, 575
  - compression system dynamics, 576
  - conditions for instability, 575
  - differences between axial and radial compressors, 568
  - effect of impeller–diffuser matching, 582
  - effect of Mach number, 578
- effect of tip clearance, 580
- Greitzer B parameter, 576
- hysteresis, 567
- inlet recirculation, 573
- rotating stall, 567, 570
- rotating stall inception
  - modes and spikes, 580
- rotating stall propagation speed, 572
- stability of individual components, 578
- surge, 567, 569
  - mild surge and deep surge, 577
  - vortex shedding, 575
- safety margin definitions, 585
- stability enhancement, 590
  - active control systems, 600
  - adjustable diffuser vanes, 594
  - bleed and injection in vaned diffusers, 599
  - bypass and bleed, 596
  - recirculating bleed, 596
  - slots and chambers, 599
  - suction and discharge throttling, 591
  - variable inlet guide vanes, 591
  - variable speed control, 591
  - variable trim, 598
- system requirements, 584
- parasitic losses, 320
- disc friction loss, 320–321
  - effect of flow coefficient, 322
  - effect on performance, 323
- leakage loss, 320, 322
  - leakage flow over a shroud, 324
  - recirculation loss, 320, 322
- performance map
  - effect of heat transfer on apparent efficiency, 619
  - extrapolation to low pressure ratio, 620
  - extrapolation to negative flow, 624
  - generated from stage characteristics, 604
    - validation, 616
  - interpolation in stage characteristics, 626
  - prediction methods, 602
  - prediction of surge and choke, 613
  - stage stacking for multiple stages, 624
- polytropic head. *See* diagrams showing changes of state, aerodynamic work
- power input factor, 258
- preheat factor, 120
- preliminary design
  - determination of size, 330
  - determination of tip speed, 330
  - mean-line calculation, 330
    - compression process, 331
    - equations, 333
    - flow conditions through the stage, 332
  - stage as two components, 335

- pressure gradient
  - at inlet to a radial impeller, 146
  - blade-to-blade, 147
  - in curved flow path, 143
  - in swirling flow, 144
- process
  - incompressible
    - analysis, 264
  - isentropic
    - analysis, 263
    - disadvantage, 117
    - ideal gas, 74
    - real gas, 102
  - polytropic, 118
    - analysis, 263
    - ideal gas, 77
    - polytropic exponent, 119
    - polytropic ratio, 78
    - real gas, 102
    - special features, 79
- profile shape
  - camber, 213
  - effect of incidence, 215
  - leading edge, 214
  - thickness, 213
  - trailing edge, 214
- radial equilibrium equation, 145
- reduced frequency, 251
- reduced state variables, 96
- relative eddy, 151
- reversible shaft work, 108
- Reynolds number, 155, 252, 260
  - correction methods, 261
  - lower critical, 167, 169
  - upper critical, 167
- Reynolds stresses, 164
- rotary stagnation pressure,, 174
- rothalpy, 71
  - conservation of, 71
- rotordynamics, 677
  - rotor instability, 678
  - Jeffcott rotor, 681
  - theoretical models, 685
  - unbalance response, 680
- secondary flow, 171
  - blade surface vortex, 174
  - Coriolis vortex, 174
  - passage vortex, 172, 174
  - secondary circulation, 173
- shock structure
  - detached curved shock, 203
  - effect of operating point, 205
  - swallowed shock, 204
  - unique incidence, 205
- shock waves
  - deflection, 201
  - entropy generation, 200
  - normal, 199
  - oblique, 201
- similarity, 248
  - dynamic, 252
  - fluid dynamic, 253
  - geometric scaling, 252
  - kinematic, 250
  - normalized parameters, 264
  - pressure ratio, 266
    - effect of gas properties, 267
    - effect of tip-speed Mach number, 267
  - thermodynamic, 252, 261
- slip factor, 153
- slip velocity, 152–153
  - Wiesner correlation, 359
- specific diameter, 285
- specific speed, 284–296
  - alternative definitions, 287
  - physical significance, 288
  - speed of sound, 296
- stacking
  - stage, 297
- stage characteristic, 271
  - choking, 273
  - effect of changes in geometry, 279
  - effect of flow coefficient, 607
    - superellipse, 609
  - effect of isentropic exponent, 281
  - effect of Mach number, 273
  - effect of matching, 274
  - effect of Reynolds number, 280
  - effect of tip-speed Mach number, 607, 611
  - effect of work coefficient, 614
  - idealised, 265
  - normalised efficiency curves, 605
- stage characteristics
  - vaned and vaneless diffusers, 616
- static stresses
  - blade lean and bending, 650
  - effect on blade shape, 652
  - rotating disc, 651
  - rotational stresses in blades, 649
  - thermal stresses, 675
- streamline curvature throughflow method, 145, 482
- blade surface velocities, 488, 513
- choked flow, 515
- derivation of equations, 492
  - acceleration along the quasiorthogonal, 499
  - acceleration due to curvature, 498
  - acceleration due to swirl, 498
  - blade force, 495
  - blade force term, 495

- streamline curvature throughflow method, (cont.)
  - dissipation force term, 500
  - pressure force term, 499
- empirical modifications
  - blockage, 508
  - departure angles, 506
  - losses, 507
- iteration to pressure ratio, 506
- iterative scheme, 504
- losses, 487
- relaxation factor, 503
- spanwise mixing, 489, 508
  - Denton mixing model, 509
  - diffusion equation mixing model, 511
  - mixing at a trailing edge, 513
- streamline positions, 502
- velocity gradient equation, 485
  - integration, 501
  - modification for choke, 500
- Strouhal number, 250
- structural analysis
  - Campbell diagram, 669
  - centrifugal stress stiffening, 668
  - design cycles, 661
  - design life, 662
  - design of axial tie bolt, 675
  - design speed, 662
  - design stresses, 663
    - Goodman diagram, 666
    - high cycle fatigue, 665
    - low cycle fatigue, 663
  - design temperature, 663
  - disc design, 673
    - disc burst, 663
    - impeller hub, 673
    - impeller shroud, 675
  - engine order, 668
  - finite element methods, 660
  - fouling, corrosion and erosion, 665
  - interference diagram, 670
  - mode shapes, 666
  - nodal diameter, 667
  - shrink fit, 676
- surface finish, 167
  - centre-line average roughness, 168
  - equivalent sand roughness, 168
  - hydraulically smooth, 167
  - ISO class number, 168
  - relative roughness, 253
  - roughness in CFD, 169
- Sutherland's law, 259
- testing
  - acceptance tests, 699
  - international standards, 699
- prototype, 698, 702
- research and development tests, 702
- test stands
  - determination of component performance, 706
  - industrial compressors, 703
  - open impellers, 705
  - simplified research rigs, 707
  - types of tests, 698
- thermodynamic property
  - enthalpy, 62
  - entropy, 66
  - extensive, 57
  - intensive, 57
  - static, 62
  - total, 63
- thermodynamics
  - control volume, 56, 137
  - boundaries, 56
  - equilibrium, 57
  - reversible process, 57
  - sign convention, 58
  - specific dissipation, 68
  - state, 57
  - steady-flow energy equation, 44
- system
  - closed, 56
  - open, 3, 56
- tip-clearance flow
  - effect on performance, 179, 279
  - tip-clearance vortex, 177
  - trajectory of vortices, 178
- tip leakage flow, 176
  - vena contracta, 177
- turbulence models
  - algebraic models, 551
  - Baldwin–Lomax, 186, 551
  - low Reynolds number models, 166
  - one equation models, 552
    - Spalart–Allmaras, 552
  - Reynolds stress transport models, 554
  - transition, 553
  - two equation models, 552
    - $k-\varepsilon$  model, 552
    - $k-\omega$  model, 552
    - Menter SST model, 553
- variable inlet guide vanes, 280
- velocity triangles, 48
  - associated blade shapes, 51
  - sign convention, 51
- viscosity
  - dynamic, 259
  - eddy, 550
  - kinematic, 259
- Von Karman integral equation, 159

- work
  - aerodynamic, 69, 81, 107
  - effect of efficiency, 84
  - effect of gas properties, 83
  - displacement, 59, 68, 81
  - flow, 61, 81
  - polytropic head, 69
  - Huntington method, 104
- Mallen and Saville method, 103
- Schultz method, 103
- reversible shaft work, 70, 109
- shaft, 61
- work coefficient, 115, 239, 257, 367
  - Euler, 320
- Zweifel loading coefficient, 221, 243