

Index

- Aero-propulsive benefit, 259
- AEV. *See* Vehicle, all-electric
- Air cycle system, 234
- Aircraft
 - all-electric, 26, 192, 268
 - commuter, 263
 - electrified, 256
 - fully turboelectric, 6
 - hybrid wing body, 2
 - parallel hybrid, 265
 - parallel hybrid electric, 6
 - partially turboelectric, 6, 268
 - regional, 263
 - requirements, 260
 - Series hybrid, 267
 - tube-and-wing, 2
 - turboelectric, 266
 - turbofan, 6
- Amprius, 199
- ANPC, 178
- APU. *See* auxiliary power unit
- Architecture, 256
- ASSB. *See* Battery, all-solid-state
- Assessment, 256
- ATR 42-500, 19
- Auxiliary power unit, 32, 37, 268
- Axial flux PMSM, 70

- Baseline, 256
- Baseline Technology Projection, 270
- Battery
 - all-solid-state, 201
 - Aluminum-air, 207
 - anode, 198
 - cathode, 198
 - cell specific energy, 200
 - cycle life, 194
 - flow, 204
 - general, 225, 235, 237
 - Lithium-air, 201
 - lithium-ion, 190
 - lithium-oxygen, 201
 - lithium-sulfur, 200
 - mass, 196
 - mass fraction, 196
 - metal-air, 208
 - pack specific energy, 196, 200
 - redox flow, 205
 - weight fraction, 196
- Battery management, 225
- Battery management system, 201
- Battery-Electric Propulsion System, 224
- B-H curve, 160
- Bipolar junction transistor (BJT), 170
- BLI. *See* Boundary layer ingestion
- Blockchain efficiency, 284
- Block energy, 285
- Block fuel, 197
- Block fuel burn, 285
- Boeing 777, 12
- Boundary layer ingestion, 2, 265, 267–268
- BPR. *See* Bypass ratio
- Brake specific fuel consumption (BSFC), 276
- Breakers. *See* Contactors
- Breakeven analysis, 10
- Breakeven assumptions, 6
- Breakeven curves, 16
- Breguet range equation, 8
- BTP. *See* Baseline Technology Projection
- Bureau of Transportation Statistics (BTS), 286
- Bus power control unit, 45
- Bypass ratio, 2, 261

- Capacitor, 176
- Cash operating cost, 259
- Cathode
 - nanostructured, 201
 - porous, 201
- Climb rate capability, 261
- Coefficient of performance, 234
- Complementary metal-oxide semiconductor (CMOS), 170
- Compressor, 232
- Concept of Operations, 269
- Conceptual design, 259
- Condenser, 232
- CONOPS. *See* Concept of Operations
- Constraint analysis, 282

- Constraints, 259
- Contactors, 43
 - electromechanical, 44
 - solid state power controller, 44, 46
- Control loops, 131
- Control platform, 131–132
- Convection, 63
- Conventional takeoff and landing (CTOL), 277
- Core specific power, 276
- C-rating, 194
- Cryo-coolers, 101
 - Brayton cycle, 102
 - Carnot efficiency, 106
 - efficiency, 102
 - Gifford McMahon (GM), 103
 - power density, 102
 - Stirling, 102
 - SWaP, 102
- Cryogenic power electronics
 - benefits, 151
 - cooling, 178
 - dynamic characteristics, 155
 - magnetics, 152
 - static characteristics, 155
- Cryogenic temperatures, 108, 153, 170, 174
- CTOL. *See* Conventional takeoff and landing
- Current commutation, 140

- Degree of hybridization, 266
- Design space, 283
- Direct operating costs, 265
- Distributed propulsion, 2

- EA. *See* Aircraft, electrified
- EDT. *See* electric drivetrain
- EIS. *See* Entry-into-service
- Electric drive
 - efficiency, 8
 - specific power, 8
 - system, 3
- Electric drivetrain, 224–225
- Electric machines
 - copper loss, 62
 - current density, 62
 - design drivers, 51–52
 - electric loading, 60
 - electrical frequency, 38, 61, 77
 - electromagnetic loading, 60
 - electromagnetic torque, 60
 - force production, 60
 - forced convection cooling, 64
 - high specific power, 49, 61, 73
 - high speed, 64
 - High Speed index, 65, 74
 - induction, 69
 - magnetic loading, 60
 - mass density, 66
 - mass distribution, 73
 - mechanical output power, 60
 - permanent magnet synchronous, 69
 - pole count, 37, 61
 - power density, 66
 - rotor volume, 62
 - scaling, 68
 - shear stress, 60, 78
 - sizing equation, 61
 - slot copper packing factor, 62
 - slot depth, 62
 - slot width, 62
 - state-of-the-art, 72, 79, 116
 - surface force density. *See* Electric machines:
 - shear stress
 - switched reluctance, 69
 - temperature limitations, 63
 - tip speed, 62, 74
 - tooth width, 62
 - torque per unit rotor volume (TRV), 60
 - wound-field synchronous, 34, 56, 69, 72
- Electric power system, 29
 - break power transfer, 40
 - common cause analysis, 35
 - common mode analysis, 35
 - double voltage system, 38
 - fault-tolerant, 30
 - frequency, 36
 - future trends, 39
 - high voltage dc, 39
 - isolated, 40
 - load management, 46
 - no-break power transfer, 40
 - parallel configuration, 41
 - particular risk analysis, 35
 - power cables, 117
 - reliability, 31, 33
 - single-channel configuration, 40
 - single-line diagram, 33
 - software control, 46
 - variable frequency ac, 38
 - voltage, 36, 120
 - wiring, 31
 - zonal safety analysis, 35
- Electric propulsion power, 11
- Electrical propulsion fraction, 7
- Electrically Variable Engine, 266
- Electrification, 256
- Electromagnetic interference, 150
- Emergency control unit, 45
- EMI emissions, 135
- Emissions, 259
- Emissions Databank, 271
- Energy mass efficiency, 214
- Energy specific air range (ESAR), 284
- Engine oil, 226
- Engine weight, 273

- Entry-into-service, 256
 Environmental Protection Agency (EPA), 288
 eTaxi, 270
 ETOPS. *See* Extended Operations
 Evaporator, 232
 Eviation, 195
 eVTOL, 192, 197
 Extended Operations, 260
- FAA. *See* Federal Aviation Administration
 Fan, 228
 efficiency, 243
 power, 243
 pressure ratio, 243, 266
 Fan air, 226
 Federal Aviation Administration, 29, 260
 Code of Federal Regulations, 30
 Federal Aviation Rules, 30
 Feeder, 224
 Ferrite, 160
 Field-effect transistor, 44
 Figures of merit, 256
 Filters, 133
 Fluid density, 240
 Fluid power, 240
 FOM. *See* Figures of merit
 Friction factor, 242
 Fuel cells, 190
 Fuel specific air range, 284
 Fuel weight fraction, 196
 FUELEAP, 212
 Fueled-Engine Propulsion System, 224
- Gallium nitride (GaN), 147, 152
 Gate drive, 169
 Generator, 224
 Generator control unit, 45
 Ground power control unit, 45
- Halbach magnet array, 69
 Heat capacity, 235
 Heat duty, 234
 Heat exchanger, 226
 air oil cooler, 226, 232, 243
 effectiveness, 245
 engine oil, 227
 fuel oil cooler, 232, 249
 fuel-cooled, 227
 overall heat transfer coefficient, 244
 plate-fin cross-flow, 245
 UA, 245
 Heat flow capacity, 245
 Heat flow rates, 238
 Heat pump, 228–229, 234
 Heat sink, 227, 229
 Heat transfer coefficient, 244
- HEV. *See* Vehicle, hybrid-electric
 hFan, 16
 High electron mobility transistors (HEMTs), 152
 Hot day, 225
 HTS cables, 118
 HWB. *See* Aircraft, hybrid wing body
 Hybrid-fueled propulsion systems, 224
 Hybridization parameters, 282
- IGBT, 130, 145, 152
 Induction machine, 71, 113
 solid rotor, 71
 Inductor, 174
 Influit Energy, 206
 International Civil Aviation Organization (ICAO), 271
 International Standard Atmosphere, 225
 Inverter, 136
- Key performance parameters, 5
 Kokam, 195
 KPP. *See* Key performance parameters
- Lapse rate, 261
 Lift-to-drag ratio, 2, 196
 Liquid electrolyte, 199
 Liquid hydrogen, 105
 Liquid nitrogen, 106
 Lithium-metal, 199
 LNG, 102
- Maintenance, repair, and overhaul, 265
 Mass flow rate, 238, 240, 244
 Matrix converter, 139–140
 MEA, 176
 MIL-PRF-21480B, 36
 MIL-STD-704F, 36, 39
 Mission analysis, 282
 Morphological matrix, 263
 MOSFET, 130, 145
 Motor, 224
 efficiency, 240
 Motor drive, 224, 237
 MRO. *See* Maintenance, repair, and overhaul
 Multifunctional structures, 190
 Multi-phase machines, 143
- N+3 Conventional Configuration, 16
 N3A, 14
 N3CC. *See* N+3 Conventional Configuration
 N3-X, 3, 266
 Nanocrystalline, 160
 Nanomolecules, 206
 NASA, 124, 176
 National Academy of Sciences, 260
 Normal day, 226
 NTU, 245

- One engine inoperative OEI, 261
- Overall pressure ratio (OPR), 272
- Over-the-wing propulsors, 265
- Part 25, 261
- Passenger class, 260
- Passenger count PAX, 260
- Payload, 260
- Peak power shaving, 278
- PEGASUS, 5
- PEM. *See* Proton exchange membrane
- Performance assessment process, 256
- Performance metrics, 284
- Permanent magnet generator, 37
- Permanent magnet synchronous machine, 69
- Phase-change materials, 235
- Power density, 194
- Power devices, 152
- Power distribution and protection, 29–31
- Power electronic converters, 130
 - cooling, 132
 - fault tolerance, 144
 - integration, 135
 - losses, 146
 - multi-level, 138
 - power density, 132
 - Technology Readiness Level, 135
 - topology, 135
- Power generation, 30
- Power management, 267
- Power quality, 29, 35, 44, 133
- Power semiconductor devices, 132
- Power stage, 150, 166
- Powertrain architecture
 - All Electric, 52
 - All Turboelectric, 52
 - Parallel Hybrid Electric, 52
 - Partially Turboelectric, 52
 - Series Hybrid Electric, 52
 - Series/Parallel Partial Hybrid Electric, 52
- Probability of failure, 31–32
- Propulsion motor, 237
- Propulsive device, 279
- Propulsive efficiency, 264
- Propulsor efficiency, 280
- Proton exchange membrane, 206
- Pump, 228–229
 - efficiency, 240
 - input power, 240
 - part load performance, 240
 - pressure rise, 240
- Quench, 107
- Radiation, 63
- Ram air, 226
- Ram air turbine RAT, 32, 34
- Rectifier, 39, 141, 224
- Refrigerant, 233
- Relays. *See* contactors
- Rolls-Royce, 213
- Safety assessment, 180
- Semiconductor power devices, 152
- Short circuit, 173
- SiC. *See* Silicon carbide
- Sila Nanotechnologies, 199
- Silicon, 199
- Silicon carbide, 135, 147, 152
- Single engine concepts, 262
- Sizing and synthesis, 259
- Skin cooling, 226
- SOA. *See* State-of-the-art
- Solid Oxide Fuel Cell SOFC, 211
- SolidEnergy, 200
- Specific energy, 192, 268
- Specific heat, 235
- Specific power, 49, 61, 228, 267
- Standards, 133
- STARC-ABL, 4, 268
- State-of-the-art, 256
- Structural mass efficiency, 214
- SUGAR, 265
- Supercapacitors, 190, 212
- Superconducting cables, 117, 121
- Superconducting machines
 - ac homopolar, 112
 - active shielding, 123
 - advantages, 88
 - air-core, 110
 - asynchronous, 113
 - cooling, 101
 - dc homopolar, 114
 - demonstrations, 116
 - efficiency, 89
 - fully superconducting, 109
 - partially-superconducting, 110
 - short circuit, 108
 - specific power, 88
 - thermal management, 89
- Superconductors, 89
 - ac loss, 92
 - bulk, 90, 124
 - coupling losses, 94
 - critical current, 91
 - critical field, 91
 - Critical State Model, 92
 - critical surface, 91
 - critical temperature, 90–91
 - eddy current losses, 94
 - HTS, 90–91, 110, 112

Superconductors (cont.)	Thrust specific fuel consumption (TSFC), 276
Meissner effect, 90	Thrust-to-power ratio, 280
MgB ₂ , 91, 97, 110	Thrust-to-weight ratio, 282
multi-filamentary wire, 94–95	TMS. <i>See</i> Thermal management system
Nb ₃ Sn, 91, 107	Total life cycle carbon emissions, 286
Nb-Ti, 91	Transformer rectifier unit, 33, 37
operating current, 94	Trip fuel, 285
strain, 106	Turbine/rotor inlet temperature, 272
transport current loss, 96	
Superdielectrics, 213	Vapor cycle system VCS, 232
Switched reluctance machine, 72	Vehicle
Switching frequency, 133, 138	all-electric, 256
	hybrid-electric, 256
Technology progression, 271	Volumetric energy density, 206
Technology readiness level, 117, 271	Volumetric flow rate, 240
Technology S-curves, 258	
Temperature lift, 234	WFSM. <i>See</i> Electric machines:wound-field
Thermal efficiency, 264	synchronous
Thermal management system, 201, 236	Wing loading, 282
optimization, 248	
performance, 248	X-57, 268
Thermal mass, 235	
Thin-haul, 195, 263	Zunum, 195