

Subject Index

- absorption loss, 142
- Allan deviation (ADEV), 58
- angular random walk (ARW), 78, 236
- Annual wobble, 31, 211
- AR(2) frequency estimator, 188
- area stabilization, 106
- area strain, 83
- argon laser, 32
- Arkansas ring laser, 228
- astigmatism, 20, 54
- atom interferometry, 232, 246
- atomic collision, 39
- atomic frequency standards, 263
- autoregression, 177
- backscatter correction errors, 135
- backscatter coupling, 29, 38, 39, 108
- beam power ratio, 124
- beam power stability, 120
- beam splitter, non-polarizing, 40
- beam steering, 79
- beam walk, 79
- beat note, 39
- Bessel function, 54
- birefringence, 26, 120
- Bragg grating, 138
- Bragg stack, 149
- Brewster window, 39, 160
- broadening, homogeneous, 56
- Buneman frequency estimator, 178
- buoyance frequency, 231
- C-I, 36
- Canterbury ring laser, 36
- capillary, 36, 39
- Cashmere Cavern, 40
- cavern deformation, 79
- cavity ringdown, 140
- cavity stability, 19
- Chandler wobble, 31, 211
- coating defect, 156
- coating noise, 145
- cold atom matter wave interferometer, 247
- contrast function, 63
- Coriolis force, 249
- Cramer–Rao lower bound, 181
- cross-dispersion, 116
- crosstalk, 183
- de Broglie wavelength, 247
- de Sitter geodetic precession, 260
- detector noise, 174
- dielectric coatings, 35
- discharge, 34
- discharge monitor, 194
- discharge, DC, 228
- diurnal polar motion, 185
- Doppler broadening, 120
- double-backscatter process, 110
- doublet, 155
- Earth observation, 259
- earthquake, 236
- eigenmodes, spheriodal, 223
- eigenmodes, toroidal, 223
- electrode configuration, 126
- electrodes, 36
- etalon, 39
- Experimental Laser Gyroscope System, 34
- Fabry–Perot, 87
- Faraday rotator, 252
- fiber optic gyroscope, 234, 276
- fiber optic gyroscope, large, 241
- fluctuation-dissipation theorem, 145
- FOG, large diameter, 241
- forces, van der Waals, 156
- Foucault pendulum, 248
- Fourier transform, 178
- free Earth oscillations, 269

- free spectral range (FSR), 90
- frequency estimator, 93
- frequency modulation, 70
- frequency reference, optical, 261
- Fresnel drag, 28, 36, 39, 105
- Fresnel Fizeau effect, 125
- FSR stabilization, 91
- fundamental physics, 259
- gain grating, 252, 255
- gain medium, 36
- gain saturation, 23, 114
- gain starvation, 36
- gain tube, 35
- gas composition, 99
- gas flow, 36
- gas purity, 84
- Geodetic Observatory Wettzell, 40
- geodetic precession, 32
- GEOsensor, 49
- getter, 86, 161
- Goos–Hänchen displacement, 103
- Gouy phase, 99
- Grossring, 40
- gyro, tuning fork, 249
- gyros, helium SQUID, 244
- gyrotropic, 25
- Helmholtz resonator, 229
- hemispherical resonator gyro, 250
- Hendrix College, 35
- HeNe (helium neon) laser, 13, 39
- Hermite–Gaussian, 21
- heterolithic large rings, 43
- Hilbert transform, 181, 192
- homogeneous line broadening, 120
- Hubble space telescope, 251
- hurricane infrasound detection, 230
- Incorporated Research Institute for Seismology, 192
- inertial space, 37
- infrasound detection, 228
- interference, incoherent, 138
- interference, unwanted, 133
- International Earth Rotation and Reference System Service, 288
- interstorey drift, 239
- intra-cavity phase interferometry, 32
- inverted interferometer, 148
- iodine stabilized HeNe laser, 87
- ion beam sputtering (IBS), 139
- isotope, 39
- isotopic shift, 32
- Josephson effect, 232, 244
- Julian date, modified, 200
- Kösters prism, 40
- Lamb theory, 128
- Lamb units, 128
- Langmuir flow, 28, 39, 56
- laser gain, 84
- laser gain factor G , 85
- laser gas contamination, 84
- laser gyro, solid state, 252
- laser mode, 36
- laser mode volume, 54
- lasing threshold, 36, 39
- Lense–Thirring frame dragging, 32, 106, 260
- line broadening, homogenous, 36
- lock-in frequency, 33, 39
- longitudinal mode, 34
- Lorentzian, 64
- Love waves, 94
- Mach–Zehnder interferometer, 133, 246
- magnet, neodymium, 224
- magneto-chiral birefringence, 32
- magnets, 152
- MESSENGER mission, 251
- Michelson–Gale Experiment, 232
- microseismic band, primary, 271
- microseismic band, secondary, 271
- microseismic noise, 220
- mirror coatings, crystalline, 149, 155
- mirror defects, 140
- mirror dispersion, 100
- mirror losses, 139
- mirror surface roughness, 139, 140
- mirrors, 138
- misalignment, angular, 38
- mode competition, 95, 143
- mode index, longitudinal, 60
- mode selection, 56, 140
- mode volume, 36
- mode-locking, 57
- modes, normal, 269
- mu-metal, 224
- multi-mode operation, 57, 90
- nanostrain, 69
- navigation, 34
- noise, electronic, 63
- Nomarski map, 156
- non-reciprocity, 32
- nonius, 37
- null-shift, 21, 38
- Nyquist limit, 177, 188
- observation file, 200
- Ocean Bottom Seismometer (OBS), 276
- ocean loading, 209
- operation at 543.3 nm, 150
- operation at 594 and 611 nm, 153

Subject Index

317

- Oppolzer terms, 208
- optical contact, 149
- optical frequency comb (OFC), 93, 96
- optical frequency detuning, 120
- orientation model, 203
- orientation stability, 106
- oscillator, stable, 261
- oscillators, coupled, 38
- outgassing, 84
- partial pressure, 39
- passive gyroscope, 29, 232
- perimeter stabilization, 107
- phase shift correction, 189
- phase-locked operation, 90
- planar square cavity, 39
- plasma brightness, 123
- plasma dispersion, 100
- plasma dispersion function, 22, 86, 120, 128
- plasma dynamics, non-linear, 127
- plasma excitation, 126
- polar motion, 31, 173, 208
- polarization, 25
- Pound–Drever–Hall locking, 234, 262
- pulsing, 152
- Q*-factor mechanical, 139
- quadrature demodulation, 188
- quality factor, 28
- radio frequency (RF) excitation, 36
- Raman transition, 246
- rate bias, 35, 173
- Rayleigh backscatter, 235
- reflection, total, 133
- residual amplitude modulation, 30
- resonant cavities, passive, 234
- resonator, open, 227
- ring laser alignment, 43
- ring laser equation, 27
- ring laser resolution, 62
- ringdown, 35
- ringdown time, 62
- ROMY ring laser, 159
- rotation model, 203
- S (secondary) waves, 52
- Sagnac effect, 17
- Sagnac frequency, 27
- Sagnac interferometer, single turn, 235
- Sagnac interferometers, 27
- sampling frequency, 176
- sapphire oscillator, cryogenic, 261
- scalable space inertial reference unit, 251
- scale factor, 38, 72
- scale factor correction, 104
- second gain tube, 151
- seedlink, 192, 200
- self-referenced operation, 154
- sensor groups, 158
- sensor model, 203
- sensor orientation, 196
- sensor resolution, passive gyro, 234
- shake table, 237
- Shawlow–Townes linewidth, 63
- shot noise, 32
- shot noise limit, 144
- Shupe effect, 235
- siderial day, 28
- single-pass fractional gain, 100
- Sky Tower, 240
- solar day, 28
- solid Earth tides, 185, 207
- space inertial reference unit, 251
- spheroidal modes, 269
- spoiled transmission, 142
- spontaneous emission, 194
- SPOTL ocean loading package, 210
- standing wave pattern, 37
- strong motion, 236
- substrate noise, 219
- super cavity, 87
- super mirror, 36
- teleseismic signals, 199
- The Seed Data format, 192
- tiltmeter, 196
- tiltmeter corrections, 197
- timescales, 176
- toroidal modes, 269
- torsional excitation, 221
- transducer, 239
- transfer laser, 60, 261
- transition, 36
- turbo molecular pump, 41
- turntable, 35
- UG-2, 80
- ultra large gyroscopes, 45
- universal time, coordinated, 176
- UT1 determination, 285
- variations in Length of Day, 213
- volcano infrasound detection, 230
- voltage controlled oscillator (VCO), 71
- waves, Love type, 264
- wind friction, 273
- wind loading, 220
- wine glass resonator, 250
- worth function, 39
- Zerodur, 40