

Index

- AA, *see* Aperture array
- Absorber, microwave, 209
- Active
 - impedance, 120, 124, 200, 201, 273
 - impedance matching, 206
 - reflection coefficient, 124, 201
- Active antenna
 - available gain, 189
 - available power, 190
 - definition, 39
 - effective area, 194
 - isotropic noise response, 186
 - noise matching efficiency, 202
 - noise temperature, 197
 - receiver, 39
 - terms, 185
- Active array
 - equivalent transmitting, 196
 - impedance matching, 204
 - noise matching, 204
 - reciprocity, 196
 - sensitivity model, 207
 - SNR model, 175
- Active element pattern, 126
- Adaptive beamforming, 328, 337, 347, 370
- Adaptive cross approximation algorithm, ACA, 268
- AFAD, 315
- Airy pattern, 102, 240, 337, 348, 356
- Aliasing, 111
- Ambient temperature, 62
- Amplifier
 - front end, 67
 - low noise, 52, 60, 67, 172
 - noise parameters, 66, 68
- Analog
 - beamforming, 389
 - front end, 300
- Antenna
 - aperture, 25, 43, 48, 76, 96, 101, 105, 116, 127, 171, 264
 - bandwidth, 300
 - broadband, 300, 302
 - circuit model, 45
 - differential feed, 309
 - dipole, 83, 89
 - dual circular polarization, 311
 - efficiency, 26, 196
 - electrically small, 307
 - external noise, 171
 - half-wave dipole, 86, 211
 - Hertzian dipole, 81
 - horn, 101
 - impedance, 51
 - infinitesimal dipole, 81
 - linear, 83
 - log periodic, 303
 - loop, 86, 89, 147
 - loss, 64, 143
 - loss noise, 171
 - narrowband, 300
 - open circuit voltage, 55
 - open-ended waveguide, 99
 - parameter, 45, 210
 - passive, 47, 180, 189, 192, 197
 - passive, reciprocal, 161
 - patch, 92, 310
 - patch excited cup, 301
 - polarization, 49
 - quality factor bound, 307
 - receiving, 51
 - reflector, 1, 2, 10, 15, 19, 22, 62, 65, 75, 96, 101, 103, 226, 235, 240, 278, 303, 332, 336, 356, 412, 415
 - single-ended feed, 309
 - sinuous, 15, 300, 304
 - SNR model, 70
 - spiral, 304
 - temperature, 60, 66, 67, 180, 199, 215
 - terms, 24, 185
 - transmitting, 42
 - ultrawideband, 308
- APERTIF, 16, 20, 315, 420
- Aperture
 - antenna, 25, 43, 48, 76, 96, 101, 105, 116, 127, 171, 264
 - array, 2, 11, 12, 14, 221, 222, 224, 244, 259, 264, 300, 307, 315, 333, 341, 377, 396, 412, 415, 425, 432

array design considerations, 226	system modeling, 254
array effective area, 227	transmitting, 122
efficiency, 25, 196	types, 10
uniformly illuminated, 98	uniform linear, 107, 109
Aperture synthesis, <i>see</i> Interferometry, aperture synthesis	Y-factor, 208
Area	ASIC, 432
receiving, 51	ASKAP, 17, 20, 221, 306, 315, 319, 384, 397, 410, 420
effective, 51, 52, 56, 194, 227	ASTRON, 16, 226, 304, 315, 407, 435
Array	Atmospheric windows, 4
aperture, 2, 11, 14, 221, 222, 224, 244, 259, 300, 307, 315, 333, 341, 377, 396, 412, 415, 425, 432	Auxiliary antenna, 372, 384
aperture, design considerations, 226	Available
aperture, effective area, 227	gain, 52, 58, 189
beam scanning, 111	power, 51
calibration, 325, 333	power, active antenna, 190
calibration, polarimetric, 368	power, network source, 191
correlation matrix, 166, 175, 187, 194, 329, 332, 333, 337, 347, 350, 353, 361, 369, 374, 378, 380, 388	Axial ratio, 311, 359, 364
dense, 223, 228	Balun, 301, 306, 309, 314
dense dipole, 306	Marchand, 309
directivity estimate, 115	Bandwidth, 27, 29, 62, 91, 141, 164, 307, 327
Dolph–Chebyshev, 117	antenna, 300
dual polarization, 302, 306, 360	relative, 300, 308
element, 11, 13, 18, 108, 111, 124, 142, 149, 158, 166, 242, 300–313	system noise equivalent, 8, 58, 71, 164, 173
element excitation, 116, 130	Baseband
element radiation pattern, 107	representation, 163
element, open circuit voltage, 157, 160, 184, 331, 338	subsampling, 319
factor, xi, 2, 80, 106–120, 126, 149, 224, 230, 233, 249, 330, 341	Baseline, 8, 222, 233, 371, 379, 397, 403, 409, 414, 421
feed, 2, 11, 15, 23, 207, 221, 243, 254, 273, 279, 304, 310, 348, 377, 384, 389	Basis function, 255, 262
feed, design aspects, 235	Beam
gain, 181, 347	displacement factor, 358
hierarchical, 396	independent, 358
impedance matrix, 212	Nyquist, 358
irregular, 230	pair, correlation matrix, 362
isotropic radiators, 136	pair, polarimetric, 359, 361
limited scan, 111	pattern, 12, 28, 140, 210, 213, 326, 331, 336, 340, 345, 371, 377, 383, 398
low frequency, 12, 223, 227, 333, 426	pattern perturbation, 380
manifold, 330	pattern, pencil, 117
network model, 154	scanning, 111, 325
octagonal ring, 306	solid angle, 358
overlap matrix, 212	Beamformer, 3
passive, 142	biscalar, 369
polarimetric, 360	Capon’s, 352
response vector, 330	conjugate field match, 139, 216, 338–340
sensitivity map, 356	constrained response, 345
signal processing, 325	digital, 425
sparse, 223, 230	linearly constrained minimum variance, 351
sparse, regular, 232	maximum directivity, 137, 146, 148, 150, 195, 197, 216, 333, 338–340, 347, 355
spatial response, 333	maximum gain, 145, 195, 339, 355
	maximum SNR, 214, 328, 333, 347, 351, 355, 367, 368, 373, 380, 386, 391
	minimum mean squared error, 349
	minimum variance distortionless response, 352
	narrowband, 325, 338

- normalization, 347
- pattern matching, 345
- relationships among, 352, 355
- response pattern, 331
- singular vector, 353
- weight vector, 130
- windowed, 340
- Beamformer weights, 130
 - complex conjugate convention, 132, 327
 - computation, 420, 426
 - open circuit referenced, 160
- Beamforming, 108, 122, 137, 155, 160, 216, 236, 325–391
 - adaptive, 328, 337, 347, 370, 420
 - analog, 389
 - broadband, 337
 - data-independent, 338
 - digital, 389
 - implementation, 389, 425
 - narrowband, 337, 421
 - polarimetric, 328
 - post-correlation, 336, 357, 383, 389, 425
 - real time, 425, 426
 - spatial code, 354
 - statistically optimal, 346
- Beamwidth
 - half-power, 47, 358
 - null to null, 47
- Bias correction, 380
- Biscalar beamformer, 369
- Blackbody radiation, 9, 57, 61, 62
- Bosma's theorem, 171, 289
- Brightness, 6
 - temperature, 62
- Broadband
 - antenna, 300, 302
 - beamformer, 326
- Broadside, 341
- Calibration, 325, 327
 - in situ*, 333
 - array, 333, 348
 - drift, 336
 - grid, 335
 - open-loop, 410
 - polarimetric, 368
 - procedure, 335
 - source, 327, 332–336, 365, 368, 388, 396, 410
 - stability, 336
- Capacity, 353
- Capon's beamformer, 352
- CBFM, *see* Characteristic basis function method
- CEM, *see* Computational electromagnetics
- Central processing unit, 440
- CFM, *see* Conjugate field match
- Channel matrix, 352
- Characteristic
 - basis function method, 264, 265
 - basis function method (multi-level), 269
 - impedance, 44
- Chebyshev
 - beamformer, 106, 115, 117, 150, 249
 - window, 342, 346
- Checkerboard array, 17, 20, 305
- CHIME, 14
- CLEAN, 380, 400, 402, 412
- Cluster feed, 11, 237
- Coherency vector, 361, 366
- Cold load, 209
- Collocation, 256
- Common mode, 309
- Complex baseband, 163
- Complex conjugate convention, 132, 327
- Computational electromagnetics, 253
- Conjugate
 - field match, 139, 146, 216, 228, 235, 240, 291, 327, 338–340
 - field match, pros and cons, 242
 - gradient method, 247
 - match, 51, 58, 307
- Connection matrix, 290
- Conservation of energy, 141
- Constrained response beamformer, 345
- Constraint, 127, 231, 245, 351
 - derivative, 351
 - multiple, 351
 - pattern, 330, 332, 334, 335, 345, 347, 351, 372
- Coordinate system, 40
 - rectangular, 40
 - spherical, 41
- Correlation matrix
 - array response, 166, 194, 332, 333, 337, 347, 350, 353, 369, 378, 380, 388
 - beam pair, 362
 - definition, 164
 - diagonal, 165
 - external noise, 168
 - isotropic noise, 170, 187
 - loss noise, 171
 - noise, 175, 333–335, 347, 353, 374
 - noise wave, 289
 - point source, 329
 - polarization state, 361
 - receiver noise, 172
 - receiver noise, approximate, 174
 - signal, 167, 336, 347, 361
 - signal and noise, 163, 335
- Correlator array, 396
- Correlators
 - computational cost, 422
 - FX, 422
 - XF, 421
 - XF versus FX, 422

Cosmic microwave background radiation, 9	improved, 272
Covariance matrix, <i>see</i> Correlation matrix	iterative, 275
CPU, <i>see</i> Central processing unit	Downconversion, 319
Cross-polarization, 50	DSP, <i>see</i> Digital signal processing
discrimination, 31, 362	Dual
isolation, 31, 362	circular polarization, 311
Cross-subspace projection, 384	linear polarization, 312
Cryogenic	Effective
amplifier, 16, 315	area, 51, 52, 56, 194, 227, 327
phased array feed, 16, 21, 314	system temperature, 26, 76
CSIRO, 17, 20, 305, 309, 314	Efficiency
Dense	antenna, 26, 196
array, 223, 228	aperture, 25, 196
dipole array, 306	embedded element, 124
Derivative constraint, 351	radiation, 26, 47, 61, 143
DGFM, <i>see</i> Domain Green’s function method	receiving, 47, 191
Differential feed, 309	spillover, 65
Digital signal processing, 4, 12, 18, 122, 131, 154,	survey, 27, 359
166, 180, 204, 326, 354, 391, 420–442	EFIE, <i>see</i> Electric field integral equation
beamformers, 425	Eigenchannel, 354
correlators, 421–424	Eigenvalue, 140, 216, 274, 331, 335, 368, 376, 384
digitization, 424	problem, generalized, 137, 138, 339, 347, 368
hardware, 431	Electric field integral equation, 256, 257
Nyquist sampling, 425	Element
second band sampling, 425	array, 11, 13, 18, 108, 111, 124, 142, 149, 158,
Dipole, 83, 89, 211	166, 242, 300–313
half-wave, 86, 147	embedded pattern, 121, 125, 127, 132, 211, 329,
Hertzian, 81	338, 340
horizontal, 226	isotropic, 344
thickened, 301	loaded pattern, 213
Direct Fourier transform, 408	loading condition, 128
Direction of arrival, 331	open circuit voltage, 157, 160, 184, 331, 338
Directivity, 48	pattern, primary, 254
approximation, 140	pattern, secondary, 254
map, 47, 214	types, 300
optimization, 137	Embedded
over element spacing, 216	element efficiency, 124
overlap integral formulation, 133	element pattern, 121, 125, 127, 132, 211, 329,
partial, 47, 134, 338	338, 340
receiving pattern, 161	EMBRACE, 12, 221, 225, 229, 304, 315
Dirichlet function, 113	Emissivity, 62
Dishes	Equivalent
Arecibo, 1	temperature, 59
cost, 1	circuit model, 54
FAST, 1, 102	current, 54, 97
GBT, 18, 21	current model, antenna, 43
Green Bank 20 Meter Telescope, 346, 387	network source, 156
parabolic, 1, 10, 15, 19, 22, 65, 75, 101, 226, 235,	source, xii, 51, 53, 57, 122, 124, 128, 149, 176,
278, 303, 332, 336, 356, 415	191, 254
Parkes, 384	temperature, 58, 60
versus aperture arrays, 224	Expectation, 40, 164, 167, 288, 332, 350, 373
Dispersion relation, 93	Extended source, 6, 348
Dolph–Chebyshev beamformer, 106, 115, 117, 150,	External noise, 2, 60, 62–65, 180, 196, 203, 214,
249, 342	286, 353
Domain decomposition, 263	correlation matrix, 168
Domain Green’s function method, 269	isotropic, 170, 171, 189, 200, 338, 349

- Far field, 40, 42, 48, 87, 92, 95, 103, 126, 136, 142, 157, 278, 329
 - point source, array response to, 329
 - radiation integral, 43, 279
- FAST, 1, 102, 426
- Fast Fourier transform, *see* FFT
- Fast multipole method, 277–278
 - multilevel fast multipole algorithm, 278
- FDTD, *see* Finite difference time domain method
- Feasible region, 245
- Feed
 - reflector interaction, 273, 280
 - cluster, 11
 - horn, 11
- FEM, *see* Finite element method
- FFT, 400, 402, 420
 - and FX correlator, 422
 - and polyphase filters, 429
 - comparison with Fourier transform, 409
 - telescope, 399
- Field
 - (under)sampling, 236
 - incident, 51, 54, 101, 147, 157, 181, 211, 284, 330, 360, 363
 - scattered, 147, 235
- Field of view, 11, 27, 224, 243, 325, 327, 332, 359, 396
 - and number of beams, 357
 - definition, 356
 - survey speed weighted, 27, 356
- Field programmable gate array, 432–438
 - ROACH board, 432
 - SKARAB board, 434
 - UniBoard, 435
- Figure of merit, 24, 71, 154, 176, 203, 208, 243, 316
- Filter bank, 337
- Filtering, 319
- Finite
 - difference time domain method, 253, 285
 - element method, 253, 285
 - impulse response filter, 326, 340
- Fixed word length arithmetic, 348
- FLAG, 18, 21, 302
- Flux density, 6, 44, 46
 - system equivalent, 27
- Focal plane array, *see* Phased array feed
- Focal plane, fields in, 235, 348
- Fourier
 - components, 278
 - discrete, 409
 - series, 94, 120
 - shift theorem, 107
 - transform, 11, 44, 99, 102, 259, 284, 288, 342, 396, 397, 401, 415, 421, 427
 - transform, direct, 408
- FoV, *see* Field of view
- FPA, *see* Phased array feed
- FPGA, *see* Field programmable gate array
- Friis transmission formula, 31
- Functional analysis
 - linear operator notation, 255
- Fundamental noise theorem, 175
- G/T, 8
- Gain, 62
 - antenna, 8, 48, 49
 - array, 181
 - available, 58
 - isotropic noise, 182
 - maximum, 103, 145, 195, 339, 355
 - realized, 206
 - SNR, 181
 - transmitting array, 144
 - variation, 340
 - white noise, 184
- Galerkin
 - and MoM, 256
- Gaussian quadrature, 262
- GBT, 18, 21
- Generalized eigenvalue problem, 137, 138, 347, 368
- Genetic algorithm, 248
- GPU, *see* Graphical processing unit
- Gradient-free, 246
- Graphical processing unit, 438–440
 - CUDA, 438
 - OpenCL, 438
- Grating lobe, 110, 140
- Green Bank Observatory, 15, 21, 32, 301, 304, 346, 387
- Green's function, free-space, 280
- Ground shield, 209
- Half-power beamwidth, 47, 357–359
- Half-wave dipole, 86, 147, 211
- HERA, 13
- Hertzian dipole, 81, 147
- Hierarchical array, 396
- Hilbert space, 375
- Horn
 - antenna, 101
 - feed, 11
- Hot load, 209
- Hot/cold sky method, 208
- HPBW, *see* Beamwidth, half-power
- Hydrogen line, *see* Radio astronomy, HI line
- IBC, *see* Surface impedance
- IEEE standard antenna terms, 39, 45, 46, 48, 51, 60, 64, 179, 185, 192, 198, 203, 362
- IID, *see* Independent identically distributed
- Image reject mixer, 319
- Impedance
 - matching, 204, 205
 - matrix, 123, 212
 - mismatch, 52, 73

Incident field, 51, 54, 101, 147, 157, 181, 211, 284, 330, 360, 363	Jacobi method, 273
Independent	Jansky
beams, 358	Karl G., 4
identically distributed, 165, 182, 184, 350	unit, 6
Integration	JIVE, 435
long term, 380	Jones matrix, 360, 364, 368, 413
numerical, 127, 135, 212, 258, 260, 262, 279, 280, 291	Kronecker product, 366, 381
short term, 372	Krylov subspace, 265
Interference to noise ratio, 373, 374, 378, 383, 386	MBF enhanced iteration, 276
Interferometry, 3, 10, 396–417	Limited scan array, 111
1st generation calibration, 410–411	Linearly constrained minimum variance
2nd generation calibration, 412	beamformer, 351
3rd generation calibration, 415–416	LNA, <i>see</i> Low noise amplifier
and subspace projection, 379	Loaded element pattern, 213
aperture synthesis, 397	Loading condition, element, 128
baseline, 8, 222, 233, 371, 379, 397, 398, 403, 409, 414, 421	LOFAR, 12, 222, 226, 232, 301, 315, 389, 412, 416, 420, 426
calibration, 410–412, 415–416	Log periodic antenna, 303
CLEAN, 400	Long term integration, 380
closure relationships, 411–412	Loop antenna, 86, 89, 147
computational cost, 409	Loss, 143
direction cosines, 398	antenna, 61, 64
direction-dependent effects, 415	factor, 59, 61
direction-dependent effects, LOFAR example, 416	noise, 61, 63, 171
direction-independent effects, 415	ohmic and dielectric, 48, 53
Earth rotation synthesis, 403–410	tangent, 311
east-west array, 404	Lossless, resonant, minimum scattering
gridding, 400	approximation, xii, 3, 80, 104, 106, 121, 146, 148, 211, 212
Jones matrix, 413	Lossy
one-dimensional synthesis example, 400–403	component, 59
point spread function, 401, 408, 415	material, 26, 143, 171
primary beams, 415	Low noise amplifier, 52, 60, 67, 172, 313
Radio Interferometry Measurement Equation, 412–415	characterization, 317
source brightness, 398	design, 316
van Cittert–Zernike theorem, 398	differential, 207, 306, 309, 314
visibilities, 11, 397, 398	noise figure, 316
Intermediate frequency, 319	single-ended, 314
Inverse sensitivity, 26, 76	spot cooling, 315
IQ mixer, 319	LRMSA, <i>see</i> Lossless, resonant, minimum
Irregular array, 230	scattering approximation, 211
Isolation, 311	LWA, 13, 426
Isotropic	Macro basis function method, 262, 264
external noise, 170, 338	Magnetic field integral equation, 280
noise gain, 182	Main lobe, 109, 325
noise response, 170, 175, 186–190, 194, 198, 200, 208	Map
noise response, measuring, 188	directivity, 214
pattern, 46	sensitivity, 356
radiator, 46, 80, 136, 344	Matching, impedance, 52
Iterative method, 246, 263, 272, 275, 278, 336, 400, 412	Matrix
Jacobi, 282	correlation, 163
	covariance, 163
	mutual impedance, 141
	mutual reactance, 141
	mutual resistance, 141
	pattern overlap, 132, 141

- rank one, 135, 167, 331, 332, 338, 348, 369
- symmetric, 141
- trace, 361
- Maximum
 - directivity beamformer, 137, 146, 148, 150, 195, 197, 216, 328, 333, 338–340, 347, 355
 - gain beamformer, 145, 195, 328, 339, 355
 - SNR beamformer, 214, 328, 333, 347, 351, 355, 367, 368, 373, 380, 386, 391
- MeerKAT, 225, 397, 410, 421, 432
- Mesh, 256
- Method
 - of moments, 253, 255
 - of weighted residuals, 255
- MFAA, 14
- MFIE, *see* Magnetic field integral equation
- Microstrip patch antenna, 92, 310, 312
- Microwave
 - absorber, 209
 - radiometry, 28
- Minimum
 - detectable signal, 8
 - mean squared error beamformer, 349
 - variance distortionless response, 352
 - variance RFI mitigation methods, 371
- Mixer
 - image reject, 319
 - IQ, 319
- MoM, *see* Method of moments
- Mueller matrix, 365
- Multipath, 354, 370
- Multiple input multiple output communication, 352
- Multiple sidelobe canceler, 372
- Multipole expansion, 278
- Mutual
 - coupling, 2, 80, 106, 116, 120, 123, 124, 126, 131, 133, 137, 142, 146, 148, 158, 173, 177, 213, 216, 227, 230, 233, 242, 266, 270, 271, 280, 304, 330, 333, 339, 341, 345, 374, 378, 416
 - coupling, definition, 123
 - impedance matrix, 141
 - reactance matrix, 141
 - resistance matrix, 141
- MWA, 13, 420, 426
- Narrowband
 - antenna, 300
 - beamforming, 325, 337, 371, 421
 - condition, 337
- Network
 - analysis, xi, xii, 2, 3, 106, 120, 123, 126, 131, 141, 145, 154, 158, 160, 172, 176, 180, 186, 254, 352
 - source, xii, 122, 124, 128, 149, 156, 176, 191, 254
- Noise
 - antenna loss, 61
 - budget, 70
 - coupling, 206
 - external, 62–64, 168, 170, 171
 - factor, 59
 - figure, 58, 59
 - figure, cascaded, 60
 - isotropic, 170, 171, 175, 186–190, 194, 198, 208
 - loss, 63, 171
 - matching, 67, 204, 205
 - matching efficiency, 202
 - model, 355
 - parameters, 69
 - receiver, 57, 66, 172, 199, 204
 - sky, 62
 - spillover, 65
 - system, 8, 26, 76, 198, 199, 203, 211, 214
 - temperature, 60, 62, 66, 67, 180, 197, 199, 200, 215
 - theorem, 175
 - thermal, 57, 58
 - whitening, 386
- Noise wave, 69, 171, 288, 316
 - correlation matrix, 289
 - representation, 206, 286
- Norton equivalent, 53
- Null, 110
 - deep, 373, 375, 384
 - depth, 377
 - placement, 337
- Number of beams, 27, 29, 243, 333, 357
- Numerical
 - integration, 127, 135, 212, 258, 260, 262, 279, 280, 291
 - modeling, 253
- Nyquist
 - beams, 357–359
 - criterion, 111, 112
 - sampling, 425
- Objective function, 248
- Octagonal ring array, 306
- Open circuit voltage, 54, 55, 160, 184, 188, 331, 338
 - array element, 157, 349
- Open-ended waveguide, 99
- Optimization, 11, 198, 204, 253
 - algorithms, 244
 - array design, 291
 - directivity, 137
 - objective function, 248
- Orthogonal projection, 375
- Orthogonality principle, 349
- Overlap
 - integral, 133
 - integral, computing, 135
 - integral, primary or secondary patterns, 254
 - matrix, 132, 133, 141, 142, 145, 212, 340
- PAF, *see* Phased array feed

PAPER, 13, 16	incident, 55, 157, 159, 213, 239, 330, 360
Parkes Observatory, 384	polarization, 50
Partial	power flux density, 51
directivity, 134, 338	spectrum expansion, 284
effective area, 194	time harmonic, 7
Particle swarm optimization, 247	Plasma frequency, 5
Passive	PO, <i>see</i> Physical optics approximation
antenna, 47, 161, 180, 189, 192, 197	Point
array, 142	constraint, 345
array elements, 156	source, 6, 82, 102, 167, 191, 265, 327, 330, 333,
component, 171	337, 347, 350, 355, 360, 391, 401, 408, 412,
remote sensing, 2, 18	414
Patch antenna, 92, 310	spread function, 401, 408, 415
Patch excited cup antenna, 301	Polarimetric
Pattern	array, 359
constraint, 345	array calibration, 368
matching beamformer, 345	array calibration, approximate, 368
overlap integrals, 132	beam pair, 359, 361
perturbation, 380	beamforming, 328, 359
synthesis, 113, 119	beamforming, optimal, 367
Peeling algorithm, 380	calibration, 359
Pencil beam, 117	Polarization
Periodic sinc function, 113	antenna, 47, 49, 50
Phase shifter, 24, 222, 389	coherency vector, 361, 366
Phased array	cross-, 50
contemporary usage, 1	dual, 14, 50, 302, 306, 352, 360
design and optimization, 221	dual circular, 311
design methods, 2	efficiency, 51
feed, 2, 11, 15, 23, 207, 221, 243, 254, 273, 279,	Jones matrix, 364
304, 310, 348, 377, 384, 389	Mueller matrix, 365
feed, cryogenic, 314	state, 360
feed, design aspects, 235	Stokes parameters, 365
fundamental noise theorem, 175	Polyphase filters, 327, 427–430
high sensitivity, 1	Position vector, 41, 42, 55, 157
history, 1	Post-correlation beamforming, 336, 357, 383, 389,
mutual coupling, 2, 80, 106, 116, 120, 123, 124,	425
126, 131, 133, 137, 142, 146, 148, 158, 173,	Power
177, 213, 216, 227, 230, 233, 242, 266, 270,	available, 51
271, 280, 304, 330, 333, 339, 341, 345, 374,	density, 46
378, 416	radiated, 44
mutual coupling, definition, 123	Poynting flux density, 44
numerical modeling, 253	Primary pattern, 254, 415
receiver vs. receptor, 4	Printed circuit board, 23, 92, 302, 305, 306, 310,
remote sensing, 18	313
satellite communication, 22	PTD, <i>see</i> Physical theory of diffraction
types, 10	Pulsars
Phasor, 39	discovery of, 10
Physical optics approximation, 102, 103, 236–238,	Q, <i>see</i> Quality factor
254, 278	Quadrature hybrid, 312
corrections, 280	Quadrature rule, 135, 212, 262, 280
implementation, 279	Quality factor, 92
Physical temperature, 58, 61	bound, 307
Physical theory of diffraction, 103, 236–238, 280	Quantum mechanics
Planck’s law, 9	bra-cket notation, 256
Plane wave, 49, 54, 97, 102, 111, 167, 194, 197,	Quasi-Newton method, 247
210, 235, 277, 349	Radiated power, 44

Radiation	SNR model, 175
efficiency, 26, 47, 48, 53, 61, 72, 143, 311	Reciprocal, 141
pattern, 46, 333	antenna, 161
resistance, 44	array elements, 156
Radio astronomy, 4, 25	Reciprocity, 54, 55, 160, 196, 249
“Cradle of Life”, 9	Rectangular coordinates, 40
history, 4	Reference
beam area, 6	plane, 64, 131, 155, 338, 348
bremsstrahlung, 6	plane, transformation, 124, 146, 159, 167, 168,
continuum, 5	174, 188, 201, 213, 329, 348, 355
exoplanets, 9	temperature, 58
HI line, 6	Reflector
non-thermal origin, 9	beam displacement factor, 358
polarization, 5	cylindrical, 13, 102
reading, 10	illumination taper, 237
science drivers, 9	parabolic, 1, 2, 10, 15, 19, 22, 62, 65, 75, 96, 101,
science goals, 9	103, 226, 235, 240, 278, 303, 332, 336, 356,
SETI, 9	412, 415
spectral line, 5	scattering, 254
synchrotron radiation, 6	spherical, 102
Radio camera, 11	surface error, 303
Radio frequency interference, 3, 10, 57	torus, 240
mitigation, 320, 337, 369–389	Residual, 255
mitigation bias correction, 380	Resolution, 8
mitigation, real time, 420, 426	RFI, <i>see</i> Radio frequency interference
motion, 337	Rocket array, 305
moving, 380	Room temperature, T_0 , 58
Radiometer equation, 8	Ruze factor, 303
Radiometry, 8, 28	RWG element, 257
Random	S-parameters, 123, 142
process, 163	Sampling, 111, 112, 154, 222, 319, 401, 427, 441
search, 247	baseband, 319
vector, 164	density, 235
Rank one	Satellite communication, 22, 29
matrix, 135, 138, 167, 331, 332, 338, 348, 369	Scan element pattern, 126
signal, 138	Scattered field, 147, 235
Rayleigh–Jeans law, 9	Scene, 62
Reaction integral, 54	Schellkunoff representation, 113
Realized gain, 206	Secondary pattern, 254, 415
Reber, 4	SEFD, <i>see</i> System equivalent flux density
Receiver	Self-calibration, 336, 396, 410, 412, 415
electronics, 313	Sensitivity, 8, 71, 327
noise, 66, 204	G/T_{sys} , 30
noise correlation matrix, 167, 172, 173, 175, 200,	beam, 332
209, 214	feed and reflector, 75
noise correlation matrix, approximate, 174	inverse, 26, 76
noise figure, 199	map, 47, 356
noise temperature, 199, 200	model, 207
sensitivity, 71	reduction factor, 356
Receiving	Separation of variables, 93
area, 51	Short term integration, 372
efficiency, 47, 48, 191, 211	Sidelobe, 110, 115, 325
pattern directivity, 161	level, 31, 46, 117, 340, 345
Receiving array	Signal of interest, 167
network model, 154	Signal processing
signal and noise model, 166	array, 325

- digital, 4, 12, 18, 122, 131, 154, 166, 180, 204, 326, 354, 391, 420–442
- Signal to interference plus noise ratio, 391
- Signal transport, 318
- Simplex method, 247
- Simulated annealing, 248
- Single-ended feed, 309
- Singular value decomposition, 266, 353
- Sinusoidal antenna, 15, 300, 304
- SKA, 9, 12, 16, 221, 227, 272, 304, 315, 371, 397, 416, 423, 431, 442
- SKADS, 13
- SNR, 25, 58, 60, 205
 - gain, 181, 347
 - maximum value, point source, 349
 - model, 70, 286
- Source
 - equivalent, xii, 51, 53, 57, 122, 124, 128, 149, 176, 191, 254
 - extended, 6, 348
 - impedance, 51, 53
 - network, xii, 122, 124, 128, 149, 176, 191, 254
 - point, 6, 82, 102, 167, 191, 265, 327, 330, 333, 337, 347, 350, 355, 360, 391, 401, 408, 412, 414
- Sparse
 - array, 223, 230, 396
 - array, regular, 232
- Spectroscopy, 421
- Spherical coordinates, 41
- Spherical wave, 49
- Spillover
 - efficiency, 65
 - noise, 65
- Spiral antenna, 304
- Spot cooling, 315
- Square Kilometre Array, *see* SKA
- Standard, IEEE, antenna terms, 39, 45, 46, 48, 51, 60, 64, 179, 185, 192, 198, 203, 362
- Station, 228, 396
- Steering vector, 329–331, 335, 338, 350
- Stochastic, 246
- Stokes parameters, 5, 365, 414
 - error, 367
- Subband, 39, 325, 337, 371
- Subspace projection, 375
 - and synthesis imaging, 379
 - beamforming, 377
- Superdirectivity, 115, 116, 140, 216, 228
 - on receive, 184
- Surface impedance, 261
- Survey
 - efficiency, 27, 359
 - speed, 11, 27, 243, 244, 301, 356, 359
 - speed weighted field of view, 27, 356
- SVD, *see* Singular value decomposition
- Symmetric matrix, 141
- Synthesis imaging, *see* Interferometry
- Synthetic functions approach, 264
- System
 - equivalent flux density, 27
 - modeling, 254
 - noise, 8, 198, 199, 203, 214
 - noise equivalent bandwidth, 8, 58, 71, 164, 173
 - noise temperature, 26, 76, 211, 226
 - reference impedance, 67
 - reference temperature, 58
 - temperature, effective, 26, 76
- Taper efficiency, 115
- Tapered slot antenna, 14, 72, 125, 229, 262, 270, 300, 304, 308
- Temperature
 - ambient, 62
 - antenna, 60, 66, 67, 180, 199, 215
 - equivalent, 9, 58, 59
 - physical, 58
- Thévenin equivalent, 51, 53
- Thermal
 - radiation, 57
 - equilibrium, 59
 - noise, 9, 57, 58
 - radiation, 62
- Thickened dipole, 301
- Time
 - average, 40, 164, 167, 288, 332, 350, 373
 - harmonic, 40
- Transformation
 - element loading condition, 128
 - reference plane, 124, 146, 159, 167, 168, 174, 188, 201, 213, 329, 348, 355
- Transistor, 314
- Transmitting
 - antenna, 42
 - array, 122
 - array, equivalent, 196
 - array, gain, 144
- TSA, *see* Tapered slot antenna
- Twiss’s theorem, 171, 175, 188, 289
- ULA, *see* Uniform linear array
- Ultrawideband antenna, 308
- Uniform linear array, 107, 109, 344
 - directivity, 115
- UWB antenna, *see* Ultrawideband antenna
- Vector current moment, 44, 279
- Visible window method, 113
- Vivaldi, *see* Tapered slot antenna
- VLA, 397
- VLBI, 10, 396, 414, 435
- Voltage
 - open circuit, 54
- Wave vector, 54, 331

Waveguide, 99
Weighting function, 255
White noise gain, 184
Wideband, 164, 421, 423
 ADC, 425
 antenna, 300
 array, 16, 207
 element, 223, 300
 feed, 304
 PAF, 240
 RFI, 388
 signal, 122
 source, 6
Wiener filter, 349
Wiener–Khinchine theorem, 288
Window function, 341, 342, 429
 2-D array, 343
Windowed beamformer, 340–345
WSRT, 12, 19, 281, 399, 407
XPD, *see* Cross-polarization discrimination
XPI, *see* Cross-polarization isolation
Y-factor, 208
 measurement, 180, 189, 208, 317
Zero forcing, 375