

INDEX

- AC (alternating current) circuit fundamentals, 86–8
- access (construction), 233–5
- active stall, 79
- actuator disc, 35–8
- aerodynamic damping, 153–5
- aerodynamic loading
 - deterministic, 144–7
 - reference frames, 142–4
 - steady, 144
 - stochastic, 147–9
- aerodynamic theory
 - actuator disc, 35–8
 - BEM, 42–5
 - blade element, 39–41
 - drag, 46–7
 - dynamic inflow, 59–60
 - momentum theory correction, 47–8
 - multiple streamtube, 38–9
 - radial flow and stall delay, 48
 - rotor wake, 50–5
 - stall effects, 57–8
 - tangential induction factor, 47
 - tip loss correction, 49–50
- aeroelastic codes, 166–7
- aerofoil, 11
- ailerons, 81
- anisotropy, 174
- annual wind speed, 22, 23
- array interactions
 - array losses, 217–23
 - wake turbulence, 223–5
- aviation
 - collision risk, 258–60
 - radar interference, 260–4
- BEM theory
 - as combined theory, 42–5
 - modifications to, 46–50
- bending analysis (blade), 189–91
- Betz limit, 37
- binning, 11
- bird impacts, 244–6
- blade balancing, 200–1
- blade edgewise vibration, 156–9
- blade element theory, 39–41
- blade manufacture
 - balancing in, 200–1
 - GFRP (glass fibre reinforced plastic), 195–7
 - wood-epoxy, 197–9
- blade number, 72–4
- blade structure
 - bending analysis, 189–91
 - cantilever beam model, 179–84
 - composite elements, 185–9
 - compressive buckling in, 184–5
 - shear, 185
- blade testing, 201–3
- blade twist, 70–2
- Blyth, James, 5–6
- boundary layer, 15
- brakes, mechanical, 130
- Campbell diagram, 155
- cantilever beam model, 179–84
- capacity factor, 11
- carbon fibre reinforced plastic (CRFP), 174
- Carter, President Jimmy, 1
- centrifugal loading, 150–1
- collision risk, 258–60
- composites
 - anisotropy, 174
 - elements of, 185–9
 - fibre-reinforced, 174–9
- compressive buckling, 184–5
- constant speed, variable pitch (CSVP), 120–3
- construction (wind turbine)
 - access, 233–5
 - crane operations, 235–7
 - crane road weight, 237–40
 - foundations, 226–32
 - transport, 232–3
- control
 - sector management, 132–3
 - starting and stopping, 128–32
 - yaw, 117–18
- control, power limiting
 - constant speed, variable pitch (CSVP), 120–3
 - stall regulation, 120
 - variable speed, variable pitch (VSVP), 123–7
- Coriolis effect, 14
- cost (wind energy)
 - calculations, 269–70
 - installation, 271–2
 - intermittent generation affecting, 273
 - operational, 272–3
 - total, 273–4
- crane operations (construction), 235–7
- crane road weight, 237–40

dampers, mechanical, 158
damping, 153–5
deterministic loading, 140, 144–7, 165–6
distributed ownership, 283–5
diurnal wind variation, 24
double/multiple stall, 57–8
doubly-fed induction generator (DFIG), 11, 93
downwind rotor design (HAWT), 81–3
drag, 46–7
dynamic inflow, 59–60
dynamic loading, 137–9
dynamic response measurement
 load spectra, 163–4
 mean loads, 161–3
 for stochastic and deterministic loading, 165–6
dynamic stall, 57–8

ecological impacts, 244–7
economics (wind turbine)
 cost, 265–6
 price, 274–6
 supply and demand, 276–83
electrical generator types
 doubly fed induction generator, 93
 gearless, 95
 history of, 95–9
 induction generator, 91–3
 permanent magnet generator (PMG), 90
 synchronous generator, 90
 variable-speed generator, 94–5
electrical principles
 fundamentals, 86–8
 metering, 89
electricity generation history (wind turbine), 5–6
electromechanical loading, 151–2
energy crisis (1970s), 1–2
environment
 ecological, 244–7
 noise, 251–6
 pollution risk, 251
European windmills
 early sail, 4
 windfarm revolution in, 7–9

fatigue prediction, 167–70
fault level (electrical), 101
fault protection, 107
fibre-reinforced composites, 174–9
fixed pitch (HAWT), 74–5
flicker
 defined, 103–5
 shadow, 250–1
foundations (construction), 226–32

gearless generators, 95
Gedser wind turbine, 6
generators, 89–99
geostrophic wind, 13–14

GFRP (glass fibre reinforced plastic) blade manufacture, 195–7
Gigha Community windfarm, 285–8
gradient wind speed, 14–15
gravitational loading, 149
grid capacity, 107–11
gust factor, 25
gust measurement, 25–6
gyroscopic loading, 149–50

harmonics, 107
horizontal-axis wind turbines (HAWT)
 blade element theory, 39–41
 cantilever beam model for, 179–84
 composite blade structure, 185–9
 Costa Head wind turbine, 6
 defined, 11
 drag and, 46–7
 Gedser wind turbine, 6
 lightning protection for, 111
 near-wake measurements of, 54
 tangential induction factor and, 47
 tip loss correction, 49–50
 vibration and resonance loading, 152–3
 wood-epoxy blade manufacture, 197–9
 yaw operation in, 56
horizontal-axis wind turbines rotor aerodynamic control
 ailerons, 81
 fixed pitch, 74–5
 pitch control, 75–80
 spoilers, 80
 tip brakes, 81
horizontal-axis wind turbines rotor design
 blade twist and pitch, 70–2
 downwind, 81–3
 number of blades in, 72–4
 power, thrust, and torque, 64–6
 power efficiency, 66–8
 tip speed ratio and solidity, 68–70
Hutter, Ulrich, 174

IEC Wind Class, 211
induction generator, 91–3
installation cost, 271–2
instantaneous voltage, 86
inter-annual wind speed, 21
intermittent generation, 273

Juul, Johannes, 6

la Cour, Poul, 6
levelised cost of energy (LCoE), 269
lidar, 118
lift, aerodynamic, 41
lightning protection, 111–14
load spectra, 163–4
loading (structural)
 aerodynamic, 142–9

- deterministic, 140, 165–6
- dynamic, 137
- dynamic response measurement, 159–66
- dynamic response of simple system, 137–9
- electromechanical, 151–2
- gravitational, 149
- gyroscopic and centrifugal, 149–51
- modal analysis, 139–40
- predicting, 166–70
- static, 136
- stochastic, 142, 165–6
- vibration and resonance, 152–3
- loading prediction
 - aeroelastic codes for, 166–7
 - fatigue, 167–70
- mammal impacts, 246–7
- material safety factor, 191
- MCP analysis, 213–17
- mean load measurement, 161–3
- metering, 89
- microwave interference, 264–5
- modal analysis, 139–40
- momentum theory correction, 47–8
- multiple streamtube theory, 38–9
- nacelle, 11
- network characteristics (electrical), 99–101
- noise
 - origins of, 251–3
 - planning limits to, 256–8
 - predicting, 253–6
- oil prices, 2
- operational cost, 272–3
- ownership
 - distributed, 283–5
 - Gigha Community windfarm, 285–8
- panemones, 2
- particle image velocimetry (PIV), 53
- permanent magnet generator (PMG), 11, 90
- pitch (HAWT), 70–2
- pitch angle, 72
- pitch control (HAWT), 75–80
- planning
 - aviation, 258–64
 - microwave interference, 264–5
 - public safety, 247
 - shadow flicker, 250–1
 - television, 265–6
 - visual impact, 247–50
- policy (wind energy)
 - ownership, 283–8
 - renewables (UK), 289–93
- pollution risk, 251
- post mills, 4
- power
 - HAWT rotor, 64–8
 - limiting, 119–27
- power coefficient, 11
- power factor, 11
- power quality
 - fault protection, 107
 - flicker, 103–5
 - grid capacity, 107–11
 - harmonics, 107
 - lightning protection, 111–14
 - network characteristics, 99–101
 - statcoms and SVCs, 105–7
 - steady-state voltage, 101–3
- Prandtl, Ludwig, 52
- pricing (wind energy), 274–6
- public safety, 247–8
- radar interference, 260–4
- radial flow, 48
- Rainflow algorithm, 168
- rated power, 11
- Rayleigh distribution, 26
- reference frames, 142–4
- renewables policy (UK), 289–93
- resonance
 - loading, 152–3
 - tower, 155–6
- Riisager turbine, 8
- rock anchors, 229
- root attachment method, 191–4
- rotational sampling, 147
- rotor aerodynamic control
 - fixed pitch, 74–5
 - pitch control, 75–80
 - spoilers, 80
 - tip brakes, 81
- rotor blade technology
 - anisotropy, 174
 - blade manufacture, 194–201
 - blade structure, 179–91
 - fibre-reinforced composites, 174–9
 - root attachment method, 191–4
 - testing, 201–3
 - weight, 203–8
- rotor design
 - blade twist and pitch, 70–2
 - downwind rotor, 81–3
 - number of blades, 72–4
 - power, thrust, and torque, 64–6
 - power efficiency, 66–8
 - tip speed ratio and solidity, 68–70
- rotor wake
 - schematics of, 50–1
 - vortex wake analysis, 52
- roughness length, 15

sails (wind power), 2–4
scaling (of wind turbines), 9–10
sector management, 132–3
shadow flicker, 250–1
siting (wind turbine)
 array interactions, 217–25
 wind assessment, 210–17
Smeaton, John, 4, 5
smock mills, 4
solar energy, 13
solidity
 defined, 11
 HAWT rotor, 68–70
space scales (wind variation), 21–4
spoilers, 80
square cube law, 9
stall delay, 48
stall effects, 57–8
stall regulation
 HAWT rotor, 74–5
 for power control, 120
starting sequence, 128–32
statcoms, 105–7
static loading, 136
static VAR compensator (SVC), 105–7
steady loading, 144
steady-state voltage, 101–3
stochastic loading, 142, 147–9, 165–6
stopping sequence, 128–32
supply and demand
 background of, 276–7
 for on-site generation, 278–81
 wide scale generation, 281–3
synchronous generator, 90

tangential induction factor, 47
television interference, 265–6
thrust (HAWT), 64–6
time scales (wind variation), 21–4
tip brakes (HAWT), 81
tip loss correction, 49–50
tip speed ratio
 defined, 12
 HAWT rotor, 68–70
topography
 effects on wind, 27–31
 wind shear estimation and, 16
torque (HAWT), 64–6
tower resonance, 155–6
tower shadow, 144
transport (wind turbine), 232–3
turbulence, 18
 defined, 18–21
 site assessment of, 217
 wake, 223–5
turbulence intensity, 20–1

vacuum resin infusion moulding (VRIM)
 blade manufacturing, 194
 defined, 12
variable speed, variable pitch
 (VSVP), 123–7
variable-speed generator, 94–5
vertical-axis wind turbines (VAWT), 12
vibration
 blade edgewise, 156–9
 loading, 152–3
visual impact, 248–50
voltage (steady-state), 101–3
voltage control, 101
vortex wake
 analysis, 52
 near-wake measurements of, 53–5

wake turbulence, 223–5
Weibull wind distribution, 26–7
weight (rotor blade), 203–8
winch erection, 236
wind assessment
 MCP analysis, 213–17
 site measurement, 211–13
 turbulence and shear, 217
 wind resource, 210–11
wind characteristics
 geostrophic wind, 13–14
 gradient wind speed, 14–15
 gust measurement, 25–6
 time and space scales, 21–4
 topographic factors, 27–31
 turbulence, 18–21
 Weibull wind distribution, 26–7
 wind shear, 15–18
wind energy converter (WEC),
 12
wind shear, 15
 defined, 12, 15–18
 diurnal, 24
 profiles, 16
 for site assessment, 217
wind turbine generator (WTG), 12
wind turbine history
 archaeology, 2–4
 scaling, 9–10
 start of electric generation, 5–7
 windfarms, 7–9
windfarms
 Gigha Community, 285–8
 revolution, 7–9
wood-epoxy blade manufacture, 197–9

yaw
 control, 117–18
 operation in, 55