

## Index

- ABCD matrix, 59  
 aberrations, 21  
 accuracy, 32  
 achromatic doublet, 22  
 achromatic waveplate, 25  
 acousto-optic modulator, 26  
 action of a lens, 61  
 active medium, 115  
 Airy pattern, 86  
 Airy's disk, 86  
 aluminum mirror, 23  
 amplitude noise, 183  
 amplitude splitting, 91  
 analog spectrometer, 88  
 angle of incidence, 50  
 antenna pattern, 104, 106  
 AOM, 26  
 aspheric, 52  
 atmospheric bending, 51  
 atomic spectra database, 87
- bare mirror, 22  
 beam, 8  
 beam radius, 157, 158  
 beam waist, 158  
 beamsplitter, 22, 23  
 bi-convex/concave, 21  
 birefringence, 25  
 blazed grating, 82  
 blink response, 14  
 bolometer, 28  
 boundary conditions, 153  
 Bragg reflector, 98  
 Brewster angle, 156
- calcite, 167  
 caustic, 65  
 cavity stability, 139, 140  
 CCD, 27  
 center of fringe, 95  
 charge-coupled device, 27  
 chi-square, 37  
 chi-square cut, 40  
 chi-square surface, 38  
 Christiaan Huygens, 2
- chromatic aberration, 21  
 circular fringes, 114  
 circular polarization, 158  
 circular polarizers, 24  
 circulator, 162  
 class 3B, 14  
 classical alignment, 110  
 CMOS, 27  
 coherence, 9, 115  
 coherence length, 9  
 coherence time, 9  
 complementary metal oxide semiconductor, 27  
 complex beam parameter, 74  
 complex field amplitude, 8  
 complex radius of curvature, 74  
 compound lens, 21  
 cornea, 55  
 curve fitting, 35  
 curved phasefront, 114
- danger label, 14  
 data stream, 168  
 dielectric coatings, 97  
 dielectric layer stack, 98  
 diffracted order, 82  
 diffraction limited beam, 115  
 digital spectrometer, 87  
 direction of travel, 152  
 discharge tube, 87  
 donut mode, 145, 150
- electric field, 1  
 electro-optic modulator, 25  
 elliptical polarization, 158  
 end mirror, 133  
 enhanced metallic coating, 23  
 EOM, 25  
 error estimate, 32  
 error propagation, 33  
 etendue, 124  
 ether, 91  
 eye, 55
- Fabri-Perot etalon, 96  
 Faraday effect, 160

- Faraday isolator, 25, 160  
 fast lens, 77  
 field amplitude, 8  
 first-surface mirror, 22  
 fit parameter uncertainty, 40  
 fits, 35  
 Fizeau interferometer, 92  
 focusing, 21  
 forbidden transitions, 121  
 four-level laser, 121  
 four-level model, 120  
 Fourier propagation of TEM<sub>00</sub>, 80  
 Fourier transform code, 81  
 Fourier transform in two dimensions, 79  
 Fourier-transform spectroscopy, 99  
 Fraunhofer diffraction, 85  
 free-space propagation, 60  
 free-space circulator, 162  
 free-space modes, 74  
 frequency domain, 168  
 frequency noise, 183  
 Fresnel diffraction, 85  
 Fresnel equations, 153, 154  
 fringe center, 95  
 fringe wrapping, 111  
 fringes, 92  
  
 g-factor, 140  
 gain, 119  
 Galilean telescope, 63  
 Gaussian beam, 74, 78, 157  
 Gaussian noise, 168  
 geometric optics, 49  
 gold mirror, 23  
 Gouy phase, 76, 142, 158  
 grating, 81  
 grating equation, 82  
 gravitational wave interferometer layout, 105  
  
 half-silvered mirror, 24  
 halogen lamp, 17  
 helium-neon laser, 121  
 Helmholtz equation, 2  
 HeNe, 115  
 Hermite-Gaussian modes, 142, 143  
 horizontal error bars, 113  
 horizontal polarizer, 158  
 human eye, 55  
 Huygens' principle and/or integral, 2  
 Huygens' wavelets, 2  
  
 Iceland spar, 167  
 image, 53  
 imaging system, 52  
 in focus, 53  
 incoherent, 49  
  
 index of glass, 155  
 index of optical glasses, 155  
 index of refraction, 49  
 input beam, 91  
 input mirror, 133  
 interference pattern, 91  
 interferogram, 99  
 interferometer arm, 91  
 interferometry, 91  
 irradiance, 49  
 irradiance of TEM<sub>mn</sub>, 76  
  
 Jones matrix, 158  
 Jones vector, 156–158  
  
 laser, 19, 115  
 laser diode, 20  
 laser hazard classes, 13  
 laser safety, 13  
 laser safety glasses, 13  
 Laser Safety Officer, 13  
 laser-line mirror, 23  
 leakage beam, 134  
 LED, 18  
 lens, 21  
 lens of the eye, 55  
 light emitting diode, 18  
 linear medium, 152  
 linear polarization, 158  
 linear polarizers, 24  
 linewidth, 9  
 LSO, 13  
  
 Mach-Zehnder interferometer, 92  
 magnetic field, 1  
 magnification, 53  
 magnifying glass, 56  
 Malus' law, 160  
 Maxwell-Boltzmann statistics, 117  
 Maxwell's equations, 1  
 meniscus lens, 21  
 Michelson interferometer, 91, 110  
 Michelson sensitivity, 92  
 micro-LED, 19  
 microscope, 57  
 mirage, 52  
 mirror, 22  
 mode-matching, 146  
 monochromatic, 2, 115  
 multi-order waveplate, 25  
 multilayer coatings, 97  
 multilayer dielectric coating, 22  
 multiple beam interferometer, 96  
 multiple polarizing optics, 160  
  
 neodymium-YAG, 115

- Newton's rings, 114  
 non-polarizing beamsplitter, 22
- object, 53  
 offset error, 33  
 optical cavity, 133  
 optical coating, 22  
 optical density, 14  
 optical isolator, 25, 160  
 optical modulator, 25  
 optical path, 111, 112  
 optical standing wave, 133  
 out of focus, 53
- parasitic interference, 25, 160  
 parasitic interferometer, 176  
 paraxial approximation, 58, 73  
 paraxial beam, 157  
 paraxial wave equation, 8  
 partial polarization, 164  
 permeability, 1  
 permittivity, 1  
 phase offset, 158  
 photocurrent, 28, 29, 185  
 photodiode, 28  
 photodiode amplifier, 29  
 physical optics, 73  
 pinhole camera, 71  
 plane-polarized, 152  
 plane-wave cavity, 133  
 plano-convex/concave, 21  
 polarization, 152  
 polarization component, 152  
 polarized sunglasses, 153  
 polarizer, 24  
 polarizing optic, 156  
 population inversion, 115  
 power spectral density, 168  
 precision, 32  
 promptly reflected beam, 134  
 propagating uncertainties, 34  
 propagation formulas, 35  
 protected coating, 22  
 PSD, 168  
 pumping, 115
- q, 74  
 quadrature addition, 49  
 quantum light sources, 17  
 quarter-wave stack, 98  
 quartz-tungsten-halogen, 17
- random error, 32  
 rate equations, 122  
 ray, 49, 53  
 ray transfer matrix, 59
- Rayleigh range, 158  
 Rayleigh refractometer, 92  
 Rayleigh scattering, 89  
 reduced chi-square, 38  
 reflected beam, 134  
 reflection grating, 81  
 refraction, 49  
 ring laser gyroscope, 92  
 RMS, 34  
 rogue beam, 160  
 root-mean-square, 34
- safety habits, 15  
 Sagnac effect, 92  
 Sagnac interferometers, 92  
 scalar electric field, 2  
 scale calibration error, 33  
 shot noise, 19, 170, 183, 185  
 signal-to-noise ratio, 168  
 silver mirror, 23  
 single-slit diffraction, 3, 6  
 single-slit minima, 5  
 small focus, 77  
 Snell's law, 49, 50  
 SNR, 168  
 Sodium D lines, 89  
 spatial coherence, 9  
 spatial mode, 142, 143  
 spectrometer calibration, 87  
 spectrum, 19  
 speed of light, 1  
 spherical aberration, 21, 52, 77  
 spin-orbit coupling, 89  
 stability criterion, 140  
 stable cavity, 140  
 standing electromagnetic wave, 133  
 standing wave, 133, 139  
 surface brightness, 125  
 symmetric cavity, 139  
 systematic error, 32, 33
- telescope, 58  
 TEM<sub>mn</sub>, 74, 157  
 temporal coherence, 9  
 thermal detector, 27  
 thermal light sources, 17  
 thermopile, 28  
 thin film stack, 98  
 thin lens equation, 53  
 thin lens propagation, 61  
 three-level laser, 123  
 three-level model, 120  
 time domain, 168  
 transmission grating, 81  
 transmittance, 14  
 transverse coordinates, 157

- 
- transverse waves, 152
  - two-level model, 116
  - Twyman-Green interferometer, 92
  
  - uncertainty, 32
  - uncertainty propagation, 34
  
  - vertical polarizer, 159
  
  - waist, 158
  - warning label, 14
  - wave equation, 1
  
  - wave function collapse, 166
  - wave number, 2
  - wavefront curvature, 157, 158
  - wavefront splitting, 91
  - waveplate, 25
  - window, 61
  
  - Young's double slit, 9
  
  - zero-order waveplate, 25
  - zeroth order, 82