

Index

- absolute velocity vector, 18, 115
 adiabatic flow process, 26, 28, 32, 33, 36, 472–476
 aerothermodynamics
 assumptions of, 25–26
 inviscid flow field in, 26, 27
 limitations of, 25–26
 total properties of, 28, 29–36, 40–41
 afterburners, 1, 4
 air intake, 4–5
 airfoil cascades
 aerodynamic loading and, 349–353, 362
 angles in, 119–120
 in axial-flow compressors, 415–417, 418–421
 in axial-flow turbines, 346–354, 362, 377–379
 cascade pitch of, 349, 352, 362
 C4 airfoils in, 419–420
 compressibility factors in, 21–23
 contouring of, 353
 definition of, 8, 15
 diffuser-like, 51
 geometry variables of, 349–351
 lift coefficient in, 421
 NACA airfoils and, 420–421
 nozzle-like, 51
 periodic boundaries of, 353, 377
 restaggering in, 377–379
 solidity ratio of, 366–369
 subsonic flow field and, 52
 viscosity factors in, 21–23
 wakes of, 415
 axial-flow compressors
 airfoil cascades in, 415–417, 418–421
 axial-flow turbines v., 412
 blade count of, 412–414
 bleed valves in, 429
 boundary layers in, 422–423, 423–427, 439
 centrifugal compressors v., 548
 C4 airfoils in, 419–420
 definition of, 412–413
 deviation angles in, 415–417, 421–422
 downstream effect in, 425–428
 efficiency of, 412
 high-solidity-ratio rotors in, 414
 incidence angles in, 421–422, 423, 425–427
 leading-edge thickness in, 418–421
 loss classification in, 415–417
 Mach number effect and, 423
 mean camber line in, 418–421
 multiple staging in, 413, 414, 428
 NACA airfoils in, 420–421
 normal stage in, 417–418
 off-design characteristics of, 425, 426, 428
 pressure gradients in, 412–414
 Reynolds number effect and, 422–423
 rotor-flow process in, 415–417
 stage definition of, 415–417
 stalling in, 421–422, 425–427
 start-up of, 428–429
 surge line in, 413, 425–427
 tip leakage in, 424, 425
 total relative properties of, 416–417, 440
 variable-geometry stators in, 429
 velocity triangles in, 417–418
 axial-flow turbines
 aerodynamic loading in, 351–354, 362
 airfoil cascades in, 346–354, 362, 377–379
 annulus height in, 320, 327, 339, 356, 399
 aspect ratio in, 319, 340, 356, 357, 370
 axial-flow compressors v., 412, 413, 414
 blade count of, 412–414
 blade reaction in, 346
 boundary layers in, 341, 345, 353, 365
 component adaptation in, 377–379
 cooling flow extraction in, 379–380, 382
 design of, 247
 deviation angles in, 344–346
 divergence angles in, 341, 398–399
 axial-flow turbines
 empirical correlation and, 358
 flow coefficient for, 320
 flow kinematics of, 333–334
 flow path construction in, 336–337, 334–339
 flow/airfoil interaction in, 119–120
 flow-analysis codes for, 351, 352–354, 376–378
 geometrical discontinuities
 influencing, 354, 355
 hot-to-cold dimension conversion in, 379
 implied stagger angle in, 366, 367
 incidence angles in, 344–346, 360–362, 364, 377–378
 leading-edge thickness in, 345, 350, 360–364, 372, 377–379
 leading-edge wedge angles in, 350, 375–376
 limitations of, 315–317
 Mach number verification in, 334–335
 mean-radius axial chords in, 327–328
 optimum blade count in, 366–369
 preliminary design of, 315–322, 325–328
 pressure gradients in, 57–60, 412–414
 pressure ratio for, 331–332
 property-invariance principle of, 129–134
 radial-inflow turbines v., 467
 requirements of, 253
 Reynolds number effect and, 358
 rotor choking in, 325–326
 shaft-work extraction in, 370
 single-stage, 317, 329

- specific speed and, 239–240, 325, 329–330, 322–330, 339
- “stacking” in, 348, 354, 369–370
- stage definition in, 314, 315
- stage reaction in, 122–124, 322, 324
- stagnation point in, 364
- stagnation streamlines in, 376–377
- stator verification in, 325–326
- stator/rotor gap in, 89–90, 269–270, 318–319, 327–328, 337–338, 339, 348
- suction-side diffusion in, 362–364
- supersonic stator option for, 370–371, 372
- three-stage, 331–334, 343
- tip leakage in, 356–358
- tip-radius axial-velocity component of, 387
- trailing-edge thickness in, 350, 365–366
- two-stage, 330–331
- unbladed passages of, 61–62
- uncovered turning angle in, 350
- work coefficient for, 321, 321–324
- work split in, 318, 331
- Zweifel’s loading criterion and, 366–368, 323
- axial-momentum equations, 112, 113
- backface clearance, 495, 496
- Bernoulli’s equation
- applicability of, 52–54
 - Mach number in, 54, 54–55
- bleed valves, 429
- boundary layers
- in axial-flow compressors, 422–423, 424–428
 - in axial-flow turbines, 341, 345, 353, 365
 - in centrifugal compressors, 550, 559
 - displacement of, 10–12, 75–77, 98, 154, 155, 341, 345, 365, 422–423
 - laminar, 98–99, 99–103
 - mixing region of, 26, 27
 - momentum thickness of, 97, 99–103, 155
 - in radial-inflow turbines, 488–490, 522
 - turbulent, 99
- Brayton thermodynamic cycle, 6–7
- Buckingham’s Theorem
- compressible flows and, 233–234
 - incompressible flows and, 232
- bulk-flow analysis, 25
- cascade pitch, 349, 353
- centrifugal compressors
- axial-flow compressors v., 548
 - blading options of, 554–556, 558
 - boundary layers in, 550, 559
 - continuity equation and, 583
 - Coriolis acceleration component in, 563–565, 592–596
 - definition of, 413, 548, 549, 550
 - deviation angles in, 559
 - diffusion in, 550, 554
 - energy transfer in, 558
 - fluid-particle motion in, 566–579
 - free-vortex flow in, 550
 - impellers in, 449, 550, 552, 553–554, 555, 558, 559–565, 573
 - impeller/stator interaction in, 573
 - inlet ducts in, 551, 552–553
 - kinetic energy loss in, 566–570
 - leading-edge thickness in, 562–563
 - mean camber line in, 562–563
 - multiple staging in, 20–21, 72, 413, 549
 - off-design performance of, 548
 - pressure gradients in, 550
 - propulsion applications of, 548, 549
 - radial gap in, 550
 - return ducts in, 548
 - Reynolds number and, 571–572
 - size of, 548
 - slip phenomenon in, 564, 565, 565–570, 593–595, 596
 - specific speed and, 587
 - stability in, 556, 567
 - stage reaction in, 558
 - surge mode in, 557
 - thermodynamics in, 553–554
 - tip leakage in, 559–562, 571–572
 - total-pressure loss coefficient of, 552–553
 - total-to-static efficiency of, 571
 - total-to-total efficiency of, 566
 - turbine rotors and, 554
 - turbine-compressor matching and, 548
 - vaned diffusers in, 551
 - vaneless diffusers in, 550, 579
 - velocity triangles in, 550, 551
 - volute in, 550, 551, 566–570
 - vorticity in, 566–570
- C4 airfoils
- in axial-flow compressors, 419–420
 - base profiles of, 419
 - nomenclature of, 419, 420
- choking
- compressor, 235–237
 - rotor, 117–119, 156, 325–326, 483, 508
 - turbine, 236–237
 - turbine-compressor matching and, 616–618
- collectors. *See* volutes
- compressibility
- in airfoil cascades, 21–23
 - Buckingham’s Theorem and, 232
 - characteristics of, 47–49
 - in flow structure, 21–23
 - Mach number gauging, 40, 47–49, 478–479
 - of working medium, 39
- compressors. *See also* axial-flow compressors; centrifugal compressors; compressibility; turbine-compressor matching
- choking in, 235–237
 - definition of, 9–14
 - maps of, 234–237
 - mixed-flow, 14
 - polytropic efficiency in, 298–300
- continuity equation
- centrifugal compressors and, 579
 - cross-flow area and, 47, 50
 - isentropic flow and, 47–49
 - total properties and, 45–47
 - turbomachinery-adapted form of, 47
- cooling, of rotors
- external, 533–534, 535
 - internal, 534–535
- coordinate system, for turbomachinery, 15
- Coriolis acceleration component, 527–532, 563–564, 593–596
- critical-velocity ratio. *See* Mach number, critical
- design point choice of, 62–64
- as operating mode, 62–64
 - in trans-oceanic turbofan engines, 64
 - in turboprop engines, 63–64

656 Index

- deviation angles
 in axial-flow compressors, 415–417, 421–422, 439
 in axial-flow turbines, 344–346
 in centrifugal compressors, 559
 definition of, 120, 134–135
- diffusion
 in centrifugal compressors, 550, 551, 553
 exhaust diffusers and, 5, 94–97, 109, 110
 in radial-inflow turbines, 477, 486–487
 suction-side, 362–364
- double-loop process
 inner loop of, 624–625
 outer loop of, 623–624
 in turbine-compressor matching, 622–625, 639, 642
- dump effect, 479
- dynamic enthalpy, 120–121, 469
- energy transfer components, 120–121
 energy-conservation law, 30
 engines. *See* gas turbine engines;
 turbofan engines; turbojet engines;
 turboprop engines
- enthalpy. *See* dynamic enthalpy; static
 enthalpy entropy-based efficiency
 definition of, 72–73
 loss coefficient for, 34–36
- equation of state, 28, 40
- Eulers theory
 equation of motion in, 48
 turbine equation in, 114, 467–469, 476
 velocity triangles in, 16–20
- exhaust diffusers annular, 94, 109, 110
 definition of, 5
 design of, 96, 97
 total-to-static efficiency and, 96–97
- Fanno flow process
 critical Mach number in, 79–80
 definition of, 75–78
 relationships in, 78–80
 system efficiency and, 396–398, 442
- flow angles, 18, 119–120, 468–469
- flow path construction, 336–337,
 339–343, 344, 412, 413
- flow-analysis codes, 351–352, 353, 354,
 376–377, 488, 489
- frame of reference rotating, 115–119
 stationary, 114, 115–119
- free turbine, 4, 5–6
- free-vortex blade design, 275–276
- free-vortex flow condition, 275–276,
 476, 485–486, 473, 500
- front rotor loading, 20
- Futral’s tangential kinetic-energy-
 destruction model, 492–493
- gas generators, 2, 4–5
- gas turbine engines
 advantages of, 1–2
 applications of, 3
- ideal-gas simplification, 29, 30–34
- impellers
 acceleration components of, 563–565
 blading options of, 554, 555, 558
 in centrifugal compressors, 550, 551,
 552, 553–554, 559–565, 573
 definition of, 550
 dynamic heads of, 558, 562–563
 inlet system of, 552, 553
 slip phenomenon influencing,
 512–513, 515, 516, 565–570
 stability of, 557, 558
 static heads of, 558, 559–563
 stator interaction with, 573
- incidence angles
 in axial-flow compressors, 421–422,
 423, 424–428
 in axial-flow turbines, 344–346,
 360–362, 364, 377–379
 in centrifugal compressors, 552
 definition of, 120, 134–137, 281, 477
 in radial-inflow turbines, 477, 488,
 491–493
- invariant thermophysical properties
 critical Mach number and, 131–133
 importance of, 131–133
 property-invariance principle and,
 132–134
 rothalpy as, 130, 132
 total enthalpy as, 129
 total relative enthalpy as, 129–130
 total relative properties of, 129–130
- inviscid flow field, 26, 27
- isentropic efficiency. *See* total-to-total
 efficiency
- kinetic-energy loss coefficient, 71, 99–100,
 104, 489–492, 488–490, 493, 498
- leading-edge thickness
 in axial-flow compressors,
 419–420
 in axial-flow turbines, 345, 350,
 360–364, 375, 377–379
 circular v. elliptical, 360–361
 incidence loss influenced by, 362
 wedge angles and, 350, 375
- loss coefficients. *See* kinetic-energy loss
 coefficient; total-pressure loss
 coefficient
- Mach number
 axial-flow compressors affected by,
 423
 in axial-flow turbines, 334–335
 in Bernoulli’s equation, 52–54,
 54–56
 compressibility gauged by, 40, 47–48,
 478–479
 critical Mach number v., 80
 total properties and, 41
- Mach number, critical
 definition of, 41–42
 in Fanno flow process, 78–80
 Mach number v., 80
 in radial-inflow turbines, 470–472,
 478–479, 437–438, 469
 relative, 74, 86–87, 132–134
 sonic state and, 50
 “stage,” 478–479
 stator-exit, 54–57
 total properties and, 43–44, 46
- mean-radius line. *See* pitch line
 meridional flow paths, definition of,
 9–10, 10–12, 412, 413
 mixed-flow turbomachines, 14, 112
- momentum equations
 axial, 112, 113
 radial, 113–114
 tangential, 114–115
- multiple spools, 5–6, 429
- multiple staging
 in axial-flow compressors, 412, 413,
 428
 in centrifugal compressors, 20–21,
 412, 413, 428, 471
 in compressors, 20–21, 72, 412, 413,
 428, 471
 in radial-inflow turbines, 532
 thermodynamic representation of, 34

- NACA airfoils
in axial-flow compressors, 420–421
nomenclature of, 420–421
- pitch line
definition of, 44–45
- polytropic efficiency, 298–300
- pressure gradients
in axial-flow compressors, 412–414
in axial-flow turbomachines, 57–60, 412–414
in centrifugal compressors, 550
definition of, 12–14, 20, 52, 53
in radial-inflow turbomachines, 60–62, 486–488, 490–491
- radial equilibrium equation derivation
of, 269–274
free-vortex flow in, 275–276
special forms of, 274–275
- radial-inflow turbines, 3
aerodynamic loading in, 486–488
axial-flow turbines v., 467
backface clearance in, 495–496
bladed components of, 61, 493–494
boundary layers in, 486–488, 488, 489
closed-form loss correlations in, 488–490, 497–501
conventional stage in, 468, 472–473, 474–477, 478
Coriolis radial-acceleration component in, 527–532
critical Mach number in, 470–472, 472–479, 506, 469
diffusion in, 486, 487
downstream ducts in, 495
dump effect in, 479
efficiency of, 478–479
external cooling in, 533–534
flow coefficient for, 470
flow process in, 468–469, 472–473, 476, 485–486, 487–488, 490–492
Futral’s tangential kinetic-energy-destruction model and, 492–493
heat-transfer problem in, 472–473
incidence angles in, 476–477, 488, 492–493
internal cooling in, 534–535
irreversibilities in, 472, 548
kinetic-energy loss coefficient for, 490–492, 493–494, 500
mean camber line in, 493–494
multiple staging in, 532–533
pressure gradients in, 60–62, 486–487, 490
radial gaps in, 61, 476, 490, 490–492
radial stators in, 476–477
Reynolds number effect and, 470, 478–479, 429
rotor admission segment in, 492–493
rotor choking in, 483
rotor design in, 487–488
scallop radius in, 495, 496
shaft-work production in, 467–469
size of, 467, 468
specific speed and, 239–240, 484
stage geometrical configurations in, 472–473, 474, 475–477, 478
stage reaction of, 469
stage scroll in, 473–475, 485–487
stage-design approach to, 485–495
stator/rotor gap in, 106, 107, 490–492
tip leakage in, 467
total relative properties of, 470–472
total-pressure loss coefficient for, 490–492, 495
vaned stators in, 473, 486–487, 488, 490, 497–501
vaneless nozzle in, 490–492
velocity triangles in, 468, 476–477, 478
work coefficient for, 401, 484
radial-momentum equations, 113–114
relative critical velocity, 42
relative flow, 73–75
relative velocity vector, 18, 115
Reynolds number, 21
axial-flow compressors affected by, 422–423
axial-flow turbines affected by, 358
centrifugal compressors and, 571–572
radial-inflow turbines affected by, 470, 478–479, 498
rothalpy, 130, 132
scallop radius, 495–496
similitude principle
dynamic similarity in, 231–232
geometrical similarity in, 231, 234–237
slip phenomenon
in centrifugal compressors, 564, 565, 566–570, 592–593, 596
impellers influenced by, 564, 565–570, 592–593, 596
slip factor in, 565–566
small-stage efficiency. *See* polytropic efficiency
sonic speed
definition of, 39
in ideal gases, 40
sonic state and, 50
specific speed approximations of, 245–246
in axial-flow turbomachines, 239–240, 325, 328–329, 330–331, 339
centrifugal compressors and, 589
compressor stages as function of, 243
definition of, 239–240
design role of, 243–245
pump performance as function of, 242
in radial-inflow turbines, 239–240, 485
turbine stages as function of, 244
specific-heat ratio, 29, 33, 78–80
“stacking,” in axial-flow turbines, 348, 353, 369–370
static enthalpy, 29, 120–121
static-pressure recovery coefficient, 94, 95
stator-domain velocity, 23
subsonic flow field, 41–42, 49, 52, 133–134
supersonic flow field, 41–42, 49–50, 133–134
tangential-momentum equations, 114–115
tip leakage
in axial-flow compressors, 424, 425
in axial-flow turbines, 356–358
casing recess preventing, 357
in centrifugal compressors, 559–562, 571–572
direct, 356–357, 424, 425, 559–560, 571–572
face seals preventing, 560–562
indirect, 357–358, 424, 425, 571–572
labyrinth seals preventing, 560–561
in radial-inflow turbines, 467
shrouding preventing, 358, 359, 560–561
wear-ring seals preventing, 561

658 Index

- total enthalpy, 129
- total relative enthalpy, 129–130, 132–134
- total-pressure loss coefficient, 71–72, 552–554, 490–492, 494, 495
- total-to-static efficiency, 70–71, 97, 571
- total-to-total efficiency, 68–70, 301, 303, 304, 566
- turbine-compressor matching
 - centrifugal compressors and, 548
 - choking line in, 616–618
 - combustor chart availability in, 615
 - double-loop process in, 622–624, 640–643
 - objective of, 609–612, 612–616
 - post processing work in, 625, 644
 - problem category 1 of, 612–616
 - problem category 2 of, 616–618
 - pumping characteristics and, 609–612
 - rules of, 609–612
 - specific fuel consumption in, 620
 - specific thrust in, 618–625
 - state “C” determination in, 609–612, 612–616, 619
 - state “T” determination in, 609–612, 615
 - in turbojet engines, 609–612
- turbines. *See also* axial-flow turbines; radial-inflow turbines; turbine-compressor matching
 - choking in, 237–239
 - definition of, 9–10, 11, 314
 - Eulers theory and, 114, 467–469, 476
 - maps of, 234–237
 - polytropic efficiency in, 300, 301
 - steam, 237–239, 314
- turbocharger, 4–6
- turbofan engines, 3, 7, 64, 548, 549
- turbojet engines, 609–612
- turboprop engines, 2, 4–5, 8, 63–64, 548, 549
- turboshaft system, 2, 4–5
- variable-geometry turbomachines airfoil
 - cascades and, 349–351
 - definition of, 64–68
 - stators in, 429
 - types of, 65, 66, 67, 68
- velocity triangles
 - absolute velocity vector in, 18, 115
 - in axial-flow compressors, 417–418
 - in centrifugal compressors, 549, 550
 - definition of, 15, 16–20
 - in Eulers theory, 16–20
 - exit/inlet, 149, 151, 154, 156, 163, 467–469, 477, 478
 - in radial-inflow turbines, 467–469, 468, 477, 478
 - relative velocity vector in, 18, 115
 - stationary cascade in, 549
- viscosity factors, 21–23
- volute (collectors), 550, 551, 566–571
- Zweifel’s loading criterion, 366–369, 389