

Index

- Aquifer
 - boundary
 - impermeable, 490
 - image recharging well, 490
 - non-radial flow, 490
 - permeable, 490
 - image pumping well, 490
 - Bouwer–Rice method, 502
 - confined, 439
 - influence radius, 462
 - piezometric surface, 441
 - steady radial flow, 462
 - Theis solution, 470
 - unsteady radial flow, 470
 - confining bed
 - aquiclude, 439
 - aquifuge, 439
 - aquitard, 439
 - flow
 - Darcy velocity, 447
 - Darcy's law, 447
 - deflection, 454
 - governing equation, 448
 - pore velocity, 447
 - steady state, 462
 - fully penetrating well, 462
 - geologic formation
 - saturated, 439
 - groundwater level, 441
 - homogenous, 445
 - isotropic, 445
 - layered, 445
 - multiple wells, 486
 - superposition theory, 486
 - partially penetrating well, 499
 - property
 - saturated hydraulic conductivity, 444
 - water holding capacity, 441
 - water movement easiness, 443
 - water withdrawing capacity, 441
 - pumping test, 501
 - pumping well, 462
 - drawdown, 462
 - recharging well, 462
 - semiconfined, 439
 - De Glee formula, 479
 - Hantush–Jacob solution, 481
 - steady radial flow, 479
 - slug test, 501
 - falling head, 501
 - rising head, 501
 - unconfined, 439
 - boundary rivers, 457
 - influence radius, 465
 - Neuman solution, 473
 - steady radial flow, 465
 - unsteady radial flow, 473
 - water table, 441
 - water budget, 437
- Basic dimensions
 - length, 41
 - mass, 41
 - time, 41
- Bridge
 - abutments, 387
 - low chord, 387
 - opening
 - flows, 387
 - piers, 387
 - under crossing, 387
 - water surface surcharge, 389
 - Yarnell equation, 389
- Conservation
 - energy, 21
 - momentum equation, 30
 - linear, 31
- Conservation: mass, 20
- Culvert
 - analysis
 - inlet-control, 370
 - outlet-control, 378
 - components, 367
 - barrels, 368
 - inlets, 369
 - flow condition
 - inlet-control, 369
 - outlet-control, 370
 - headwater depth, 367
 - maximum, 383
 - invert, 367

- inlet, 367
- outlet, 367
- tail water depth, 367
- under crossing, 367
- Dam
 - spillway
 - ogee, 421
 - shaft, 421
 - siphon, 421
 - types, 421
 - stilling basin, 424
 - type II, 425
 - type III, 425
 - type IV, 427
- Depth
 - alternate, 36
 - critical, 36
 - constant E, 38
 - constant Q, 36
 - rectangular channel, 36, 38
 - water, 36
- Design discharge
 - Rational Equation, 147
 - runoff coefficient, 147
 - time of concentration, 147
 - SCS peak method, 150
 - depressions, 150
 - unit peak, 150
- Energy
 - kinetic, 18
 - potential, 18
 - pressure, 18
 - specific, 35
 - total, 18
- Energy head
 - hydraulic, 239
 - total, 239
 - velocity, 239
- Energy loss
 - friction, 23
 - minor, 23
 - total, 23
- Flood
 - frequency, 153
 - magnitude, 153
 - return period, 153
 - skew coefficient, 155
- Flow
 - historical record, 143
 - hydrograph, 159
 - Modified Rational method, 168
 - SCS TR-55 method, 169
 - modeling, 171
 - peak discharge, 143
 - unit hydrograph, 159
 - S-curve, 164
 - SCS UH, 160, 161
 - Snyder UH, 160, 161
 - time base, 159
- Flow control device
 - broad-crested weir, 274
 - V-notch, 273
- Flow regime
 - critical, 36
 - Froude number, 40
 - gradually varied, 23
 - laminar, 34
 - nonuniform, 34
 - rapidly varied, 23
 - Reynolds number, 34
 - steady, 34
 - subcritical, 36
 - supercritical, 36
 - turbulent, 34
 - uniform, 34
 - unsteady, 34
- Force
 - acting location, 14
 - horizontal component, 14
 - hydrostatic, 14
 - resultant, 14
 - vertical component, 14
- Friction loss
 - Darcy–Weisbach equation, 23, 25
 - Hazen–Williams formula, 23, 28
 - Manning formula, 23, 26
- Head
 - potential, 18
 - pressure, 18
 - total energy, 18
 - velocity, 18
- Open channel
 - supercritical contraction, 267
 - supercritical expansion, 267
- Open channel design
 - concrete-lined channels, 280
 - most efficient cross section, 286
 - earth channels, 289
 - grass-lined channels, 295
 - riprap-lined channels, 299
- Open channel flow
 - bed slope
 - critical slope, 247
 - mild slope, 247
 - steep slope, 247
 - gradually varied flow, 245
 - hydraulic jump

614 Index

- conjugate depths, 257, 258
 - length, 257
- Manning formula, 242
- normal depth, 242
- rapidly varied flow, 257
 - choking, 261
 - hydraulic jump, 257
- uniform flow, 242
- water surface profile
 - classification, 247
 - computations, 251
 - governing equation, 250
 - multi-step method, 250
 - one-step method, 250
- Open flow measurement
 - long-throated flume, 275
 - Parshall flume, 275
 - sharp-crested rectangular weir, 271
 - sharp-crested triangular weir, 273
 - ultrasonic meter, 276
- Pipe
 - discharge measurement
 - area–velocity flowmeters, 357
 - obstruction meters, 355
 - ultrasonic flowmeters, 356
 - friction factor
 - formula, 318
 - network, 329
 - orifice, 351
 - discharge coefficient, 351
 - pipeline, 320
 - pressurized, 308
 - Darcy–Weisbach equation, 309
 - H–W equation, 309
 - Hazen–Williams equation, 309
 - piezometric tube, 308
 - pitot tube, 308
 - rough, 311
 - smooth, 311
 - surface roughness, 311
 - velocity distribution, 312, 313
 - viscous sublayer, 311
 - shear stress, 312
 - shear velocity, 312
 - thickness, 312
- Power
 - efficiency, 181
- Precipitation, 72
 - areal, 72
 - arithmetic average, 72
 - isohyet, 72
 - Thiessen polygon, 72
 - EWD, 72
 - hail, 72
 - rain, 72
 - rain gauge, 72
 - sleet, 72
 - snow, 72
- Pressure
 - absolute, 11
 - atmospheric, 11
 - gauged, 11
 - hydrostatic, 12
 - relative, 11
- Pump
 - affinity laws, 196
 - cavitation, 208
 - cavitation number, 208
 - centrifugal, 184
 - axial-flow, 184
 - mixed-flow, 184
 - radial-flow, 184
 - characteristic parameters, 180
 - definition, 178
 - discharge coefficient, 192
 - displacement, 185
 - diaphragm, 186
 - piston, 186
 - gross power loss, 182
 - head coefficient, 191
 - impeller diameter, 204
 - internal power loss, 182
 - NPSH, 208
 - operation point, 206
 - output power, 181
 - parallel pumps, 210
 - performance curves, 187
 - power coefficient, 192
 - power transferred, 182
 - series pumps, 212
 - specific speed, 203
 - system curve, 206
 - water system power loss, 182
- Rainfall
 - amount, 135
 - areal average, 136
 - excess, 56
 - hyetograph, 56
 - infiltration, 56
 - initial abstraction, 56
 - intensity, 56, 135
 - interception, 56
 - PMP, 142
 - storage, 56
- Roughness
 - Darcy friction factor, 26
 - Hazen–Williams coefficient, 28
 - Manning’s n , 26
- Runoff
 - channel flow, 59

- direct, 56
 - hydrograph, 56
 - time base, 56
 - time to peak, 57
 - overland, 59
 - shallow concentrated flow, 59
 - sheet flow, 59
 - volume, 56
- Similitude
 - Froude number, 42
 - model, 42
 - prototype, 42
 - Reynolds number, 42
- Soil property, 78
 - moisture, 78
 - saturated hydraulic conductivity, 78
- Storm
 - design storm, 122
 - historical event, 122
 - hypothetical event, 135
 - IDF, 124
 - NRCS distribution, 135
 - PMS, 142
 - Steel Formula, 147
 - synthetic storm, 135
 - triangular distribution, 135
- Stormwater
 - drain inlet, 406
 - bypass fraction, 415
 - combination, 420
 - curb opening, 419
 - efficiency, 414
 - interception capacity, 414
 - slotted, 421
 - types, 414
 - gutter, 406
 - composite cross section, 407
 - flows, 407
 - simple cross section, 407
 - manhole, 517
 - chamber depth, 517
 - riser, 395
 - sewer, 406
- Streamflow, 102
 - routing
 - Kinematic Wave method, 105
 - Modified Puls method, 102
 - Muskingum–Cunge method, 111
- Sustainability
 - constraints, 68
 - decision variables, 68
 - eco-environmental, 68
 - economic, 68
 - feasible region, 68
 - objective function, 68
 - optimal scenario, 68
 - socio-political, 68
- Topography
 - contour, 51
 - V-shaped, 51
 - DEM, 52
 - LiDAR, 53
 - map, 50
- Transient flow, 524
 - open channel
 - celerity, 553
 - governing equations, 552
 - pressurized pipe, 526
 - governing equations, 527
 - wave velocity, 527
- Saint–Venant equations, 524
 - water table
 - governing equation, 575
 - Dupuit–Forchheimer assumption, 575
 - stability condition, 577
- Turbine
 - affinity laws, 231
 - Francis, 215
 - cavitation condition, 225
 - cavitation number, 225
 - efficiency, 224
 - harvested power, 224
 - generator, 227
 - impulse, 214
 - Kaplan, 215
 - Pelton, 214
 - efficiency, 218
 - harvested power, 218
 - maximum efficiency, 218
 - maximum power, 219
 - specific speed, 227
- Water balance, 63
 - baseflow, 63
 - evapotranspiration, 63
 - actual, 89
 - complementary relationship, 89
 - evaporation, 63
 - Penman–Monteith equation, 90
 - potential, 89
 - transpiration, 63
 - wet-environment, 89
- exflux, 63
- infiltration, 63
 - actual rate, 84
 - amount, 77
 - capacity, 77
 - G–A model, 79
 - Horton model, 78

616 Index

- Philip model, 78
- rate, 77
- influx, 63
- percolation, 64
- runoff
 - CN, 95
 - curve number, 95
 - MoCN model, 100
 - MoRE model, 100
 - SCS-CN method, 94
- storage, 63
- Water property
 - density, 10
 - kinematic viscosity, 11
 - saturation vapor pressure, 11
 - specific weight, 10
 - temperature, 11
 - viscosity, 10
- Water subsystem
 - groundwater, 63
 - soil, 63
 - surface, 63
- Water use
 - consumption, 65
 - footprint, 65
 - blue water, 65
 - green water, 65
 - grey water, 65
 - LCA, 65
 - non-consumption, 65
 - supply and demand
 - WaSSI, 65
- Watershed
 - boundary, 50
 - delineation, 51
 - D8, 53
 - drainage area, 54
 - drainage density, 54
 - drainage network, 50
 - flow path, 54
 - HSGs, 56
 - length, 54
 - LULC, 55
 - slope, 54
 - slope length, 54
 - soils, 55
 - time of concentration, 57
 - FAA formula, 58
 - Kerby formula, 59
 - Kirpich formula, 58
 - SCS Lag equation, 58
 - TR55 method, 59
 - width, 54
- Watershed: lag time, 58