

Index

- π plane, 61, 106
- absolute derivative, 608, 633
- acoustic impedance, 150, 189
- actions, 560
- adiabat
 - ideal gas, 31, 576
 - metal, 575
 - rubber, 576
- adiabatic shear bands, *see also* shear bands
- advection, 14, 16, 301
- ballistic limit
 - fabric, 535
- Bernoulli equation, 334, 370
- bifurcation, 577–579
- bird strike, 4
- bolide, 441
- boundary conditions, 33
 - couple stress, 38
 - kinematic, 33
 - Saint-Venant's principle, 34, 578
 - traction, 33
- Boussinesq elastic point-load solution, 364
- Bridgman stress distribution, 75
- Burgers' equation, 39–41
- Cassini mission, 2, 235
- cavity expansion
 - cylindrical, 261–269, 278–280
 - elastic-plastic boundary condition, 260–261
- elastic-plastic extent α , 265
 - as target plastic extent, 407
 - expansion speed dependence, 284
- one dimension, 257–260, 278–280
 - spherical, 269–280
 - target resistance R_t , 353–356
- centerline momentum balance, 392
- Chelyabinsk meteor, 2
- commutative diagram, 564
- compatibility conditions (curvature), 647, 650
- composites
- fiber, 539
- conjugate stress–deformation rate, 514, 591
- connection ∇ , 606, 633
 - Christoffel symbols Γ_{ij}^k , 506, 633, 638
 - Christoffel symbols (orthonormal) γ_{ij}^k , 506, 606, 619, 638
- conservation laws
 - angular momentum, 552, 604
 - energy, 17, 514, 604, 644
 - mass, 14, 509, 601, 643
 - momentum, 16, 513, 602, 643
- constitutive models, *see also* plasticity
 - theory, 69
 - anisotropic elastic, 517, 525
 - anisotropic yield/failure surface, 552
 - damage, 84
 - dashpot, 165
 - Drucker–Prager, 62, 116
 - finite strain elasticity
 - Blatz–Ko, 572–573
 - isotropic material, 570–571
 - Mooney–Rivlin, 573–575
 - Mooney–Rivlin balloon inflation, 589
 - neo-Hookean, 573
 - nonuniqueness of solutions, 576–579, 589
 - Poisson's ratio ν , 587
 - Poynting effect, 587
- Gurson, 113
- Hall–Petch, 82
- Hooke's law, 45
- hyperelastic, 545, 571, 574
- hypoelastic, 585
- incremental, 585
- inviscid fluid, 333
- Johnson–Cook, 80
- Kelvin–Voigt, 165
- Maxwell, 165
- Mechanical Threshold Stress (MTS), 82
- Mohr–Coulomb, 62, 116
- small strain elasticity, 45
- spring, 35, 165, 210, 213, 246, 247, 525
- Steinberg–Guinan–Lund, 83

- superfluid (zero viscosity), 118
- viscoelastic, 165, 207
- viscoplastic, 52, 105, 207
- Wilkins–Streit–Reaugh, 112
- Zerilli–Armstrong, 82
- corotational rate, 579–586
 - B* diagonalization (q), 596
 - commutative diagram, 581
 - Cotter–Rivlin (*CR*), 580
 - definition (objective, frame indifferent), 584
 - for Piola–Kirchhoff *S*, 584
 - Green–Naghdi (*GN*), 569, 582
 - Jaumann (*J*), 303, 583, 597
 - Oldroyd (*O*), 582
 - Truesdell (*T*), 582
- covariant derivative, 633, 639, 640
- crater
 - ejecta, 378–379
 - radius, 315, 372–378
- cross product \times , 609, 650
- damage, 84, *see also* failure
 - saturation, 388
 - scale effects, 95
 - stress state, 84–95
- Deep Impact mission, 389
- deflagration, 242
- deformation gradient *F*, 508, 553–555, 564–565, 611–617, 645
- average rotation θ_a , 557
- average rotation matrix *R*, 557, 560, 564–565
 - explicit formula (2D), 557
- induced ellipse, 556
- invariant of one-sided rotation, 560
- stretch, *see also* tensors
- time rate of change, 568
- detonation, 236
 - Chapman–Jouguet (CJ) point, 237
 - ideal gas, 239
 - Jones–Wilkins–Lee (JWL) equation of state, 240–241
 - von Neumann spike, 241
- Zeldovich, von Neumann, Döring (ZND) theory, 238
- diagnostics
 - digital image correlation, 9
 - PDV, 9
 - pressure gages, 9
 - strain gages, 9
 - VISAR, 9
 - X-rays, 9
- diamond anvil cell (DAC), 212
- differential forms, 642
 - Hodge star (*) operator, 642, 650
- differentiating an integral (generalization of Leibniz), 601
- divergence theorem, 600
- Earth interior (PREM), 249
- eigenvalue, 49
 - characteristic equation, 49
- Einstein summation convention, 13
- elastocaloric effect, 215
- energy
 - elastic strain, 67
 - plastic dissipation, 65
- entropy, 123, 125, 129–130, 170
 - ideal gas, 32
- equations of state, 29, 69, 208
 - $p-\alpha$, 228–231
 - cold compression curve, 211, 215
 - ideal gas, 29–33, 239, 245–246
 - Jones–Wilkins–Lee (JWL), 240–241
 - Mie–Grüneisen, 209–212
 - Murnaghan, 226, 251
 - snowplow, 253–254
 - thermal mechanical model, 210–211, 246
- explosives, *see also* detonation
- failure, 78, 84
 - Al 2024-T351 model, 94, 386
 - Johnson–Cook, 86–87
 - maximum tensile stress, 320
 - size-scale effect, 386
 - strain rate, 386
 - strain to failure, 84, 95
 - strength vs. ductility, 84, 461–471
 - stress state, 84–95
 - tensile principal stress, 88
 - Tuler–Butcher, 164
 - work to failure, 84, 95, 470
- fibers, 507
 - carbon, 508, 542
 - composites, 542
 - E-glass, 508, 542
 - epoxy matrix, 542
 - graphene, 550
 - Kevlar, 507
 - Kevlar 129, 508, 542, 548
 - Kevlar 29, 508, 541, 542
 - Kevlar 49, 508, 542
 - Kevlar KM2, 508, 536, 542
 - nylon, 508, 542
 - PBO (Zylon), 508, 542, 543, 550
 - polyester matrix, 542
 - spider silk, 550
 - ultra-high-molecular-weight polyethylene, 507
 - Dyneema, 507
 - Spectra, 507, 508, 542
- fracture, 84, 86
 - compact tension specimen, 89, 163
 - fracture mechanics, 96, 381, 474
- fragmentation, 471–476
- Grady–Kipp model, 473–475

- Mott wave, 476
- generalized continua, 14, 34–38, 95, 598
 - Cosserat elasticity, 598
 - couple stress, 14, 37, 598
 - higher order derivatives, 35
 - microrotation, 598
 - nonlocal, 36, 42
 - wryness tensor κ , 598
- Grüneisen parameter Γ , 208, 211, 252
- gradient elasticity, *see also* generalized continua
- hardness
 - Brinell (BHN), 290
 - Rockwell C (Rc), 291
- heat
 - conduction, 65
 - Gough–Joule thermoelastic effect, 576
 - kernel, 65
 - mechanical model, 211, 246
 - temperature, 213–218
 - thermal expansion coefficient α , 68, 208
- Hugoniot, 121
 - elastic precursors, 191, 221–224, 226
 - impedance matching, 256
 - isentrope, 132
 - linear $U_s - u_p$, 199
 - path, 122, 194–196
 - phase changes, 232–236, 248
 - Rayleigh line, 122, 125
 - single shock, 123, 124, 128
 - entropy criterion, 130
 - sound speed criterion, 124
- stress-strain
 - ρ_0 -convex, 127
 - concave up, 127
 - superlinear, 128
- three wave, 248
- two wave, 190–194
 - very high pressure, 204
- Hugoniot elastic limit (HEL), 191, 196, 248
 - elastic precursor decay, 196
- Hugoniot jump conditions (Eulerian), 20, 22, 25, 119–133, 197
 - cylindrical, 29
 - differential equation form, 212
 - differential jump, 27, 123
 - double shock, 25
 - energy, 22, 24
 - enthalpy, 39
 - entropy, 27
 - ideal gas, 31
 - mass, 20, 23
 - momentum, 21, 24
 - multi-axis, 38
 - shear, 38, 110
 - single rise, 25
 - spherical, 29
- Hugoniot jump conditions (Lagrangian), 515
 - energy, 515
 - entropy, 515
 - mass, 514
 - momentum, 513, 514
- hydrostat, 58
- hypersonic flight, 441
- impact
 - Apollo spacecraft, 172
 - Deep Impact, 389
 - flyer plate, 190–194, 204–205, 248
 - graphical solution, 251
 - hypervelocity, 329
 - one-dimensional, 149–156
 - rigid wall, 143–149
 - Taylor anvil, 175–183, 243, 366
- indeterminate, 574
- indicial notation, 599
- invariant
 - original configuration, 569
- invariants, *see also* stress tensors, 50, 106
- isentrope, 132, 213–218
- isotropic, 50
- launchers
 - electrostatic, 8
 - explosively formed penetrator, 2
 - gas gun, 4
 - powder gun, 4
 - rail gun, 7
 - shaped charge, 2
 - two-stage light gas gun, 6
 - Z machine, 8
- Lie derivative, 646
- material derivative, 15, 17
- materials
 - 1045 steel, 76
 - 304 stainless steel, 200, 248
 - 4340 steel, 104, 168, 293, 304, 319
 - Al 2024, 88–94, 248, 252
 - Al 5083, 494, 504
 - Al 6061, 70–72, 80, 87, 89, 161, 168, 183, 200, 217, 248, 293, 491, 494, 504
 - Al 6082, 494
 - Al 7075, 70–72, 80, 87, 494
 - aluminum, 207, 232, 345, 359, 390
 - AP core steel, 70, 81, 87
 - beryllium, 207
 - bismuth, 245
 - copper, 207, 234, 243, 248, 359
 - copper gilding metal, 70, 81, 87
 - deuterium, 41, 220
 - fiber, *see also* fibers
 - gold, 359
 - helium-3, 118
 - hydrogen, 220

- ice, 235
- iron, 207, 234
- lead, 248, 346
- magnesium AZ31B, 248, 504
- molybdenum, 248
- nickel, 248
- OFHC copper, 168
- platinum, 79
- porous iron, 225
- quartz (fused), 134
- rolled homogeneous armor (RHA), 96, 295, 504
- S-7 steel, 340, 368
- steel, 293, 345, 359, 366, 454, 461, 471
- tantalum, 248
- Ti-6Al-4V, 168, 368
- titanium, 235, 248
- tungsten, 248, 295, 298, 303, 319, 332, 340, 345, 359, 366, 454, 461, 468
- uranium, 207, 468
- uranium dioxide, 233
- Zelux, 436
- mesoscale modeling, 36
- meteorites, 441
- missile defense, 2, 10
- moduli
 - bulk K , 32, 46, 47, 247
 - ideal gas, 32
 - pressure dependence, 283
- Lamé's λ, μ , 45, 47
- Poisson's ratio ν , 46, 47, 587
- shear G, μ , 45, 47
- two suffice for isotropic elasticity, 587
- Young's E , 46, 47
- Mohr's circles, 60
- momentum enhancement, 384
- moving frames (Cartan) ω_j^k , 506, 617
- Navier–Stokes equation, 165
- numerical methods
 - arbitrary Lagrangian–Eulerian (ALE), 602
 - artificial viscosity, 196, 303
 - cavity expansion, 285
 - corotational stress rate
 - Green–Naghdi, 585
 - Jaumann, 585
 - Courant–Fredrichs–Lewy (CFL) condition, 303
 - CTH, 302
 - Godunov, 145
 - hydrocode, 302
 - incremental stress update, 585
 - radial return, 101, 303
 - symbolic manipulator, 594, 649
 - Macsyma, 438
 - Mathematica, 544
 - REDUCE, 433, 594, 649
- orientation, 609
- penetration
 - L/D effect, 319–329, 484
 - complete, 443
 - direct cavity expansion approach, 497–502
 - efficiency, 367
 - eroding projectile, 297
 - eroding–noneroding transition, 502
 - erosion, 300
 - fluid target, 439–441
 - Newtonian impact theory, 440–441
 - Stoke's formula, 439–440
 - hydrodynamic, 302, 312
 - initial conditions, 409–411, 436
 - minimum speed, 366
 - nondeforming projectile, 293, 481
 - partial, 444
 - phases
 - secondary, 300, 331, 422–426, 436–437
 - shock, 300, 311
 - steady state, 300, 312
 - terminal, 300, 312
 - projectile deceleration, 401
 - projectile plastic extent s , 408
 - rigid projectile, 481
 - S curve, 296, 313
 - shatter gap, 295
 - target compression, 318
 - target of finite lateral extent, 479
 - target plastic extent α , 397
 - constant, 412
 - cylindrical cavity expansion, 407
 - dynamic plasticity, 429–433
 - target plastic strain, 315, 426–429
 - target resistance R_t , 336, 343, 357–363, 406
 - cavity expansion approach, 353–356
 - Walker–Anderson approach, 356, 406
 - target resistance S_t , 393, 403, 404
 - target resistance S_t^W , 448
 - target velocity field, 397, 484
 - back surface bulging, 450
 - shear flow field, 446
 - Tate model modifications, 348
 - Tate–Alekseevskii model, 336
 - Walker–Anderson model, 406
 - finite thickness target, 450
 - perforation
 - V_{50} , 444
 - back surface strain failure criterion, 453
 - ballistic limit velocity V_{bl} , 443, 480
 - behind armor debris, 471
 - causality, 445
 - complete penetration, 443
 - petalling, 443
 - plugging, 443

- residual velocity, 453
- fabric, 537
- zone of mixed results, 444
- permutation symbol ε_{ijk} , 50, 604
- phase changes, 232–236, 298
 - iron 13 GPa, 236, 249
- phase diagram, 249
- piezocaloric effect, 215
- plasticity theory
 - Bauschinger effect (unloading), 53, 84, 162
 - cyclic loading, 53
 - deformation plasticity, 105
 - dynamic plasticity, 100, 178–180, 429–433
 - equivalent plastic strain ε_p , 56
 - equivalent plastic strain rate $\dot{\varepsilon}_p$, 56
 - exact step, 97–100
 - finite strain, 55
 - flow rule, 48
 - associated (associative), 49
 - incremental plasticity, 47
 - maximum dissipation, 100
 - nonuniqueness of solutions, 72
 - overstress, 105
 - pressure independence, 49
 - rigid plasticity, 63–64, 402
 - scale effects, 95
 - strain increment partition, 48
 - Tresca (max shear), 59–62, 107, 108
 - associated flow rule, 61
 - uniaxial strain, 56–59
 - uniaxial stress, 53–56
 - viscoplasticity, 52, 105, 207
 - von Mises (J_2), 54, 59, 61–62
 - work hardening
 - isotropic, 52, 53
 - isotropic linear, 103
 - kinematic, 53, 104
 - yield 0.2% offset, 52
 - yield surface, 48, 52
- polar decomposition, 558, 593
- porosity, *see also* equations of state, 211, 224–252
- pressure, *see also* stress tensors
- projectile
 - armor piercing APM2, 70, 493–496, 504
 - fragment simulating projectile (FSP), 504–506
 - ogive caliber radius head (CRH), 487
- quadratic equation, 286
- Rankine–Hugoniot jump conditions, *see also* Hugoniot jump conditions
- rarefaction fan, 36, 133–143, 198, 224
 - elastic precursor, 223
- rarefaction shocks, 134
- Rayleigh line, *see also* Hugoniot
- reference frames
 - Eulerian (laboratory), 11
 - Lagrangian (initial), 11
- Reynolds number Re , 441
- Reynolds transport theorem, 601
- Riemann
 - integral, 134, 146
 - problem, 145
 - solver, 145
- sabot, 8
- Saint-Venant's principle, *see also* boundary conditions
- scale effects, 95, 323, 331
- shear
 - 2D, 560
 - 3D, 564
- shear bands, 78, 96, 384
- shock impedance, 150
- shock waves, 119–133
 - rise times, 164–167, 205–207
- Shoemaker–Levy 9, 2
- skew symmetric, 567
- sound speed, 123, 198, 221–224
- space shuttle, 4
- spall, 158–164, 390, 471
 - Grady fragment size model, 471
- specific, 18
- split-Hopkinson pressure bar (SHPB), 71, 184–189, 244
- strain, *see also* tensors
 - engineering (Lagrangian), 68, 71
 - engineering shear γ , 72
 - equivalence of large strain measures, 597
 - Eulerian, 69
 - localization (necking), 71
 - logarithmic (natural), 69, 247
 - tensorial shear ε_{12} , 72
 - true, 72
- stress
 - engineering, 71
 - true, 71
- stress tensors
 - Cauchy σ , 12, 13, 565–566
 - positive in compression $\tilde{\sigma}$, 13
 - symmetric, 604
 - Cauchy stress deviator s , 49
 - Cauchy tetrahedron, 13, 38
 - couple stress m , 14, 37, 42, 598
 - first Piola–Kirchhoff S , 14, 512, 565–566
 - elastic strain energy density potential, 516
 - invariants, 50
 - I_1, I_2, I_3 , 50
 - J_2, J_3 , 50, 51, 102
 - effective stress σ_{eff} , 54
 - Lode angle θ , 85, 92, 107
 - Lode parameter ζ , 85

- mean stress σ_{mean} , 85
- pressure p , 13
- principal stresses, 107
- stress triaxiality η , 71, 76, 85
- second Piola–Kirchhoff $S^{(2)}$, 565–566
- symmetry breaking, 79, 588
- symposia
 - American Physical Society Shock Compression of Condensed Matter, 10
 - Hypervelocity Impact Symposium, 10
 - International Symposium on Ballistics, 10
- temperature, *see also* heat
- tensors
 - contravariant (tangent basis), 565, 630
 - covariant (cotangent basis), 565, 631
 - covariant derivative, 633, 639, 640
 - curvature, 506, 646–647, 650
 - Eulerian strain E^* , 510, 566–567
 - Lagrangian (large) strain E , 44, 510, 516, 566–567, 645
 - left stretch V , 558, 560, 564–565
 - explicit formula (2D), 558
 - metric, 605, 629
 - rate of deformation D , 19, 69
 - right stretch U , 557, 560, 564–565
 - explicit formula (2D), 557
 - rotation rate Ω , 567
 - small strain ε , 44
 - positive in compression $\tilde{\varepsilon}$, 13
 - spin W , 19
- stress, *see also* stress tensors
- torsion, 646
- velocity gradient L , 18, 568
- wryness κ , 598
- tractions \vec{t} , 12
- original configuration \vec{T} , 565–566
- viscosity, 196, 206, 441
 - dynamic, 165
 - kinematic, 40
- waves
 - dispersion, 35
 - elastic, 117–119
 - $U_s - u_p$ intercept c_0 , 119, 199
 - bar c_E , 118
 - bulk c_K , 118
 - longitudinal c_L , 118
 - precursor decay, 196
 - shear c_s , 118
 - group velocity, 35
 - interface condition, 260
 - phase velocity, 35
 - Pochhammer–Chree oscillations, 189
 - reflection and transmission, 156–158, 177, 218–221
 - free surface, 145–146
- seismic
 - lunar, 173
 - p-wave, 118
 - s-wave, 118
- spherical elastic, 291
- yarn, 507
 - denier, 507
 - linear elastic, 515
 - strain energy, 515
 - tenacity (strength), 507
 - tex, 507
- transverse breaking speed, 520, 524
- transverse wave speed, 523
- yaw, 479