

Index

- ϵ -outage rate, 381
- 802.11
 - Frame structure, 70
- Acceleration estimation, 255
- Affinity propagation, 211
- Angle of arrival (AoA), 42, 67, 92
- Autocorrelation function (ACF), 231, 246
- Background subtraction, 180
- Baseband unit (BBU), 518
- Beamforming, 335, 453
- Biometric recognition, 170
- Bluetooth, 551
- Carrier frequency offset (CFO), 45, 152
- Carrier Sensing Multiple Access (CSMA), 575
- Channel estimation, 44, 69
- Channel frequency offset (CFO), 69
- Channel frequency response (CFR), 146
- Channel impulse response (CIR), 146, 556
- Channel reciprocity, 23, 121
- Channel state information (CSI), 144, 171
- Channel stationarity, 23, 121
- Cloud radio access network (C-RAN), 517
- Collision avoidance (CA), 575
- Common phase offsets (CPO), 45
- Distributed coordination function (DCF), 575
- Effective bandwidth, 9, 48
 - Frequency diversity, 11
 - Spatial diversity, 11
- Eigenvalue decomposition (EVD), 205
- Energy beamforming, 301
- Energy harvesting, 301, 335
- Frequency hopping, 77
- Gait cycle estimation, 255
- Heterogeneous network (HetNet), 518
- Human radio biometrics, 171
- Indoor tracking
 - Audio based, 92
 - Inertial measurement unit (IMU) based, 92
 - Moving direction, 102
 - Position correction, 102
 - Radio based, 92
 - Vision based, 92
- Internet of Things (IoT), 549
- K-means clustering, 211
- Linear regression, 253
- Location-specific fingerprint, 39, 297, 366
 - Channel frequency response (CFR), 39
 - Channel state information (CSI), 93
 - Received signal strength indicator (RSSI), 39, 93
- Massive MIMO, 423, 492
- Max-min SINR, 470
- Maximal ratio combining (MRC), 463
- MIMO, 44
- Minimum mean square error (MMSE), 465
- Multipath propagation, 2, 120
 - Channel impulse response (CIR), 275
 - Channel state information, 3
- MULTiple Signal Classification (MUSIC), 205
- Near-far effect, 395
- Nyquist sampling, 427
- OFDM, 44, 69
- Outage probability, 382
- Perron Frobenius Theorem, 401
- Phase correction, 47, 72, 180
- Positioning, 20
 - Angulation, 42
 - Fingerprinting, 43, 67, 93
 - Lateration, 41
 - Proximity, 20
 - Ranging, 67
 - Scene analysis, 20
 - Triangulation, 20, 41
- Power waveforming, 303

- Radio shot, 173
- Received signal strength indicator (RSSI), 67, 92, 144, 171
- Remote radio head (RRH), 518
- Round-trip time-of-flight (RTof), 41
- Sampling frequency offset (SFO), 45, 69, 152
- Simultaneous wireless information and power transfer (SWIPT), 474
- Spatial channel correlation, 387
- Spatial division multiple access (SDMA), 366
- Spectrum sharing, 488
- Speed estimation, 239
- Sum-rate maximization, 466
- Support vector machine (SVM), 211
- Symbol timing offset (STO), 45, 69, 152
- Time difference of arrival (TDoA), 41
- Time diversity, 156
- Time of arrival (ToA), 41, 67, 92
- Time of flight (ToF), 67, 144
- Time reversal, 4, 5, 22, 69, 121, 553
 - Channel probing phase, 146, 369, 460, 521, 557, 587
 - Channel reciprocity, 553
 - Channel stationarity, 553
 - Data transmission phase, 146, 370, 460, 557, 587
 - Downlink transmission phase, 522
 - Energy distribution, 93, 99
 - Resonating strength, 10, 25, 46, 71, 95, 122, 123, 146, 177, 205
 - Spatial focusing effect, 5, 554
 - Temporal focusing effect, 554
 - Uplink transmission phase, 524
- Time-Reversal Division Multiplexing, 296
- Time-reversal mirror (TRM), 394
- Time-reversal space, 121, 145, 174
- Virtual antenna, 243, 424
- Waveforming, 451
- Wireless event detection, 118
 - CSI, 118
 - Radar technique, 118
 - RSSI, 118
- Wireless power transfer (WPT), 474
- Wireless sensing, 118, 143, 171, 241
- Z-Wave, 551
- Zero forcing (ZF), 465
- ZigBee, 551