

Index

- *, 3
- β distribution
 - central, 148
 - noncentral, 148
- β function, 148
- χ^2 distribution
 - noncentral, 146
- χ^2 probability density function, 143
- H , 3
- $\exists$, 3
- $\forall$, 3
- $\in$, 3
- $\odot$, 203
- $\otimes$, 203
- i , 4
- 16-QAM, 78
- 16-quadrature-amplitude modulation, *see* 16-QAM
- 1 dB compression point, 53
- 8-PSK, 78
- 8-phase-shift keying, *see* 8-PSK
- access, 158
- acquisition, 25, 141, 143
 - frequency, 21
 - time, 21
- adaptive equalizer, 91, 103
- adaptive filter, 103, 107
- ADC, 14, 24, 59, 67, 68, 70, 71
- additive noise, 19
- AGC, 59
- Alexander Bell, 12
- allocation
 - spectral, 63
- aloha, 158
- AM, 69
- AM radio transmitter, 52
- amplifier, 14, 26, 51
 - class A, 55
 - class AB, 55
 - class B, 55
 - class D, 55
 - distortion, 55
 - filtering, 27
 - klystron, 52
 - linear, 84
 - low-noise, 15, 24, 51, 55, 68
 - magnetron, 52
 - memory, 27
 - nonlinear, 27
 - power, 51
 - solid state, 52
 - Taylor series representation, 27
 - Volterra series, 27
- amplifier chain, 55
- amplifier gain, 51
- amplitude modulation, 69
 - conventional double-sideband, 176
 - double-sideband, 178
 - double-sideband suppressed-carrier, 176, 177
 - single-sideband, 176, 179
 - vestigial-sideband, 176, 182
- analog, 13
 - communications, 151
 - filter, 20, 257
 - FM demodulation, 185
 - modulation, 177
 - PM demodulation, 185
 - radio, 176
- analog-to-digital converter, 14, 24, 59, 67, 68, 70, 71
- analytic function, 213
- angle modulation, 183
- angular frequency, 238, 239
- antenna, 16, 24, 26
 - frequency response, 27

- polarization, 16
- radiation pattern, 27
- application layer, 22
- approximate MMSE filter, 107
- approximate Wiener filter, 107
- area
 - effective, 18
- argmax, 223
- associate, 203
- atomic clock, 73
- attenuation, 9
 - line-of-sight, 40
 - propagation, 15
- audio
 - monophonic, 177
- autocorrelation, 234, 249
 - discrete, 254
- autocovariance, 249
- automatic gain control, 59
 - digital, 59
 - transmit, 59
- b/s, 27
- back-substitution, 210
- ball of noise, 34
- band-pass filter, 21, 51
- bandwidth, 63, 115
 - double-sided, 27
 - full, 27
 - is not data rate, 80
 - single-sided, 27
- baseband, 27, 62, 63
 - complex, 24, 26, 69, 83, 164, 257
- baseband thermal noise, 20
- Bayes' theorem, 222, 223
- beacon, 21
- beamformer, 165, 169
- BER, *see* bit error rate
- Bessel function, 216
 - modified, 216, 232
- beta distribution
 - central, 148
- beta function, 148
 - incomplete, 148
- biased estimates, 255
- binary, 134, 135
- binary code, 128
- binary-phase-shift keying, *see* BPSK
- bipartite graph, 131
- bit, 13
 - information, 126
 - parity, 126
- bit error rate, 94
- bits per channel usage, 28
- bits per chip, 28
- bits per sample, 28
- bits per second, 27
- bits per second per hertz, 28
- bits per symbol, 28
- block code, 128
- block-wise fading channel, 174
- Boltzmann constant, 19
- bound
 - Shannon, 32
- BPSK, 78
- broadcast topology, 158
- camera, 14
- capacitor, 179
- capacity
 - channel, 32, 33, 76, 80
 - low-SNR, 33
 - MIMO channel, 167
 - modulation, 80
 - outage, 174
 - real channel, 33
 - Shannon, 32
- carrier frequency, 13, 63, 242
- carrier recovery, 150
- carrier-sense multiple access, *see* CSMA
- Cartesian space, 191
- cat videos, 13
- CDF, 222
- CDMA, 160
- center frequency, 141
- central β distribution, 148
- central limit theorem, 19, 31, 229
- central moment, 225
- chain
 - amplifier, 55
 - receive, 23
 - transmit, 23
- channel, 13, 31
 - block-wise fading, 174
 - dispersion, 15, 99
 - Doppler-frequency spread, 99
 - doubly dispersive, 99
 - flat-fading, 15, 76, 151, 163
 - frequency-selective, 15, 99, 163
 - line-of-sight, 16
 - memory, 15
 - multiple-input multiple-output (MIMO), 163, 166
 - multiple-input single-output (MISO), 172
 - narrowband, 112
 - single-input multiple-output (SIMO), 163
 - single-input single-output (SISO), 163
 - slow-fading, 174
- channel capacity, 32, 33, 36, 80
- channel distortion, 25
- channel estimation, 23, 25, 26
- channel impulse response, 100

- channel reciprocity, 168
- channel usage, 28, 32, 34, 77, 80
- channel-uninformed MIMO transmitter, 167
- Charles Wheatstone, 12
- chip, 28, 77, 80, 166
- chip rate, 76, 77, 85
- circulant matrix, 200
- circular polarization, 17
- class A amplifier, 55
- class AB amplifier, 55
- class B amplifier, 55
- class D amplifier, 55
- Claude Shannon, 31
- closed set, 130
- code
 - binary, 128
 - block, 128
 - forward error correction, 166
 - linear, 128
 - Morse, 78
 - space–time, 166, 170
 - systematic, 128, 135
 - Walsh, 160
- code-division multiple access, *see* CDMA
- codeword
 - sum, 129
- coding, 115
 - source, 14, 44
- column vector, 7
- communications, 12, 31
 - analog, 151
- complex baseband, 13, 24, 26, 62, 63, 69, 83, 164, 242, 257
- complex conjugate, 5, 193
- complex Gaussian noise, 20
- complex hypervolume, 35
- complex normal distribution, 229
- complex number, 4
- complex tone, 238
- compression, 14
 - data, 23
 - lossy, 46
 - source, 25, 44
- compression point
 - 1 dB, 53
- computational cost
 - FFT, 115
- computer scientist, 80
- conditional probability density, 222
- confinement
 - spectral, 115
- conjugate transpose, 193
- constant
 - Boltzmann, 19
 - Planck, 19
- constant modulus, 84, 85
- constellation, 26, 41, 73, 76–78, 82
 - QPSK, 108
- constraint length, 135
- continuous-phase frequency-shift keying, *see* CPFSK
- control signals, 23, 25
- conventional double-sideband amplitude modulation, 176
- converter
 - analog-to-digital, 14, 24, 67, 68, 70
 - digital-to-analog, 67, 70
- convolution, 248
 - discrete, 104
 - sampled, 104
- convolutional code, 134
 - non-recursive, 134
 - recursive, 134
- correlated noise, 151
- Costas loop, 151
- covariance
 - spatial noise, 165
- covariance matrix, 229, 230
 - MIMO transmit, 167
 - spatial, 164
- CPFSK, 84
- cross-correlation, 234
- crystal oscillator, 73
 - age, 73
 - oven-controlled, 73
 - phase noise, 73
 - temperature, 73
 - temperature-compensated, 73
- CSMA, 159
- cumulative distribution function, 222
- current, 16
- DAC, 26, 67, 70, 71
- data compression, 23
- data link layer, 22
- dB, 9
- dBm, 52
- dBW, 52
- DC, 13, 62, 244
- DC offset, 178, 179
- de-spread, 160
- de-spreading SNR, 161
- decibel, 9
- decision
 - hard, 76, 92, 126, 137
 - soft, 76, 126, 137
- decoder
 - Viterbi, 137
- decoding
 - hard, 126
 - soft, 126, 132

- decomposition
 - eigenvalue, 204
 - QR, 209
 - singular value, 207
 - subspace, 210
- degrees of freedom
 - spatial, 166
- delay spread, 15, 91, 99, 100, 115
 - root mean squared (RMS), 119
- delta function, 8, 240
- demodulation, 76, 91
 - analog FM, 185
 - analog PM, 185
 - hard, 76, 92
 - likelihood, 95
 - soft, 76
- density
 - probability, 221
- derivative
 - matrix determinant with respect to real scalar, 213
 - matrix inverse with respect to real scalar, 213
 - matrix log determinant with respect to real scalar, 213
 - matrix trace with respect to real scalar, 213
 - matrix with respect to real scalar, 213
 - real, 212
 - vector with respect to real scalar, 212
- destination, 13
- detection
 - missed, 144
- detection probability, 144
- detection test statistic, 145–147, 150
- detector
 - energy, 143
- determinant, 202
- DFT, 255
 - inverse, 114
 - taper, 257
 - window, 257
- DFT matrix, 256
- diagram
 - constellation, 78
- differential modulation, 83
- digital, 13
 - automatic gain control, 59
 - filter, 20, 257
 - IF, 70
 - modulation, 127
 - signal, 14
- digital-to-analog converter, *see* DAC
- Dirac delta function, 8
- direct current, 13, 244
- direct down-conversion, 67
- direct up-conversion, 67
- discrete autocorrelation, 254
- discrete convolution, 104
- discrete Fourier transform, 255
 - inverse, 114
 - matrix, 256
- discrete set, 76
- discrete-time Fourier transform, 253
- dispersion, 15, 91
- dispersive channel, 99
- distance
 - Hamming, 130, 137
- distortion, 15, 55
- distribution, 221
 - χ^2 , 231
 - central β , 148
 - central χ^2 , 231
 - complex χ^2 , 231
 - complex Gaussian, 229
 - exponential, 230
 - Gaussian, 148, 229
 - noncentral β , 148
 - probability, 221
 - Rayleigh, 230
 - Rician, 232
- distributive, 203
- Doppler-frequency spread, 99, 151
- dot product, 195
- double-sideband amplitude modulation, 178
- double-sideband suppressed-carrier amplitude modulation, 176, 177
- double-sided bandwidth, 27
- doubly dispersive channel, 99
- down-conversion, 13, 24, 67
- draw, 221
- DSB AM, 176, 178
- DSB-SC AM, 176, 177
- duplex, 157
 - frequency-division, 157
 - full, 52
 - in-band full, 157
 - time-division, 157, 168
- dynamic range, 59
- effective area, 18
- Egyptians
 - early written language, 12
- eigenvalues, 204, 207
 - 2×2 Hermitian matrix, 206
 - degenerate, 204
 - duplicated, 204
- eigenvectors, 204
- electromagnetic wave, 13, 16
- electron beam, 52
- Elisha Gray, 12
- elliptic polarization, 17
- encoding
 - source, 14

- energy detector, 143
- energy signal, 237
- energy spectral density (ESD), 109, 241, 249, 254
- entropy, 36, 46, 229
- envelope, 179
- equalizer
 - adaptive, 91, 103
 - zero-forcing, 104
- erf, 217
- ergodic random process, 235
- error
 - false-positive, 144
 - type-one, 144
 - type-two, 144
- error correcting code, 25, 41, 115, 125
 - convolutional, 134
 - Hamming, 133
 - SISO, 171
- error correction
 - hard decoding, 126
 - soft decoding, 126, 132
 - Viterbi decoder, 137
- error function, 217
- estimation
 - bias, 255
 - channel, 25
 - maximum a posteriori, 223
 - maximum likelihood, 151, 223
- Euler's formula, 4, 62
- Euler's number, 4
- excess kurtosis, 227
- exclusive-or (XOR), 134
- external interference, 15

- factorial, 215
- false alarm, 144
- false alarm probability, 144
- false-positive error, 144
- fast Fourier transform, *see* FFT
- FDD, 157
- FDMA, 159
- Federal Communications Commission (FCC), 63
- FFT, 24, 255, 257
 - inverse, 26, 114
 - taper, 257
 - window, 257
- filter, 14, 24
 - adaptive, 103, 107
 - analog, 20, 257
 - approximate MMSE, 107
 - approximate Wiener, 107
 - band-pass, 21, 51
 - digital, 20, 257
 - finite-impulse-response (FIR), 111
 - high-pass, 21
 - IF, 69
 - low-pass, 21
 - minimum mean squared error (MMSE), 105
 - Parks–McClellan, 181
 - phase, 85
 - pre-selection, 51, 68
 - pulse shaping, 87
 - surface acoustic wave (SAW), 21, 257
 - Wiener, 105
 - zero-forcing, 104
- finite bandwidth, 253
- finite-impulse-response (FIR) filter, 111, 257
- finite-state machine, 21
- flat-fading channel, 15, 76, 151, 163
- FM, 69, 176
 - demodulation, 185
- forward error correction, 22, 25, 125, 166, 171
 - convolutional, 134
 - Hamming, 133
 - hard decoding, 126
 - LDPC, 133
 - LDPC code, 133
 - soft decoding, 126, 132
 - turbo code, 133, 134
- Fourier series, 250
- Fourier transform, 237, 239
 - angular frequency, 239
 - autocorrelation, 249
 - conjugation, 244
 - constant, 244
 - convolution, 248
 - cosine, 240, 244
 - DC, 244
 - derivative, 249
 - discrete, 255
 - discrete autocorrelation, 254
 - discrete-time, 253
 - even function, 245
 - frequency shift, 242
 - Gaussian function, 246
 - impulse train, 252
 - linear operator, 241
 - odd function, 245
 - real sinusoids, 240
 - sine, 240, 244
 - sine and cosine, 240
 - temporal scaling, 243
 - time reversal, 243
 - time shift, 241
 - top hat function, 246
 - unitary, 240
- frame, 22
- frequency
 - angular, 238
 - carrier, 63
 - center, 141
 - instantaneous, 84, 183

- intermediate, 26
- normalized, 259
- radio, 13
- real, 238
- frequency correction, 25
- frequency hopping, 103
- frequency modulation, 69, 176, 183
- frequency offset estimation, 26
- frequency offsets, 99
- frequency planning, 69
- frequency shift, 242
- frequency spread, 151
- frequency synchronization, 141, 142, 150
- frequency synthesizer, 72
 - settling time, 74
- frequency-division duplex, *see* FDD
- frequency-division multiple access, *see* FDMA
- frequency-selective channel, 15, 99, 163
- frequency-shift keying, 84
- Friis equation, 16, 40
- Friis formula, 58
- Frobenius norm, 202
- FSK, 84
- full bandwidth, 27
- full-duplex, 52, 157
- function
 - β , 148
 - analytic, 213
 - Bessel, 216
 - beta, 148
 - error, 217
 - gamma, 143
 - Gaussian, 246
 - Gaussian Q, 217
 - incomplete gamma, 144
 - Marcum Q, 218
 - probability density, 221
 - sinc, 86, 89, 112, 215, 216, 246
 - top hat, 86, 89, 112, 215, 246
- gain
 - amplifier, 51
- gain control
 - adaptive, 59
- Galois field, 128
- gamma function, 143, 215, 231
 - incomplete, 231
- Gaussian distribution, 148
- Gaussian function, 246
- Gaussian minimum-shift keying, *see* GMSK
- Gaussian noise, 19
- Gaussian Q-function, 217
- Gaussian signal, 77
- generator matrix, 128
- GF(2), 128, 134, 135
- GMSK, 85
- graph
 - bipartite, 131
- guard bands
 - spectral, 41
- Guglielmo Marconi, 12
- Hadamard code, 160
- Hadamard inequality, 204
- Hadamard product, 203
- Hamming code, 133
- Hamming distance, 130, 137
- hard decision, 76, 92, 126, 137
- hard decoding, 126
- hard demodulation, 76, 92
- harmonics, 237
- Hartley modulator, 180
- Hata channel model, 120
- Hedy Lamarr, 103
- Hermitian conjugate, 193
- Hermitian matrix, 198
- heterodyne, 62
- hidden-node problem, 159
- high frequency, 26
- high-order modulation, 41, 80
- high-pass filter, 21
- Hilbert space, 191
- Hilbert transform, 180, 181
- hop, 158
- hopping
 - frequency, 103
- horizontal polarization, 17
- Householder transformation, 209
- human voice, 14
- hypersphere, 35
- hypervolume
 - complex, 35
- hypotheses testing, 143
- I–Q, 64
 - mismatch, 68
- i.i.d., 31, 228
- ICI, 116
- idempotent, 211
- identically distributed, 228
- identity matrix, 196
- IF, 26, 69
 - digital, 70
- IF filter, 69
- IFFT, 114
- IIP, 53
- IIP₃, 54
- impulse response
 - channel, 100
- in-band full-duplex, 157
- in-phase, 64, 70
- incomplete beta function, 148

- incomplete gamma function, 144, 215
- independent, 227
- independent and identically distributed, *see* i.i.d.
- index
 - modulation, 183
- infinite temporal support, 253
- infinite-impulse-response (IIR) filter, 257
- infinity norm, 201
- information, 12, 31
 - mutual, 38
- information source, 44
- information source compression, 44
- information theory, 31
- inner product, 153, 195
 - Hermitian, 195
 - normalized, 147
- input intercept point, 53
- instantaneous frequency, 84, 183
- integer number, 4
- integrated signal-to-noise (SNR) ratio, 149
- integration, 7
 - volume, 214
- inter-subcarrier interference, 116
- inter-symbol interference, 15, 99, 103, 110
- intercept point, 53
- interference
 - external, 15
 - inter-subcarrier, 116
 - inter-symbol, 99, 103, 110
- intermediate frequency, *see* IF
- interval
 - spectral coherence, 115
- inverse
 - pseudo, 105
- inverse DFT, 114
- inverse discrete Fourier transform, 114
- inverse FFT, 26, 114
- IP, 53
- IP₃, 54
- ISI, 15, 110
- ISNR, 149
- iterative soft decoding, 132

- Jacobian, 225
- Johnson–Nyquist noise, 19

- K-factor, 232
- Kelvin, 19
- keying, 78
 - continuous-phase frequency shift, 84
 - frequency shift, 84
 - Gaussian minimum-shift, 85
 - minimum-shift, 84
- klystron, 52
- Kronecker delta, 8
- Kronecker product, 161, 203

- kurtosis, 227
 - excess, 227

- L2-norm, 199, 201
- Lamarr, Hedy, 103
- lattice, 76
- LDPC code, 133
- length
 - constraint, 135
- lens, 14
- leptokurtic, 227
- likelihood
 - demodulation, 95
 - symbol, 137
- limit
 - Shannon, 32
- line-of-sight
 - attenuation, 40
 - channel, 16
 - propagation, 16
 - received power, 40
- linear amplifier, 84
- linear code, 128
- linear scale, 9
- linear time-invariant system, *see* LTI
- LNA, 15, 24, 51, 55, 59, 68
- local oscillator, 99, 151
- local oscillator phase noise, 41
- logarithm, 5
 - complex value, 6
 - natural, 5
 - principal value, 7
 - translation of base, 6
- logarithmic scale, 9
- lossless source coding, 14
- lossy source coding, 14
- lossy source compression, 46
- low-density-parity-check (LDPC) code, 133
- low-noise amplifier, *see* LNA
- low-pass filter, 21
- low-SNR capacity, 33
- low-SNR Shannon limit, 33
- LTI, 102

- MAC, 22, 25, 158
- magnetron, 52
- MAP, 223
- MAP estimate, 223
- Marcum Q-function, 147, 218
 - generalized, 218
- marginal probability density, 222
- matched filter, 160
- matrix, 7, 192
 - 2×2 inverse, 197
 - circulant, 200
 - determinant, 202

- determinant of inverse, 203
- diagonal, 194
- discrete Fourier transform (DFT), 256
- eigenvalues, 207
- Frobenius norm, 202
- generator, 128
- Hadamard product, 203
- Hermitian, 198
- identity, 196
- inverse of identity plus rank-1 matrices, 197
- inverse of identity plus rank-2 matrices matrix, 197
- inverse partitioned, 197
- inversion, 196
- Kronecker product, 203
- low rank, 207
- minor, 202
- nonsingular, 196
- orthonormal, 207, 166
- parity check, 131
- positive-definite, 198, 204, 208
- positive-semidefinite, 198, 204, 208, 209
- product, 196
- projection, 210
- quadratic Hermitian, 208
- rank, 208
- rank-1, 207
- rank-2, 207
- SVD of inverse, 208
- Toeplitz, 200
- trace, 200
- unitary, 169, 198
- upper triangular, 209
- matrix decomposition, 204
- maximum a posteriori estimate, 223
- maximum likelihood estimation, 151, 223
- maximum likelihood path, 137
- maximum-redundancy space–time block coding, 171
- mean, 225
- mean of random process, 233
- media access control, *see* MAC
- memory, 15
- mesh network, 158
- MIMO channel, 163, 166
- MIMO channel capacity, 167
- MIMO transmit covariance matrix, 167
- MIMO transmitter
 - channel-uninformed, 167
- minimum mean squared error filter, 105
- minimum-shift keying, 84
- mismatch
 - I–Q, 68
- MISO channel, 172
- missed detection, 144
- mixer, 59
- mixing, 65
- ML, 223
- ML estimate, 223
- MMSE
 - finite-sampled signal, 107
- MMSE filter, 105
- model
 - open systems interconnection (OSI), 21
 - single-carrier, 151
- modulation, 26, 62, 76, 83, 115
 - amplitude, 69
 - analog, 177
 - angle, 183
 - digital, 127
 - frequency, 69, 183
 - higher order, 41, 80
 - OFDM, 112
 - phase, 183
 - pulse-shaping filter, 87
 - single-carrier, 26, 76
 - spectral shape, 85
 - up-conversion, 242
- modulation index, 183
- modulation-specific capacity, 80
- modulator
 - Hartley, 180
- modulus
 - constant, 84, 85
- moment
 - central, 225
- monophonic audio, 177
- Monte Carlo evaluation, 175
- Morse code, 78
- MSK, 84
- multiaccess receiver, 165
- multipath, 169
- multiple access
 - aloha, 158
 - carrier-sense, 159
 - code-division, 160
 - frequency-division, 159
 - time-division, 159
- multiple-antenna receiver, 163
- multiple-input multiple-output channel, *see* MIMO channel
- multiple-input single-output channel, *see* MISO channel
- multiplex, 25
- multiplexing
 - spatial, 166
- mutual information, 36, 38, 229
- narrowband channel, 112
- nats per second, 27
- natural logarithm, 5
- negative frequency, 62

- network, 158
 - mesh, 158
 - topology, 158
- node, 158
- noise, 15
 - complex baseband, 20
 - complex Gaussian, 20
 - correlated, 151
 - Gaussian, 19
 - Johnson–Nyquist, 19
 - out-of-band, 24
 - phase, 73, 99
 - spatial covariance matrix, 164, 165
 - transmitter, 52
- noise ball, 34
- noise factor, 55
- noise figure, 9, 41, 55
- non-recursive convolutional code, 134
- noncausal, 89
- noncentral β distribution, 148
- noncentral χ^2 distribution, 146
- nonlinear, 15
- nonlinearity, 27
- nonsingular matrix, 196
- norm, 201
 - Frobenius, 202
 - infinity, 201
 - L2, 199, 201
 - p, 201
 - zero, 201
- normal distribution, 229
- normalized frequency, 259
- normalized inner product, 147
- notation, 3, 191
- Nyquist rate, 28
- Nyquist sample rate, 27, 28
- Nyquist sampling, 253

- OCXO, 73
- OFDM, 24, 26, 112, 257
- OFDM modulation, 112
- OIP, 54
- Okumura–Hata channel model, 120
- open systems interconnection model, *see* OSI model
- operator
 - projection, 148
- optimize, 213
- orthogonal, 160
- orthogonal frequency-division multiplexing, *see* OFDM
- orthonormal, 169
- orthonormal matrix, 207, 208
- oscillator
 - crystal, 73
 - local, 99
 - oven-controlled crystal, 73
 - temperature-compensated crystal, 73
 - voltage controlled, 74, 185
- OSI layer
 - application, 22
 - data link, 22
 - physical, 22
- OSI model, 21, 120
- OSI stack, 21
- out-of-band noise, 24
- outage capacity, 174
- outer product, 195
- output intercept point, 54
- oven-controlled crystal oscillator, 73
- oversample, 28, 89

- p-norm, 201
- packet, 22
- parity bit, 25, 126
- parity check matrix, 131
- Parks–McClellan filter design, 181
- passband, 13, 24, 26, 27, 62, 63, 177
- path
 - maximum likelihood, 137
- PDF, 221
- periodogram, 254
- phase filter, 85
- phase modulation, 176, 183
 - sinusoidal, 184
- phase noise, 73, 99, 151
 - local oscillator, 41
- phase-lock loop, *see* PLL
- photon, 27
- physical layer, 22
- pilot sequence, 23, 26
- pilot signal, 23, 144
- Planck constant, 19
- platykurtic, 227
- PLL, 73, 151, 185
- PM, 176
 - demodulation, 185
- polarization, 16
 - antenna, 16
 - circular, 17
 - elliptic, 17
 - horizontal, 17
 - vertical, 17
- positive-definite matrix, 198, 204, 208
- positive-semidefinite matrix, 198, 204
- posterior probability density, 222
- power, 9
- power amplifier, 51
- power control, 25
 - transmit, 59
- power signal, 237, 250

- power spectral density, *see* PSD
 - pulse-shaping filter, 88
- pre-selection filter, 51, 68
- precoding
 - spatial, 170
- prior probability density, 222
- probability, 221
 - change of variables, 223
 - detection, 144
 - false alarm, 144
 - multivariate distribution, 227
- probability density
 - a posteriori*, 222
 - a priori*, 222
 - conditional, 222
 - marginal, 222
 - posterior, 222
 - prior, 222
- probability density function, 221
 - χ^2 , 143
 - zero-mean circularly symmetric complex Gaussian, 20
- probability distribution, 221
- processing
 - direct down-conversion, 67
 - direct up-conversion, 67
 - down-conversion, 67
 - up-conversion, 67
- processing chain
 - receive, 23
 - transmit, 23
- product
 - inner, 195
 - Kronecker, 161
 - outer, 195
- projection matrix, 210
- projection operator, 148
- propagation
 - line-of-sight, 16
- propagation attenuation, 15
- propagation delay, 15
- PSD, 241, 249, 254
- pseudoinverse, 105
- pulse shaping, 78, 85
- pulse-shaping filter, 24, 87
 - power spectral density, 88
- QPSK, 78, 108
- quadrature, 64, 70
- quadrature-phase-shift keying, *see* QPSK
- radiation pattern, 27
- radio, 23
 - analog, 176
- radio frequency, 13
- random process, 233
 - ergodic, 235
 - mean, 233
 - stationary, 234
 - wide-sense stationary, 234
- rate
 - chip, 76, 77, 85
 - Nyquist, 27, 28
 - sample, 89
 - symbol, 76, 85, 89
- rate-distortion theory, 47
- ratio
 - signal-to-interference, 174
- real frequency, 238
- real number, 4
- receive chain, 23
- received power
 - line-of-sight, 40
- receiver, 13
 - multiaccess, 165
 - multiple-antenna, 163
 - nonlinearity, 15
- reciprocity
 - channel, 168
- recursive convolutional code, 134
- redundancy
 - spatial, 166
- reference signal, 144
- register
 - shift, 134, 135
- resampling, 24
- resistive load
 - unit, 238
- resistor, 179
- resolvable delay spread, 102
- resonant cavity, 52
- RF, 13
- Rician distribution, 147
 - K -factor, 232
- RMS, 119
- rolloff factor, 90
- root mean squared, 119
- row vector, 7
- sample, 28
- sample rate, 24, 89
 - Nyquist, 27, 28
- sample-and-hold circuit, 71
- sampled convolution, 104
- Samuel Morse, 12
- SAW filter, 21, 257
- scalar, 4
- scale
 - linear, 9
 - logarithmic, 9
- scatterer, 99

- Schuster's periodogram, 254
- sequence
 - symbol, 77
- SER, 94
- series
 - Fourier, 250
 - Taylor, 6, 53
 - Volterra, 53
- set
 - closed, 130
- settling time
 - frequency synthesizer, 74
- Shannon limit, 14, 25, 32, 127
 - low-SNR, 33
- shift register, 134, 135
- signal, 13
 - digital, 14
 - energy, 237
 - Gaussian, 77
 - power, 237
- signal-to-noise ratio, *see* SNR
- signal-to-noise-plus-interference ratio, *see* SINR
- SIMO channel, 163
- sinc function, 86, 89, 112, 215, 216, 246
- single-carrier model, 151
- single-carrier modulation, 26, 76
- single-input multiple-output channel, *see* SIMO channel
- single-input single-output channel, *see* SISO channel
- single-sideband amplitude modulation, 176, 179
- single-sided bandwidth, 27
- singular value decomposition, *see* SVD
- sink, 13
- SINR, 174
- sinusoidal phase modulation, 184
- SISO channel, 163
- SISO error correcting code, 171
- skew, 226
- slow-fading channel, 174
- SNR, 9, 14, 15, 83
 - de-spreading, 161
 - integrated, 149
- soft decision, 76, 126, 137
- soft decoding, 126, 132
- soft demodulation, 76
- solid state amplifier, 52
- source, 13
- source coding, 14, 44
 - lossless, 14
 - lossy, 14
- source compression, 25
 - lossless, 14, 44, 45
 - lossy, 14, 46
- source encoding, 13
- space
 - Cartesian, 191
 - Hilbert, 191
- space-time block coding
 - maximum-redundancy, 171
- space-time code, 166, 170
- spatial degrees of freedom, 166
- spatial multiplexing, 166
- spatial noise covariance, 164, 165
- spatial precoding, 170
- spatial redundancy, 166
- spectral allocation, 63
- spectral analysis, 237
- spectral coherence interval, 115
- spectral confinement, 115
- spectral density
 - energy, 241
 - power, 241
- spectral efficiency, 32, 78, 115, 127, 160
- spectral guard bands, 41
- spectral harmonics, 237
- spectral synchronization, 150
- spectrum
 - pulse-shaping filter, 88
- sphere hardening, 34
- spread, 160
 - delay, 15, 99, 115
- spreading code, 160
- SSB AM, 176, 179
- stability
 - filter, 259
- stable filter, 259
- stack
 - OSI, 21
- star topology, 158
- state transition, 137
- stationary random process, 234
- Stieltjes transform, 180
- subcarrier, 112
 - number, 115
- Sumerians
 - early written language, 12
- superheterodyne, 62, 68, 70
 - down-conversion, 68
 - frequency planning, 69
 - up-conversion, 68
- superheterodyne down-conversion, 70
- superheterodyne up-conversion, 70
- surface acoustic wave (SAW) filter, 21, 257
- SVD, 207
- symbol, 26, 28, 77
- symbol error rate, 94
- symbol likelihood, 137
- symbol rate, 76, 85, 89
- symbol sequence, 77

- synchronization, 23, 141
 - frequency, 25, 26, 141, 142, 150
 - spectral, 150
 - temporal, 153
 - time, 141, 153
 - timing, 25, 26
- syndrome, 132
- syndrome table, 133
- synthesizer
 - frequency, 72
- system
 - linear time-invariant, 102
- systematic code, 128, 135
- taper, 257
- Taylor series, 6, 53
- TCXO, 73
- TDD, 157, 168
- TDMA, 159
- telegraph, invention, 12
- telephone, invention, 12
- temperature, Kelvin, 19
- temperature-compensated crystal oscillator, *see* TCXO
- temporal scaling, 243
- temporal synchronization, 153
- test statistic
 - detection, 145–147, 150
- thermal noise, 15
 - complex baseband, 20
- threshold, 92
- time reversal, 243
- time shift, 241
- time synchronization, 153
- time-division duplex, *see* TDD
- time-division multiple access, *see* TDMA
- timing, 141
- timing offset estimation, 26
- timing synchronization, 141
- Toeplitz matrix, 200
- tone, 238
 - complex, 238
- top hat function, 86, 89, 112, 215, 246
- topology
 - broadcast, 158
 - network, 158
 - star, 158
- trace, 200
- track-and-hold circuit, 71
- training data, 23
- training sequence, 26
- training signal, 144
- transceiver, 157
- transfer function, 259
- transform
 - Fourier, 239
 - Hilbert, 180, 181
 - Stieltjes, 180
 - Z, 135
- transformation
 - Householder, 209
- transition
 - state, 137
- transmit chain, 23
- transmit covariance matrix, 167
- transmit power control, 59
- transmitter, 13
 - AM radio, 52
 - nonlinearity, 15
- transmitter noise, 52
- transpose, 193
- trellis, 137
- tube, 52
- turbo code, 133, 134
- type-one error, 144
- type-two error, 144
- unit resistive load, 238
- unitary Fourier transform, 240
- unitary matrix, 169, 198
- up-conversion, 26, 67, 178, 242
- up-convert, 13, 242
- upper triangular matrix, 209
- usage
 - channel, 77
- use
 - channel, 32
- variance, 226
- VCO, 74, 185
- vector, 7, 191
 - column, 7
 - inner product, 153
 - norm, 201
 - operation, 194
 - row, 7
 - space, 191
- vertical polarization, 17
- vestigial-sideband amplitude modulation, 176, 182
- Viterbi decoder, 137
- vocoder, 14, 46
- voltage, 16
- voltage level, 76
- voltage-controlled oscillator, *see* VCO
- Volterra series, 27, 53
- VSB AM, 176, 182
- Walsh code, 160
- wave
 - electromagnetic, 16
- waveform, 22
- wide-sense stationary random process, 233, 234

Wiener filter, 105	XO, 73
Wiener–Hopf equation, 106	XOR, 134
WiFi, 52	
William Cooke, 12	
window, 257	Z-transform, 135, 258
wireless	zero norm, 201
invention, 12	zero-crossing, 84
wireless communications system, 23	zero-forcing equalizer, 104
Woodbury’s formula, 197	zero-forcing filter, 104