Index

abalone shell, 43, 45, 912, 915
abductin, 51
Achilles' tendon, 56, 271, 273
actin, 51, 56–57
activation energy, 136, 218, 223, 225, 298, 440, 749, 754–755, 757–758, 760, 766–767, 785, 947
active materials, 61
adhesion
  thin films to substrates, 627
adiabatic curve, 450–451
adiabatic heating, 218
adiabatic shear bands, 451
AISI 1040 steel
  effect of strain rate, 202–203
  stress–strain curves after heat treatments, 189–190
AISI 1045 Steel
  determination of Johnson–Cook parameters, 192
AISI 4140 steel
  fatigue crack propagation, 838
  hot-rolled, 196
  true engineering stress–strain curves, 196
Al-Li alloy, 268, 651
  alloy 8090, 268
alpha-helix, 51, 53
amino acids, 51–52, 64
anelasticity, 136
anisotropy, 7, 77, 110, 113, 115, 123–124, 130, 171, 241, 259, 261, 263, 275, 337, 403, 452–453, 462, 558, 571–572, 574, 884, 890
annealing point, 224
antiphase boundary, 714, 718, 721
aorta, 151
aragonite, 49–50, 912
  atomic structure, 50
ARALL. *See* composites
argon model, 222
articular cartilage, 153, 156
atactic polymer. *See* polymer
atomic point defects. *See* point defects

bake-hardening, 671
barreling, 188, 210–211
Bauschinger effect, 213–214
Berg–Barrett topography, 308
bicycle frame, 173–174
biocompatibility, 6, 846, 911, 939
biocomposite, 43
biological
  artery, 151–154
  blood vessels, 52, 54, 150–152, 703
  cartilage, 154
  in the body, 49
  mechanical properties, 10, 156, 273, 579
  monolithic, 3, 7, 43, 50
  sandwich structure, 42
  veins, 57, 150–152, 825
biological materials, xvii, xix, 10, 40–44, 48, 150, 163, 273, 586–587, 590–591
  nano- and microstructure, xix, 48, 61
  stress–strain curves, 44, 275
biomaterials
  fatigue of, 845
biomimetics, 275, 912
blue brittleness, 650
bone
  cancellous, 46, 156, 275, 730
  cortical, 5, 156, 273, 275–276
Brale indenter. *See* hardness
branched polymers. *See* polymers
Bravais lattices, 11–12
Bridgman's correction, 200–201
Brinell indenter. *See* hardness
brittle materials, 480, 482–483, 500, 506–507, 513, 515, 534, 556, 568–569, 621
Budiansky and O'Connell, 131–132
bulk modulus, *K*, 113, 167–169, 791, 882
Burgers circuit. *See* dislocation
Burgers vector. *See* dislocation

calcium carbonate, 42–43, 45, 50, 586, 912
carbon nanotubes, 64–65
  configuration, 64
cartilage. *See* biological
cavitation. *See* void
cellular materials, 46
  mechanical response, 732
    densification, 732
    elastic region, 92
    plastic plateau, 735
  open-cell geometry, 732
  structure, 733
cellulose, 58, 274, 958
ceramic systems, 673, 799
change in Poisson's ratio
  with deformation, 195
Charpy impact test, 547, 598–599, 604–605
chevron notch test, 621
chitin, 42, 51, 59
Coble creep. *See* creep
coincidence site lattice. *See* grain boundaries
cold-working, 424
collagen, 42, 50–51, 54–56, 58–60, 151, 153–154, 156, 275, 586, 588, 590–591
  structure, 51, 55, 154
  tropocollagen, 9, 54
compliance, 105–106, 108
composite(s)
  aging response of matrix, 889
  anisotropic nature, 890
  B_4C/Al composite, 22, 46
  heat capacity, 880
  lamellar, 415
  laminated
    abalone, 45, 912
    aramid aluminum (ARALL), 914

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

composite(s) (cont.)
glass aluminum (GLARE), 135, 908, 913–914
laminated composite, 43, 238, 741, 912, 915
load transfer, 877, 892, 895–898
matrix materials, 873–874, 879, 883, 892
reinforcement, 7, 255, 448, 534, 725, 870–871, 873–880, 882–883, 886, 889, 891, 893, 902, 905
sandwich structure. *See* sandwich
compressibility, 113
controlled rolling, 666
copper
variation of modulus with direction, 114
corrosion
crevice, 923
electrochemical, 921
erosion, 924
galvanic, 922–923
intergranular, 657, 924
nature, 921
pitting, 924
stress, 462, 598, 811, 835, 921, 925–926, 930, 935, 944
uniform, 923
Cottrell atmosphere, 642, 644–645, 671, 690–691
crack
closure, 849
extension force, 482–484, 497–499, 504, 506–507, 944
nucleation, 534, 824
opening displacement, 500
opening displacement testing, 611
propagation, 61, 462, 466, 478–479, 481–483, 495, 506, 532, 551, 554, 556, 563, 576, 589, 609, 611–612, 623, 724, 811, 814, 830–832, 834, 838, 842, 847, 849–850, 859, 887, 890, 892, 900–901, 927, 934, 942, 944, 946
propagation testing, 859
propagation with plasticity, 481
tip stress field, 487
crack-tip separation modes, 485
crazing, 216, 236–237, 534, 577, 579, 585, 814, 842, 940, 942–943
creep
activation energy, 749, 758, 766–767
alumina, 763
Coble, 762–763, 770–772, 774
correlation and extrapolation methods, 751
crowdion, 299
definition of, 745
diffusion:, 759
diffusion coefficient, 749
dislocation, 764
dislocation climb, 357, 762, 764, 767
electronic materials, in, 791
fracture, 772
Frank–Read source, 765
glide, 767, 770–771, 773
Harper–Dorn, 763–764, 774
intergranular fracture, 772
Larson–Miller, 751–754, 757, 801
Manson–Haferd, 751, 753, 757–758
Maxwell model, 782–784
mechanism, 397, 763
Monkman–Grant equation, 773–775
Mukherjee–Bird–Dorn equation, 749, 765
Nabarro–Herring, 397, 563, 761–763, 770–771, 774
polymers, in, 782
power law, 764
rafting, 778
relaxation time, 784
rocks, 746
Sherby–Dorn, 751, 753–754, 756–758
stress relaxation, 782, 784–786, 788–790, 829
superplasticity, 204, 793, 797, 799
Voigt model, 784–785, 788
cross-slip, 344–345, 404, 438–441, 444, 535, 716–717, 719–720, 825
crystal structures, 70, 713, 955
cubic zirconia
variation of modulus with direction, 171
cyclic stress–strain curve, 825, 859

damage
cumulative, 820
environmental, 921
hydrogen, 926, 928, 931, 933, 937
radiation, 297, 924, 942
deep drawing, 230, 259–261, 453
deformation energy density. *See* strain energy density
deformation mechanism maps, 763
degree of crystallinity, 34, 37, 581, 879, 941
density, 4
diamond, 22–24, 65, 125–126, 246, 248, 535, 622, 626, 629
diamond pyramid hardness. *See* hardness
diffusion coefficient, 746, 749, 755, 759–760, 762, 765, 774, 792
dilation, 102
direction cosines, 104, 106, 113, 122
dislocation(s)
Burgers circuit, 309
Burgers vector, 287, 304, 309, 311, 313–314, 321, 323, 326, 328, 331–332, 336, 338, 343–347, 349–351, 358, 374, 395, 436, 443, 545, 659, 668, 671, 716, 749, 762
caterpillar, 304
cells, 445
ceramics, in, 335, 337
climb, 762
density, 319, 321, 339, 342, 350–351, 379, 402, 404, 435, 440–442, 445, 447, 449, 534, 643, 671, 874, 878–879, 889, 936
dislocation behavior, 713
edge, 304–306, 309, 313–314, 316, 319, 347–348, 370, 374, 443, 639–642, 645
energy, 337, 377, 450
experimental observation of, 308
force required to bow a dislocation, 321
forest, 346–347, 357
Frank–Read source, 343–345, 401, 447, 764
Frank's rule, 338
Frenekel defects, 291
glassy silica, 222
glide, 295, 323, 332, 354, 430, 433, 439, 441, 444, 452, 481, 536, 545, 764, 767, 770
helical, 40, 51, 53, 56, 100–101, 307, 586

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

interfacial, 656
jogs, 295, 297, 347, 350, 415
Kear–Wilsdorf, 716–717, 724
Lomer–Cottrell lock, 328, 330, 445
loops, 309, 311, 445, 545, 659
prismatic loop, 311, 544
misfit, 360
molecular beam epitaxy, 339
ordered intermetallics, in, 714
Orowan's equation, 348
Peach–Koehler equation, 321–322, 326, 353, 642
Peierls–Nabarro stress, 337, 351–354, 357, 427, 671, 691, 763
pileup, 346, 400
precipitate interaction, 659
screw, 295, 304, 306, 311, 314–315, 317, 319, 321, 343, 347–348, 548, 550, 639, 643, 717
sessile, 328
Shockley partials, 331, 333
stress fields, 77, 314
tangles, 441, 767
velocity, 357
dislocation(s)
Gilman model, 222
dispersion strengthening, 637
divacancy, 294
DNA, 15, 49, 156–157
DNA molecule, 157
dual-phase steels, 672
ductile material(s), 482, 506–507, 513, 535–536, 540, 613, 833
ductile–brittle transition temperature, 230, 547, 551, 600, 602

earing, 261
edge dislocation. *See* dislocation
effect of mean stress
Gerber, 819
Goodman, 819
Soderberg, 819
effective displacement energy, 298
effective stress, 227, 771, 849
elastic compliance matrix, 111, 134
elastic constants and bonding, 163
elastic interaction, 639, 642
elastic matrix
cubic system, 109
elastic modulus
biaxial, 161
elastic properties
biological materials, 150
ceramics, 125
materials, 125
metals, 125
polycrystals, 119
polymers, 132
elastic stiffness matrix, 112
elasticity, xvii, xix, 77, 88, 94, 129, 132–133, 142, 146–147, 150–151, 163, 273, 276, 315, 322, 375, 462, 472, 478, 485, 490, 614, 642, 888
anisotropic, 114, 261, 717
electronic materials, 160
rubber, 141
elastin, 51, 58, 151, 204, 274
elastomer, 141, 143, 145–147, 149, 583–584, 586, 942, 944
electromigration, 791
electron backscattered diffraction (EBSD), 384
electronic materials, xvii, xix, 68
engineering stress–strain curves, 196, 207, 209, 211, 426
environmental effects, xix, 193, 553, 725, 728, 849, 921, 939–941, 944
Erichsen test, 259
Euler buckling, 266, 268

failure criteria, xix, 225, 231, 238, 241
failure modes in composites, 900
fatigue
biomaterials, 845
crack closure, 849–850
crack nucleation, 720, 824, 827
crack propagation, 829, 832, 859
cumulative damage, 820
cycles to failure, 720, 813–814, 836, 854, 861, 869
damage, 821–822, 845, 861
discontinuous crack growth, 833
effect of frequency, 820
environmental effects, 849
extrusions and intrusions, 720, 827
hysteretic heating, 847
intrinsic and extrinsic factors, 845
life, 814
Basquin relationship, 812, 814, 817
Manson–Coffin, 816–817
life exhaustion, 820
linear elastic fracture mechanics, 834
mean stress, effect of, 818–819
mechanisms, 824
Palmgren–Miner rule, 822–824
parameters, 812
Paris–Erdogan equation, 836–838, 842, 844, 846–847, 859
persistent slip bands, 825–826
residual stress, effect of, 829
short crack problem, 852
shot peening, 828–829
S–N (Wöhler) curves, 720, 812, 814–815, 817, 844, 846, 853
strength, 814, 816–817, 819, 828, 843
striations, 535, 830–831, 833–834
testing, 853
two-parameter approach, 850
fatigue testing
conventional, 853
rotating bending, 854
servohydraulic machine, 857
ferroelectrics, 62
flexure, 60, 518, 599, 614–615, 621, 700, 844
flexure test, 614–616
flow criteria, 196, 200, 226, 229
flow stress, 69, 187, 192, 200, 202, 204, 212, 225–227, 230, 250, 252, 254, 300, 342, 356–357, 398, 402, 405–406, 410, 425, 428, 441, 443, 445, 447, 475–476, 534, 648–649, 662, 718–719, 721, 723, 740, 796
fluidity, 136
foam, 46, 48, 132, 711, 730–732, 736–737, 743
aluminum foam, 48–49, 729–731
syntactic foam, 736
focuson, 298
forging, 187, 424, 451
formability, 259, 262–263, 265, 671–672
forming-limit curves, 260, 263, 266
Keeler–Goodwin diagrams, 262–263, 266
four-point bending, 616–617

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

fracture
biological materials, 586
brittle, 309, 483, 533, 547, 576–577, 579, 600–601, 604, 606, 719
ceramics, in, 554, 563, 566, 572
cleavage, 66, 286, 289, 466–468, 532, 547–552, 600, 602, 696, 838
ductile, 532–534, 538, 541–544, 547, 550, 553
environmentally assisted, 559, 926
Griffith criterion, 469, 482, 568, 935
intergranular, 532, 550, 601, 725, 833
mechanism maps, 591
mechanisms and morphologies, 533, 586
metals, in, 534, 926
modes, 485, 532, 833
polymers, in, 575, 939
fracture mechanism maps
Weertman–Ashby maps, 591
fracture toughness
biological materials, 586
ceramics, 621, 703, 890
composites, 900
high entropy alloys, 675
intermetallics, 724
metals, 673
parameters, 497, 507–508
polymers, 582
fracture toughness tests, 463, 606, 609, 624, 626
chevron notch test, 621
double cantilever beam test, 561
double torsion test, 561, 621
indentation test, 624, 626
J-integral test, 613
plane strain fracture toughness tests, 606
free volume, 235–237, 941
Frenkel defects, 290
friction hill, 212
Fukui test, 259–260
functionally graded materials, 907

geometry of deformation, 424, 455
GLARE. *See* composites
glass
plastic deformation, 219, 222
specific volume, 27, 643
structure, 27, 945
temperature dependence and viscosity, 222
glass transition temperature, 3, 28–29, 132, 136, 218, 220, 223, 576, 746, 782, 786, 788, 848, 940–941
glassy polymers, 27, 216, 237, 535, 575, 577, 584, 785, 942
graft copolymer, 30
grain boundary
ASTM grain size, 372
coincidence site lattice, xvii, 383
energy, 383
ledge, 384
mean lineal intercept method, 371–372
packing of polyhedral units, 386
sliding, 396
tilt, 375–377, 380, 387
triple junctions, 383
twist, 40, 52, 375, 586
grain boundary dislocation, 402
grain size
Hall–Petch equation, 398, 400, 402–403, 405, 407, 409–410, 548, 551–552, 562, 602, 667, 671, 689, 719–720, 887
Li's theory, 402
strengthening, 667
Griffith failure criterion, 233

habit plane, 688, 696–697
hardness
Brinell, 243–246, 248
Knoop, 251–252, 626
microindentation, 242, 250–251, 285, 562
nanoindentation, xix, 242–243, 257–258
Rockwell, 244–249, 689, 958
Vickers (or diamond pyramid), 243–244, 247–249, 251–252, 254, 285, 624–626
Harper–Dorn. *See* creep
heat-resistant materials, 775
high-entropy alloys, xvii, 673, 676
high-strength low alloy (HSLA) steel, 666–667, 672
Hooke's law
generalized, 93–94, 96, 117, 161, 316, 358, 888
hot working, 424
hydride formation, 936
hydrigen damage
theories, 932
hydrogen damage
metals, 931
hydroxyapatite, 42, 49–50, 275
hysteresis, 43, 80, 151, 847, 858

idealized stress–strain curves, 695
impact testing, 598–599
imperfections in polymers, 414
imperfections, point and line defects, 286
implants, 4, 6, 46, 846, 911
Inconel, 648–649, 674–675, 911
independent slip systems, 349, 396, 440, 725
Inglis equation, 470, 473, 480
instrumented Charpy impact test, 604
interfaces in composites, 875–876
interfacial bonding, 543, 877
interfacial defects, 369
interlaminar shear strength test, 618
intermetallic
compounds, 566, 662, 713, 728
intermetallics
composite route, 727
ductility, 724
effect of ordering on mechanical properties, 717
environmental effects, 728
gold-based, 711
ordered, 711, 714, 721, 724–725, 728
dislocation structure, 714
ductility, 725
environmental effects, 728
fatigue, 720
Hall–Petch, 719
macroalloying, 725, 727
microalloying, 666, 725
pesting, 712, 714, 948
internal friction, 649–650
internal obstacles, 405
interstitial point defect, 415
interstitial solid solution, 637
interstitials, 293–295, 299–301, 348, 642, 649–650, 765

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

ion implantation, 302–303
irradiation, 296, 299–301, 415, 553
isotactic polymer, 31, 415
isotropic hardening, 230
Izod test, 599, 602, 958

J_2 criterion, 229
J-integral, 612
jogs. *See* dislocations
Johnson–Cook equation, 192, 396
Johnston–Gilman equation, 357

Kear–Wilsdorf. *See* dislocation(s)
Keeler–Goodwin diagrams. *See* formability
keratin, 42, 46, 48–49, 51, 58, 742
kinematic hardening, 214, 231
kinks. *See* dislocation(s)
knock-on, 299

ladder polymer, 30
laminated composites. *See* composites
Larson–Miller parameter. *See* creep
lath, 684–686
ledges. *See* grain boundary
limiting draw ratio, 260
line defects. *See* dislocation(s)
line tension. *See* dislocation(s)
lineal intercept, 371–372
linear elastic fracture mechanics
  applied to fatigue, 834
linear elastic fracture mechanics (LEFM), 462
linear polymer, 30, 132–133, 415
linear polymers, 30, 32
liquid crystal(s)
  cholesteric, 39
  director, 39
  mesophase, 39
  nematic, 39
  order, 40
  smectic, 39–40
  thermotropic, 39
liquid metal embrittlement, 462, 928, 938
logarithmic decrement, 140, 650
Lomer–Cottrell. *See* dislocation
loss tangent, 140
low-cycle fatigue tests, 858
Lüders band, 263, 646
Ludwik–Hollomon equation, 191–194, 202

magnetic hard disk, 64
martensite
  acicular, 686–687
  ceramics, in, 703
  habit plane, 688
  lath, 685
  lenticular, 684–685, 704, 706–707
  mechanical effects, 688, 692
  microcrack generation, 696
  morphologies, 682
  strain-induced, 695
  stress-assisted, 695–696
  structure, 682
  twinned, 685, 687, 691
maximum distortion energy criterion, 227
maximum shear stress criterion, 226
maximum stress criterion, 226
maxwell model. *See* creep
McClintock–Walsh criterion, 231, 233, 235
metallic glass, 29, 219–221, 223, 511, 820
  microscopic deformation, 221
  shear bands, 221
metals
  elastic properties, 125
Meyers–Ashworth theory, 403
microalloyed steels, 666
Miller indices, 13
Möhr circle, xix, 77, 98–99, 101, 103, 231
Möhr–Coulomb failure criterion, 231, 242
molecular weight, 35–37, 414–415, 581, 785, 788–789, 842–843, 939–940, 942
monolithic $MoSi_2$, 713
Mooney–Rivlin equation, 147–148
muscle, 43, 49, 52, 56, 58, 151, 268–270
muscle force, 268
myosin, 51, 56–57

nanocrystalline materials, 408–409
nanoindentation, 254
nanotechnology, 64, 67
nanotubes, 65
necking
  Bridgman's correction, 200
  correction factors, 201

NiTiNOL, 697
Nix–Arzt equation, 792

octahedral sites, 291, 336, 649, 724
Olsen test, 259
Orowan equation, 350, 661
Orowan model, 660
orthotropic, 109, 113, 132, 134, 238–239, 241, 888
oxidation
  ceramics, 948
  metals, 925
  polymers, 941

Palmgren–Miner rule. *See* fatigue
Paris–Erdogan equation. *See* fatigue
particle flattening, 739, 741
Patel–Cohen equation, 698
Peach–Koehler equation. *See* dislocation(s)
Peierls–Nabarro stress. *See* dislocation, persistent slip bands
pileup. *See* dislocation
plastic deformation
  compression, in, 210
  glasses, 222
  polymers, of, 214
  tension, in, 562, 795
plastic zone, 490–494, 500, 503, 506, 608, 620, 830, 833, 835, 849, 927, 935–936
plastic zone size, 506
point defects, 66, 286, 290, 292, 295, 297, 299, 415, 449, 638, 690, 924
Poisson's ratio, 83, 88, 91–93, 95, 105, 113–114, 128, 131, 159, 161–162, 185, 195, 219, 257, 472, 629, 882, 886, 889, 905, 957
pole figure, 454
polycrystals
  elastic constants, 105
  elastic properties, 125
  Hill's formulation of elastic constants, 119
polyehtylene
  neck propagation, 217
polyethylene, 6, 26, 30, 32, 35–36, 46, 72, 217–218, 414, 416, 577, 873, 879, 940, 943
  bonding angle, 26

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

polygonization, 445
polymer types
  glassy, 216, 237
  isotactic, 31, 415
  lamellar, 33
  spherulitic, 34
  syndiotactic, 31, 415
  tacticity, 31
polymers
  atactic, 31
  block copolymers, 703
  branched, 30
  cross-linked, 30, 32, 58, 141–142, 147, 576–577, 582, 873, 940,
  defects, 415
  graft copolymers, 30–31
  isotactic, 31, 415
  ladder, 30
  linear, 30
  plastic deformation, 214
  random copolymer, 30
  semicrystalline, 216–217, 414–415, 535, 579, 581, 842
  syndiotactic, 31
  thermoplastic, 218, 503, 842, 848, 873–874, 890, 943
  thermoset, 576, 582, 873–874, 890, 940
polypeptide, 51, 53
  alpha helix, 53
  beta sheets, 51
porous materials, 737
post-yield fracture mechanics, 510
precipitate particles, 655, 659, 661–662, 665, 668
precipitates at grain boundaries, 650
precipitation hardening, 424, 652, 818
principle of superposition, 85
prismatic loop, 311, 314, 544
production of point defects, 294
prostheses, 5–6, 846–847
proteins, 49, 51, 56, 59, 64, 153, 579
pseudoelasticity, 697
punch-stretch tests, 262
pure shear, 95, 103, 105, 237, 639

quasicrystals, 38

R curve, 506–507, 559, 588, 845
radiation damage, 298–299, 415, 925, 942
radiation effects, 338
Rankine criterion, 226, 229
reinforcements, 65, 875–876
residual stress, 153, 625, 628, 890
resilience, 197
resilin, 58, 274
Reuss average, 121
rubber elasticity, 147

Salganik equation, 131
sandwich structure, 42, 731
Schmid factor, 432–434, 437–438, 448–449
Schmid law, 251, 432
Schottky defects, 290–291
second-rank tensor, 105
Seeger cascade, 296
Seeger model of irradiation damage, 299
Seeger theory, 351
semicrystalline polymers, 216, 414, 576
sensitization, 924
serrated stress–strain curve, 648
servohydraulic testing machine, 857
sessile dislocation, 330
shape memory effect, 61
shear
  banding, 534
  coupling, 906
  deformation, 136, 436, 577, 893
  modulus, 82, 88, 113, 120, 135, 140, 191, 219, 288, 337, 354, 395, 524, 662, 671, 690, 734, 749, 882, 889, 896, 905
  pure, 103
  yielding, 216, 237, 577, 579, 584, 943
SiC whisker, 67, 798
silicides, 711
silicon carbide, 3, 116, 129, 870, 874–875, 879, 886, 890, 892, 909, 914, 948
silk, 59, 274
single crystal blade, 779
skin, 1, 9–10, 49, 53, 57, 61, 100, 159–160, 273, 731, 909
slip
  bands, 303, 401, 535–537, 830
  conjugate, 438, 833
  cross, 344–345, 440
  direction, 322, 332, 389, 430, 436, 716
  lines, 221, 438–439
  markings, 332, 439
  planes, 254, 295, 328, 332, 346, 354, 432–433, 452, 534, 661–662, 717, 830, 833
  primary, 438, 723
  system, 336
  systems, 251, 334, 347, 436–438, 440, 452
Snoek effect, 649, 691
softening mechanisms, 448
softening point, 224
solid metal embrittlement, 926, 938
solid solution strengthening
  interstitial solid solution, 637
solid sulition strengthening
  elastic Interaction, 639
solid sulution strengthening
  interstitial solid solution, 637
spinodal decomposition, 657, 684, 691
sponge spicule, 60
stacking fault, 325, 327–328, 440, 716
stainless steel, 4, 198, 200, 211, 301, 328, 402, 542, 551, 686–687, 695, 723–724, 755, 767–768, 801, 829, 924, 926–927, 929
statistical analysis, 512
stereographic projections, 428
stiffness, xvii, 7, 33, 35, 41, 43, 46, 62, 105–106, 108, 110, 112–113, 119, 134, 156, 162, 170, 172, 174–177, 185, 197, 207, 257, 268, 275–276, 579, 590, 651, 727, 850, 877, 885, 888, 908, 914
storage modulus, 139–140
strain
  engineering, 164, 212, 427
  plane, 95, 187, 252, 465, 479, 483, 488, 492, 500, 507–508, 510, 606, 608, 620, 840, 882
  point, 646
  rate, 136, 191–193, 197, 200, 202–203, 215, 218, 223, 236, 259, 269, 276–277, 285, 309, 350–351, 354, 356, 393, 395, 509, 546–547, 563, 581, 584, 586, 598, 600, 603, 611, 646, 648, 650, 750, 760, 762, 764, 766, 770–772, 790, 793–796, 798, 803, 806

© in this web service Cambridge University Press & Assessment www.cambridge.org

CAMBRIDGE

Cambridge University Press & Assessment
978-1-108-83790-3 — Mechanical Behavior of Materials 3rd Edition
Marc A. Meyers , Krishan K. Chawla
Index
More Information

shear, 85, 89, 103, 221–223, 288, 313, 322, 349–351, 389, 437, 443, 448, 451, 555, 692–693, 697, 699–700, 706, 766, 794, 826, 896, 906
true, 79, 189, 197, 200, 208
strain aging, 647–648, 672
strength of martensite, 688, 691
strength of real materials, 66
stress
compressive, 78, 102, 117, 211–212, 236, 275–276, 472, 555, 568–569, 571, 614, 639, 693, 732, 778, 829
concentration, 340, 342, 400–401, 405, 410, 469–472, 482, 488, 534–537, 541, 554–555, 561, 565, 587, 646–647, 657, 830, 890, 927
engineering, 80, 196, 205, 207, 209, 211, 427, 747, 751–752
hydrostatic, 94, 117, 226–227, 235–237, 641, 692, 740, 799, 932
linear, 239
nominal, 491
plane, 94, 161, 238–239, 262, 476–477, 479, 483, 495, 500, 502, 507, 509–510, 608
tensile, 78, 84, 102, 146–147, 166, 190, 197, 216, 233, 253, 433, 448, 469, 472, 485, 487, 499, 515, 519, 556, 562–563, 566, 568, 613, 618, 620, 639, 645, 648, 693, 745, 799, 818, 829–830, 849, 890, 895, 901, 906, 927, 933, 944
true, 80, 146, 189–190, 196, 208, 211, 748, 816, 818
uniaxial, 83, 86, 93–94, 190, 200, 225, 227, 236, 430, 547
stress concentration factor, 469
stress corrosion cracking (SCC), 926
stress required for slip, 430
stress singularity at crack tip, 522
stress–strain curve, 197, 199, 698
stretching, 80, 143–144, 147, 149, 157, 214, 218, 258–260, 265
structural design elements, xvii, 41, 43
subgrains, 369, 445
superalloys, 650, 652, 665, 674–675, 745–746, 752, 762, 775–776, 778–779, 793, 911
surface energy, 286, 299, 411, 466, 468, 476–479, 482, 564, 663, 665, 935, 938, 943, 947
swelling, 301, 921, 925, 939–941
Swift test, 259

Taylor–Orowan, 349
tendon, 9, 54, 56, 271–272
tetragonal distortion, 640
tetrahedral sites, 291
texture, 81–82, 261, 388, 398, 445, 452–454
texture strengthening, 452
theoretical shear strength, 67, 287, 770
theoretical tensile strength, 465
thermal barrier coating, 779
thermal stress, 828, 889
thermal stresses, 558, 572, 876
thin films, 63, 160, 339, 344, 357, 627
tissue, 5–6, 9, 46, 57, 153, 156, 701, 939
torsion, 87, 101, 140, 174, 187–188, 230, 236, 430, 621
toucan beak, 46, 49, 58, 743
toughness
particle toughening, 890
transformation toughening, 890
transformation-induced plasticity (TRIP), 683, 695
tridimensional defects, 411
TRIP steel, 671, 695
turbine, 22, 68, 730, 770, 775, 778–780, 909
twin boundary, 327–328, 379, 383
twinning, 35, 192, 220, 380, 388–395, 399, 406, 455, 548, 571, 648, 671, 673, 685, 687

uniform strain, 197, 200, 205, 207, 209, 259, 720

vacancy loops, 314
viscoelastic polymer, 782, 786
viscosity, 28, 36, 61, 136–137, 218, 222–224, 746, 783, 794, 848
Vitalium, 6
void
octahedral, 292
tetrahedral, 292
Voigt average, 119, 130
volumetric defects, 369
volumetric strain, 555
von Mises criterion, 230–231, 235, 237, 242, 725

Wachtman–MacKenzie equation, 126
waves, 77, 82, 304, 357, 811
Weibull distribution, 513, 517, 864, 907
Weibull modulus, 515, 517–518, 566, 617, 907, 957
whiskers, 66–67, 417, 534, 797, 873–874, 886–887, 891
Wigner effect, 296
Williams, Landel, and Ferry (WLF) equation, 788
wire drawing, 201, 261, 406, 452
Wöhler curves, 812
work hardening, 77, 198, 443, 671–672, 829

yield criteria, 228, 242, 259
Young's modulus, 43, 81–82, 86, 88, 95, 113–114, 119–120, 123–126, 130–131, 147, 159, 161–162, 164, 167, 169–170, 172, 175, 205–207, 209, 219, 267–268, 274–275, 355, 408, 413, 425, 427, 448, 452, 466, 468, 503, 507, 534, 614, 625, 628, 731, 734, 783, 880–882, 884–885, 887–888, 905, 957–958

Zachariasen model, 27, 221
Zener anisotropy ratio, 110
Zerilli–Armstrong, 193
Zircaloy, 301, 774, 780, 807
zirconia-toughened alumina (ZTA), 704

© in this web service Cambridge University Press & Assessment www.cambridge.org