

Index

- !, 26, 38
- !=, 38
- .RData, 48
- :, 14
- ::, 28
- <, 38
- <-, 9
- <=, 38
- =, 9
- ==, 38
- >, 38
- >=, 38
- ?, 29
- ??, 30
- ???, 31
- #, 8, 115
- %*%, 205
- %/%, 9
- %>%, 113
- %%, 8
- &, 38
- &&, 38
- ^, 8
- \n, 128
- |, 38
- |>, 114
- ||, 38

- abline(), 68
- abs(), 105
- aes(), 72
- aesthetics, 72, 75
- annuity, 108
- any(), 101
- apply(), 174, 219

- argument list, 12
- arguments, 12, 109
- array, 20
- arrows(), 68
- as.character(), 63
- as.integer(), 19
- attributes, 113
- axis(), 251

- backsolve(), 213
- bar charts, 54
- barplot(), 54, 56
- base, 25, 27
- base graphics, 53
- base packages, 28
- Bayes' theorem, 179
- Bayesian, 188
- Bernoulli trial, 156
- bias, 150
- binary, 22
- bisection algorithm, 107
- body, 109
- Boolean algebra, 37
- boot, 241
- box(), 251
- box-and-whisker plot, 60
- boxplot, 60
- boxplot(), 60
- branch and bound algorithm, 240
- break, 106
- breakpoint, 130
- browser(), 130
- bugs, 125

- c(), 13
- camel case, 117

- case-by-variable format, 40
- case-sensitive, 13
- cat(), 128
- catastrophic loss of precision, 24
- cbind(), 198
- central limit theorem, 151
- chol(), 212
- chol2inv(), 213
- chron, 25, 27
- class(), 113
- column vectors, 197
- column-major, 20
- concatenation, 14, 18
- condition number, 221
- conditioning scatterplots, 87
- confidence interval, 151
- Console Pane, 5
- constrOptim(), 231
- continuous, 248
- contour(), 229
- CRAN, 4, 28
- crossprod(), 206

- data frame, 40
- data.frame(), 43
- dates and times, 25
- dbinom(), 158
- debug(), 130
- debugging, 125
- debugonce(), 130
- declarative programming style, 93
- decomposition
 - Choleski, 212
 - LU, 207

- QR, 214
 - singular value, 211, 218
- default value, 12
- `det()`, 202
- determinant, 202
- `dexp()`, 166
- `diag()`, 202, 203
- `dim()`, 41, 202
- dimension, 41
- discrete, 248
- distribution, 248
 - Bernoulli, 157
 - beta, 172
 - binomial, 157, 158, 173, 179, 249
 - Cauchy, 172
 - chi-square, 172
 - exponential, 166, 172, 249
 - F, 172
 - gamma, 172
 - geometric, 173
 - hypergeometric, 173
 - logistic, 172
 - lognormal, 172
 - negative binomial, 173
 - normal, 151, 168, 172, 249
 - Poisson, 162, 173, 249
 - Student's *t*, 172
 - uniform, 151, 153, 156, 167, 172, 249
 - Weibull, 172
- distribution function, 248
- `dnorm()`, 169
- dot charts, 54
- `dotchart()`, 55
- `dpois()`, 162
- `dump()`, 47
- edge cases, 126
- `eigen()`, 210
- environment, 110
- Eratosthenes, 100, 109
- `example()`, 30
- expected value, 249
- `factor()`, 18
- factorial, 94
- FALSE, 37
- Fibonacci sequence, 96, 223
- Files Pane, 46
- fixed-point problem, 97
- floating point, 22
- `for()`, 93
- `format()`, 25, 253
- `forwardsolve()`, 213
- Freedman–Diaconis rule, 59
- function header, 109
- functional programs, 93
- functions, 12, 108
 - generic functions, 113
 - `geom_bar()`, 75, 80
 - `geom_col()`, 72, 75, 76
 - `geom_histogram()`, 80, 85, 86
 - `geom_line()`, 75, 76
 - `geom_point()`, 75, 76, 85
 - `ggplot()`, 71
 - `ggplot2`, 70–86
 - `ggplotly()`, 89
 - global environment, 9
 - golden ratio, 223
 - golden section search, 222
 - graphical parameters, 255
 - graphics, 28
 - grid, 53, 87, 97
 - `grid.circle()`, 97
 - `grid.rect()`, 88
 - grobs, 88
 - `help()`, 29
 - `help.search()`, 30
 - `help.start()`, 30
 - Hilbert matrix, 198
 - `hist()`, 58
 - histograms, 58
 - Horner's rule, 137
 - IDE, 3
 - `if()`, 99
 - imperative programming style, 93
 - importance sampling, 186
 - indices, 14
 - logical, 26, 38
 - negative, 15
 - zero, 15
 - Inf, 26
 - `install.packages()`, 28
 - integer, 24
 - integer programming, 240
 - integrated development environment, 3
 - interior point methods, 241
 - interquartile range, 60
 - invariant distribution, 175
 - `invisible()`, 113
 - IQR, 60
 - `is.na()`, 26, 127
 - `ISODATE()`, 25
 - `ISODATETIME()`, 25
 - `jitter()`, 165
 - `jpeg()`, 255
 - `kappa()`, 221
 - knitr, xv, xvii, 4, 27
 - `kronecker()`, 219
 - L, 25
 - LAPACK, 198
 - `lapply()`, 45
 - lattice, 53, 87
 - law of large numbers, 150, 177, 178
 - leaflet, 89
 - `legend()`, 68
 - `levels()`, 19
 - library, 28
 - linear operations, 197
 - linear programming, 231
 - `lines()`, 68
 - linprog, 241
 - `list()`, 45, 195
 - `load()`, 48
 - logical vectors, 99
 - `lower.tri()`, 203
 - `lp()`, 234
 - `lpSolve`, 234
 - `ls()`, 13
 - `magrittr`, 113, 131
 - Markdown, 35
 - Markov chain, 175, 201
 - Markov chain Monte Carlo, 175
 - matrix inverse, 207
 - matrix multiplication, 197
 - `matrix()`, 20, 198
 - maximization, 222

- MCMC, 175, 187
- mean(), 23
- median(), 34
- methods, 113
- Metropolis algorithm, 188
- Metropolis–Hastings algorithm, 188
- microbenchmark(), 135
- minimization, 222
- Monte Carlo, 150
- MPV, 253
- mtext(), 251

- NA, 25
- namespace, 112
- NaN, 26
- ncol(), 41
- Nelder–Mead simplex algorithm, 227
- Newton’s method, 104
- Newton–Raphson, vii, xiii, 225
- next, 106
- nlm(), 231
- nlminb(), 231
- non-conformable, 205
- nrow(), 41
- numeric(), 15

- object oriented, 93, 112
- objects(), 13
- one-pass formula, 24
- open source, 3
- optim(), 231
- optimize(), 231
- optional parameters, 17
- outer(), 218

- p*-value, 150
- package, 27, 112
 - base, 28
 - contributed, 28
- palette, 68, 77, 78
- panes, 5
- par(), 64, 255
- paste(), 18
- paste0(), 18
- pbinom(), 158
- pdf(), 255
- pexp(), 166
- pie charts, 57
- pie(), 58
- pipe operator, 113
- plot margins, 251
- plot region, 251
- plot(), 61
- plot3d(), 95
- plotly, 89
- plotting character, 63
- png(), 255
- pnorm(), 169
- points(), 68
- Poisson process, 163, 167
- polygon(), 68
- posterior distribution, 190
- postscript(), 255
- ppois(), 162
- precision, 22
- prime numbers, 100
- print(), 128
- prior distribution, 189
- probability density function, 248
- procedural programs, 93
- profiling, 136
- pseudorandom, 151
- pushViewport(), 88, 97

- q(), 10
- qbinom(), 158
- qexp(), 166
- qnorm(), 169
- qpois(), 162
- QQ plots, 64
- qqline(), 165
- qqnorm(), 165
- qqplot(), 66
- qr(), 214
- qr.solve(), 209
- quadprog, 243
- quadratic programming, 241
- quantile, 249
- quantile-quantile plots, 64
- quitting, 10

- R Markdown, 35
- random variable, 248
- rbind(), 198
- rbinom(), 158
- RColorBrewer, 68
- read.table, 49
- recursion, 121
- recycling, 16
- rejection sampling, 180
- relational operators, 99
- rep(), 17
- repeat, 106
- replicate(), 114, 160
- repository, 28
- return(), 110
- rexp(), 167
- rgl, 89, 95
- rm(), 48
- rnorm(), 169
- rounding error, 23
- row-major, 20
- rpois(), 162
- Rprof(), 136
- RSiteSearch(), 31
- RStudio, xvii, 3, 5, 10, 14, 28, 30, 46, 89, 115, 129
- rstudio.com, 5
- runif(), 153

- S3 methods, 112
- sample variance, 23
- sample(), 17, 155
- save.image(), 48
- scatterplot, 61
- scope, 111
- Scott rule, 59
- segments(), 68
- seq(), 17
- set.seed(), 154
- setup, 4
- setwd(), 13, 46
- short-circuit evaluation, 38
- silver ratio, 223
- simplex method, 234
- simplex(), 241
- sink(), 48
- solve(), 209
- solveLP(), 241
- sos, 31
- Source Pane, 5
- source(), 47
- square root, 39
- stats, 28
- stochastic matrix, 201

260 | INDEX

- `str()`, 42
- `strptime()`, 25
- Sturges rule, 59
- subscripts, *see* indices
- `substr()`, 18
- `substring()`, 18
- `svd()`, 212
- `symbols()`, 68
- `system.time()`, 135
- systems of linear equations, 197

- `t()`, 203
- `table()`, 157

- task views, 28
- `text()`, 68
- tibble, 40
- times and dates, 25
- `title()`, 251
- top-down design, 120
- `traceback()`, 128
- transparency, 75, 76, 91
- TRUE, 37

- unboundedness, 238
- `unique()`, 63
- `upper.tri()`, 203

- `vapply()`, 45
- `var()`, 23
- vector spaces, 197
- `viewport()`, 88, 97
- viewports, 88
- visual perception, 67

- `weighted.mean`, 186
- `while()`, 102, 185
- `with()`, 42
- working directory, 13
- workspace, 9, 10