

Index

- Accidental flooding, 264–265, 470
- Accidental limit state, 25, 53, 162, 262, 380, 470
- Aged structure, 211, 255, 447
- Aircraft impact, 347–349
- ALPS/HULL, 39–40, 46, 216, 237–241, 256
- ALPS/SPINE, 226, 233
- ALPS/ULSAP, 216, 220, 223, 228
- Annual surveys (AS), 457
- ANSYS AQWA, 393
- Average zero-up-crossing wave period, 89–90, 114–126, 153–154, 509
- Ballasting material, 327, 347, 349, 353, 363, 371
- Boeing 777 aeroplane, 350–352, 354, 357, 367–372
- Brittle, 49
- Brittle behaviour, 278
- Brittle fracture, 49–50, 57, 215, 247–254, 259
- Brittle material, 49, 244–245, 354
- Buckling coefficient, 69–70, 171
- Buckling strength, 68–70, 170
- Cathodic protection, 17, 193–194, 206, 402, 433, 435, 439–440
- Charpy V-notch, 50–51
- Chemical inhibitor, 433
- Close-up visual inspection, 15, 445, 456
- Coating life, 256, 415, 438–439, 452
- Coating material, 437
- Coefficient of variation (COV), 413
- Cold temperature, 55–56
- Collision, 265–279
- Comparative approach, 19
- Computational fluid dynamics (CFD), 86, 172, 251, 281, 309, 379, 393
- Consequence, 162, 172, 184, 187, 195, 262–263, 375–380, 390, 393, 395, 452–456, 461, 488, 496
- Construction, xv–xvi, 6, 10–15, 20–24, 27–28, 30, 49, 62–63, 67, 72, 74, 78, 100, 104, 183–184, 189, 199, 376, 433–434, 445, 461, 472, 477, 483
- Convection, 251–252, 378
- Conversion, 5, 10–19, 21, 23, 29–30
- Corrosion assessment, 400–401, 409
- Corrosion depth, 414–416, 419, 430, 473
- Corrosion management, 49, 401, 433, 437
- Corrosion margin, 16, 101, 256, 401, 433, 445, 458
- Corrosion wastage, 14–15, 26, 62, 162, 217, 255–256, 400–403, 406, 408, 411–414, 417, 440, 445, 447, 449–450, 456, 458, 465, 473, 485
- Cost-benefit analysis, 24
- Coulomb–Mohr fracture criterion, 244
- Cowper–Symonds equation, 173, 256
- Crack growth model, 211
- Cracked plate, 465
- Cracking damage, 183, 211, 215, 307, 450, 456, 474–475
- Crashworthiness, 59, 62, 263, 266–268, 270, 274–275, 277, 279, 335, 347, 349–357, 360, 367, 396
- Crevice action, 402
- Cryogenic condition, 4, 49, 244, 248, 307, 374, 448
- Cumulative probability, 147, 510–511
- Current direction, 90, 99, 113, 309–310, 312, 391
- Current speed, 24, 90, 99, 113, 309–310, 312
- Cyclic loading, 183, 254–255
- Damage detection, 452
- Decommissioned ship, 5–6
- Decommissioning, xv–xvi, 5, 81, 215, 297, 376, 445–447, 477–481, 483–485
- Deep-sea mining, 7
- Dented plate, 466–469
- Denting, 15–16, 162, 217, 220, 255, 265, 273, 279–280, 374, 391, 447–448, 452, 456, 465, 473, 475, 485
- Deoxygenation, 433, 440–441
- Detailed engineering, 20, 22
- Digital twin, 377, 484–485
- Direct approach, 19, 307
- Disconnectable mooring system, 112, 297, 301
- Double bottom and double side arrangement, 7, 14, 28, 30–33, 45
- Dropped-object impact, 26, 244, 279
- Dry-docking, 11, 25, 102, 190, 401, 435, 464, 470–472
- Ductile, 49, 57

- Ductile behaviour, 249, 278
 Ductile fracture, 49, 244
 Ductile material, 49, 183, 244
 Ductile model, 277
 Ductile regime, 248
 Ductile-to-brittle fracture, 49, 244, 248
 Dynamic effect, 167, 201, 334
 Dynamic fracture strain, 59–62, 270, 335, 357, 367
 Dynamic ultimate strength, 255
 Dynamic yield stress, 59, 62, 173–174, 270, 357
- Earthquake, 27, 81, 102–103, 327–329, 331–333, 339, 345, 374
 Effective breadth, 165, 232
 Effective length, 221–222
 Effective shear modulus, 222
 Effective width, 165, 220–222
 Elastic deflection limit, 162
 Elastically rotation-restrained, 69
 Elastic–perfectly plastic material model, 54, 247
 Electrochemical action, 402
 Elevated temperature, 54–55, 249, 251, 253, 374, 380, 389
 Emergency response services (ERSs), 470
 Energy absorption, 6, 268, 273, 277, 280, 371, 395
 Engineering stress-engineering strain, 335
 Enhanced survey programme, 438, 457
 Equivalent ratio, 390
 Erosion action, 402
 Event scenario, 144, 377
 Exceedance diagram, 144–147, 149, 197, 377–378, 380, 386–387, 395
 Excessive motion, 178
 Explosion, 10, 22, 26–27, 74, 215, 262, 280, 282–285, 331–332, 345, 374, 447, 470–471, 481–482
 Explosion risk, 389, 391
- FAHTS, 252–253, 281
 Fatigue action, 185–186, 196, 210, 374
 Fatigue cracking, 14–15, 26, 37, 75, 105, 172, 183–184, 186, 211, 220, 255, 438, 447, 452, 456–457, 465, 473, 475–476, 485
 Fatigue damage, 14, 181, 184–185, 192–193, 195–197, 201–202, 205–211, 255
 Fatigue limit state (FLS), 25, 162, 183–186, 190–192, 194–202, 210
 Filling level, 199, 202
 Fire hazard, 378, 381, 472
 Fire risk, 378, 380
 Fire safety, 249–251, 378, 380, 389
 Flux-cored arc welding (FCAW), 62
 Fracture criterion, 244
 Fracture strain, 50, 55–57, 59, 248, 253, 268, 357
 Front-end engineering and design (FEED), 20
 Fuselage model, 350, 367
- Galvanic action, 402, 407
 Gas metal arc welding (GMAW), 63
 General corrosion, 16, 404–407, 421, 474
 Geometric stress, 188–189
 Grade A, 39, 45, 49, 174
 Grade D, 49
 Grade E, 49
 Grade F, 49
 Green water, 9, 18, 24, 26, 83, 104, 106–108, 162, 172, 177–178, 201, 300, 374
 Grooving, 15–16, 400, 403, 406–407, 421, 435
 Gross scantling, 42, 45, 256
- Hazard identification, 376, 379, 461
 H-CSR (harmonized common structural rules), 39–45, 149, 160, 256, 514
 Heading control, 18, 29, 107, 163, 177–178, 288
 Health condition, 401, 445–447, 458, 463, 473, 485
 Health condition assessment, 417, 464–465, 470, 475, 485
 Health condition monitoring, 256, 452–453, 456, 481, 485
 Healthcare, 445–447, 485
 Heat flux, 251–252
 Heat transfer, 251–253, 281, 378–380, 386
 Heeling moment, 175–176, 264
 Helicopter crash, 26, 380, 384–387
 Helicopter deck, 380–381, 386–389
 High-cycle fatigue, 196, 211
 Hindcast data, 95
 Hot-spot stress, 188–204
 Humidity, 26, 81, 100–101, 407–408, 411, 438, 452
 Hydrodynamic added mass, 394
 Hydrodynamic analysis, 93, 104–105, 178
 Hydrodynamic effect, 314
 Hydrodynamic load, 197–198, 200–201, 216, 483, 485
 Hydrodynamic resistance, 279
- Icing, 101
 IFORM (inverse first-order reliability method), 153–154
 Impact loading, 49–50, 57–59, 62, 173, 183, 448
 Impact pressure action, 104–105, 162, 172–173
 Impressed current corrosion-protection (ICCP), 400, 402, 407, 410, 435, 440
 Incremental Galerkin method (IGM), 226, 233
 Initial deflection, 39, 67–68, 224–225, 229–230, 232, 238, 241, 419, 424
 Initial planning, 21
 In-service damage, 15–16, 220, 445–449, 460, 465, 476, 485
 Intact stability, 175–176
 Intelligent supsize finite element method (ISFEM), 39, 46, 237–238
 Intergranular action, 402
 Intermediate survey (IS), 457
 Irregular wave, 89–91, 96, 314, 394

- Johnson–Cook constitutive equation, 278
 Johnson–Holmquist damage model, 245–247
 Johnson–Ostenfeld formulation, 222, 230
 JONSWAP spectrum, 96–98
- KFX, 251–253, 281
 Kinetic energy, 263, 266, 268–269, 273, 277, 279, 347–350, 357, 362, 365–372, 394
- Limit state design and engineering, 26
 LNG power plant, 6
 Longitudinal strength, 18
 Long-term wave statistics, 96
 Loukakis–Chrysostomidis seakeeping table, 158–160
 Low-cycle fatigue, 9, 105, 172, 196–197, 206, 307
 LS-DYNA, 59, 252–253, 269–270, 275, 281, 284, 334, 336–337, 353–354, 357–360, 371, 395
- MAESTRO, 130, 149, 216, 220, 226, 228, 233, 237
 Maintenance, xvi, 11, 14, 17, 35–36, 72–73, 104, 163, 183–184, 187, 265, 289–292, 295, 297, 407, 411–412, 433, 435, 438, 440, 447, 453, 458, 461, 470, 473, 485
 Marine growth, 24, 81, 102, 434, 456
 MCOL, 269
 Mean zero-crossing wave period, 94
 Mechanical damage, 445–452, 475
 Metocean data, 86, 112, 114, 128, 154, 328, 381, 392
 Microbial action, 402, 406, 412
 Modified static-fracture strain, 61–62
- Nautical zone, 114
 Net plate thickness, 16
 Net scantling, 42, 45
 New build, 10, 17, 20–21, 23, 30, 73, 78
 Noise, 37, 163, 179–181
 Nominal stress, 183, 188–189, 191, 194, 202
 Non-destructive examination (NDE), 15, 448, 456
 Notch stress, 188–189
 Nuclear power plant, 6–7, 46, 102, 327, 347–350, 353–355, 357–358, 371
- Ocean environmental condition, 81, 111, 216, 310, 327, 447
 Offshore supply vessel, 392
 Offshore support vessel, 265, 481
 Oil terminal, xv, 4, 327
- Paik–Mansour method, 234
 Paik–Thayamballi empirical formulation, 229
 Permanent set limit, 162
 Permanent-set plate deflection, 172–174, 306
 Persistence time, 88, 90, 105, 159–160, 331–334, 339, 343, 465
 Phase angle, 130
- Pierson–Moskowitz spectrum, 96–97, 205, 394
 Pitting corrosion, 403, 406, 421, 450, 474
 Plasticity correction, 222, 230
 Plate-stiffener combination model, 164–168, 228–231, 237–238
 Plate-stiffener separation model, 164
 Post-buckling regime, 219
 Post-ultimate strength regime, 224–225
 Pre-assembled unit (PAU), 18–19, 72, 74
 Probability of detection (POD), 452, 456
 Process facility, 23, 25
 Progressive collapse, 215, 237–241, 244, 249–251, 380
 Project management, 11, 22, 27–28
- Qualitative approach, 375–376
 Quantitative approach, 375–376
 Quantitative risk assessment and management, 26, 266, 376–377, 391, 481
 Quasi-static action, 105, 162, 172
- Radiation, 251–253, 280, 378
 Regular wave, 88–89, 96, 198, 201, 204
 Remedial action, 438, 453, 464, 470–471, 476, 481, 485
 Renewal criteria for the general corrosion, 16
 Residual strength, 14, 255, 401, 404, 417–421, 423, 437, 447, 465, 475, 485
 Residual stress, 39, 63–66, 68, 70, 183, 191, 229, 238–241, 254–256, 448
 Return period, xvi, 8–9, 18, 24, 83–85, 88–93, 95, 101, 154, 263, 510–513
 Righting moment, 175–176, 264
 Risk mitigation, 101, 262, 264, 350, 375, 391
 Risk-based inspection (RBI), 453, 460
 Rotational restraint, 69–71, 166–167, 173, 216
- Sandwich plate system (SPS), 472
 Sea surface temperature, 24, 81, 100–101
 Seakeeping analysis, 197–201
 Seakeeping table, 158–160
 Serviceability limit state (SLS), 25, 162, 289, 470
 Shakedown, 254–255
 Shear lag effect, 192
 Shielded metal arc welding (SMAW), 62
 Short-term sea state, 156, 205, 210
 Shuttle tanker, 1, 4–33, 36, 38, 265–266, 268–270, 391, 395–397, 460
 Side-by-side collision, 270–273, 391, 395
 Sideways initial deflection, 68
 Significant wave height, 24, 86, 89–91, 94–96, 114–128, 130, 144, 153–156, 159–160, 299, 309, 391
 Single-point mooring, 1, 9, 29, 97, 197, 200, 289–290
 Site-specific metocean data, 112, 128, 154, 310, 328, 332, 381, 392

- Site-specific wave data, 114
 Slamming, 9, 24–25, 30, 83, 106–107, 162, 172,
 177–179, 190, 198, 201, 374
 Sloshing, 9, 19, 27, 83
 Sloshing bulkhead, 105
 Sloshing damage, 104
 Sloshing impact, 25, 105–106, 303–310, 318–321,
 324–325
 Sloshing load, 190, 202, 303, 307–310, 318–321
 Sloshing mitigation option, 303
 Sloshing peak pressure, 310
 Sloshing period, 104, 303
 Sloshing resonance, 105
 Sloshing response, 310, 321–324
 Sloshing scenario, 309–312, 316, 318, 321
 Sloshing simulation, 317–318
 S–N curve, 188–189, 191–195, 197–198,
 205–211
 Snow, 24, 81, 95, 101
 Special periodical survey (SPS), 457
 Spread mooring, 9, 18, 128–130, 147–149, 176,
 178, 200, 288–289, 295–296, 483
 Springing, 179, 198, 201, 374
 Squall, 81
 Stochastic analysis, 197
 Strain rate, 54, 57–59, 62, 173–174, 244–245, 248,
 255–259, 268, 277–278, 335, 357–359
 Stress amplitude, 191
 Stress range, 26, 185, 188, 190–197, 201, 205,
 207–211, 474
 Stress-range transfer function, 201–202
 Structural collapse, 72, 215, 247, 255, 280–282,
 327, 380
 Structural congestion, 282
 Structural details, 183, 186, 188, 190, 193–194,
 196, 198, 202–207, 408, 450, 452
 Sub-zero temperature, 49, 100–101, 248, 268, 412,
 448
 Supply ship (vessel), 26, 30, 81, 102, 265–266,
 268–269, 273–276, 391–397
 Support column, 29, 72, 74, 77–78
 Support stool, 26, 72–73
 Surface degree of pitting intensity (SDOP), 406,
 432
 Surface preparation, 400, 435–436, 438
 Survival condition, 84, 153–154
 Swell, 5, 81, 95–99, 107, 177, 197–200, 205

 Terrorist attack, 27, 265, 347–349, 374
 Thermal buckling, 66, 71
 Thermal conductivity, 252
 Thermal elongation, 252
 Thermal property, 250, 252
 Thermal radiation, 280
 Thermal response, 251
 Tide, 81, 99–100, 392
 Topside flooring, 71, 74
 Topside module, 11, 29–30, 71–77, 103, 201,
 282–285
 Topside support, 76, 186
 Torsion constant, 70
 Torsional rigidity, 69
 Tow condition, 23, 156
 Trading ship, 8, 39, 68, 81, 83, 105, 111, 113, 144,
 149, 156, 158, 160, 174, 179, 310, 433, 435,
 439, 452–453
 Trading tanker, 7–21, 23, 25, 29–30, 35–36, 42,
 45–46, 72–73, 104, 106–107, 178, 185–188,
 196–197, 264, 400, 407–409, 414, 456–458,
 470–473
 True stress-true strain relation, 53–54, 268, 335, 356
 Tsunami, 81, 103–104, 329, 344, 374
 Turret mooring, 18, 126–130, 147–149, 176, 256,
 289, 293–297, 483

 Ultimate limit state (ULS), 25, 53, 111, 162, 183,
 196, 215, 234–237, 244, 306, 327, 417, 422,
 430, 470, 475
 Ultimate strength, 53, 68, 103, 170, 216, 218–225,
 228–231, 234, 237, 249, 255–258, 268, 280,
 300, 306, 356, 401, 417–421, 429, 465–469,
 473–477
 Ultrasonic inspection technique, 403, 456
 Ultrasonic sensor, 449
 Ultrasonic surface-guided wave, 450
 Ultrasonic testing, 450
 Ultrasonic thickness measurement, 15, 458
 Uniform corrosion, 256, 404–406, 421, 462
 USAS-L, 160, 465
 USAS-S, 237–241
 USFOS, 253, 281

 Vibration, 37, 85, 105, 163, 178–181, 198, 296, 482
 Visual examination, 445, 448
 Volumetric degree of pitting intensity (VDOP),
 406
 Vortex-induced vibration, 85, 163, 181, 482
 VUCA (volatile, uncertain, complex and
 ambiguous) environments, 374–376

 Wave energy, 5, 98, 200
 Wave energy spectrum, 93, 96
 Wave heading angle, 90, 114, 130, 144
 Wave height, 24, 83–84, 86, 88–91, 94–96,
 113–128, 130, 144, 153–156, 159–160,
 197–198, 299, 309–310, 391
 Wave period, 5, 24, 86, 88–95, 113–126, 144,
 153–154, 198, 200–201, 309–310, 391
 Wave scenario, 128–144, 147
 Wave spectrum, 96, 98, 205
 Wave steepness, 89–91
 Wave-induced load, 111, 130
 Weathervaning, 18, 29, 76, 95, 97, 106, 126, 128,
 163, 176–178, 197, 200, 290–295

Weld connection, 191, 194, 205	Wind load, 86, 175–176, 190
Weld leg length, 63	Wind rose, 88
Weld metal corrosion, 403, 407	Wind speed, 85–88, 90, 99, 112, 176, 282, 299, 309–310, 312, 379, 381, 391, 394
Weld toe, 188–190, 194, 202–205	
Welding-induced initial imperfection, 39, 46, 65–66, 68, 220	Yield stress, 50, 59, 62, 66–67, 173, 219, 221–222, 229–230, 234–236, 238, 248–249, 253, 256, 268, 419
Wind direction, 86–88, 90, 112, 120–128, 144, 177, 282, 309–310, 312, 379, 381, 391	